TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING API number: 15-065-21,138-0006 52 SZ SE SW SE /4 SEC. 10 , 09 S, 24 W 330 feet from S section line
WICHITA, KANSAS 67202 <u>1320</u> feet from E section line
Operator license# 6861 Lease Nickelson well # E-1
Operator: Ron's Oil Operations, Inc. County Graham Address: R.R. 1 - Boy 194 Well total depth 4085 foot
Address: R.R. 1 - Box 194 Well total depth 4085 feet Penokee, Kansas 67659 Conductor Pipe: 0 inch 0 0 feet Surface pipe 8 5/8 Inch 0 315 feet
Aband. oil well <u>X</u> , Gas well <u></u> , Input well <u></u> , SWD <u></u> , D & A <u></u>
Plugging contractor: <u>Kelso Casing Pulling</u> License# 6050
Address: Chase, Kansas 67524
Company to plug at: Hour: P.M. Day: 20 Month: January Year: 94
Plugging proposal received from: Richard
Company: Kelso Casing Pulling Phone:
Were: Order 250 sxs. 65/35 pozmix - 10% gel - 500# hulls.
Sand and common cement. Allied Cement Company.
STATE OF THE STATE
2-2-94 ¹⁷⁷ 100000
FEB 2 1994
Plugging Proposal Received by: Carl Goodrow
Plugging Proposal Received by: <u>Carl Goodrow</u> Plugging operations attended by agent? All[X], Part[], None [Non
Completed: Hour: 12:30P.M, Day: 20, Month: January, Year: 94
Actual plugging report: 8 5/8" set @ 315' w/275 sxs. cwc. 5 1/2" set @
4081' w/135 sxs. Prod perfs. 3834' - 4012'. P.B.T.D. 4043'. Shot @ 2100' - 1250'. Mix and pump 125 sxs. cement blend displace to 750'.
Shot free at 700' circulate cement to surface with 100 sxs. with hulls
mixed in - lay down 5 1/2" casing - topped off with 25 sxs. cement blend.
mixed in - lay down 5 1/2" casing - topped off with 25 sxs. cement blend. Used total of 250 sxs. cement blend with 500# hulls mixed in.
Used total of 250 sxs. cement blend with 500# hulls mixed in. Plug complete. Bottom sanded back to 3780' with 5 sxs. common cement
Used total of 250 sxs. cement blend with 500# hulls mixed in. Plug complete. Bottom sanded back to 3780' with 5 sxs. common cement on sand with bailer.
Used total of 250 sxs. cement blend with 500# hulls mixed in. Plug complete. Bottom sanded back to 3780' with 5 sxs. common cement on sand with bailer. Remarks:
Used total of 250 sxs. cement blend with 500# hulls mixed in. Plug complete. Bottom sanded back to 3780' with 5 sxs. common cement on sand with bailer. Remarks: Condition of casing(in hole):GOOD / BAD Anhy.plug:YES / NO
Used total of 250 sxs. cement blend with 500# hulls mixed in. Plug complete. Bottom sanded back to 3780' with 5 sxs. common cement on sand with bailer. Remarks: Condition of casing(in hole):GOOD X BAD Anhy.plug:YES X NO Bottom plug(in place):YES X ,CALC ,NO Dakota plug:YES X ,NO
Used total of 250 sxs. cement blend with 500# hulls mixed in. Plug complete. Bottom sanded back to 3780' with 5 sxs. common cement on sand with bailer. Remarks: Condition of casing(in hole):GOOD / BAD Anhy.plug:YES / NO
Used total of 250 sxs. cement blend with 500# hulls mixed in. Plug complete. Bottom sanded back to 3780' with 5 sxs. common cement on sand with bailer. Remarks: Condition of casing(in hole):GOOD BAD Anhy.plug:YES NO Bottom plug(in place):YES CALC ,NO Dakota plug:YES ,NO Plugged through TUBING ,CASING Elevation: 2500 GL