

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-065-21849-00-00  
Spot: SENWNESE Sec/Twnshp/Rge: 15-9S-24W  
2210 feet from S Section Line, 940 feet from E Section Line  
Lease/Unit Name: NICKELSON Well Number: 1  
County: GRAHAM Total Vertical Depth: 4050 feet

Operator License No.: 5205  
Op Name: MID-CONTINENT ENERGY CORP.  
Address: 105 S. BROADWAY, STE 900  
WICHITA, KS 67202

Production Casing Size: 4.5 feet: 4049 w/150 sxs cmt **8/31.63**  
Surface Casing Size: 8.625 feet: 328 w/125 sxs cmt

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 02/12/2003 8:00 AM  
Plug Co. License No.: 5205 Plug Co. Name: MID-CONTINENT ENERGY CORP.  
Proposal Rcvd. from: JERRY PATTERSON Company: MID-CONTINENT ENERGY CORP. Phone: (316) 265-9501

Proposed Plugging Method: Ordered out 300 sxs 60/40 pozmix - 10% gel - 500# hulls.  
Backed off tubing at 3550' and rods at 2122'.

Plugging Proposal Received By: HERB DEINES Witness Type: Plugging Operations Partially Witnessed  
Date/Time Plugging Completed: 02/12/2003 1:00 PM KCC Agent: JAY PFEIFER

Actual Plugging Report:

Perforated casing at 2115' and 1000'.  
TIH with tubing to 2016' and circulated cement with 125 sxs cement and 500# hulls.  
POOH and topped with 15 sxs cement.  
Hooked up to 8 5/8" and pumped 50 sxs cement.  
S.I.P. 100#.

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: TBG

District: 04

Signed \_\_\_\_\_

*Jay Pfeifer*  
(TECHNICIAN)

RECEIVED  
2-19-03  
FEB 19 2003

KCC WICHITA

INVOICED

Form CP-2/3

DATE 2-19-03

INV. NO. 2003061207

FEB 13 2003

MYO-CONTINENT  
 ENERGY CORPORATION  
 120 S. MARKET, #712  
 WICHITA, KS 67202  
 CONTR B & B DRILLING, INC.

REPLACEMENT CARD

#1 NICKELSON

15-9-24W  
 2210' FSL &  
 940' FEL, SE/4

CTY GRAHAM

GEOL \_\_\_\_\_

FIELD HOLLEY SE EXT  
 (1/8 SW)

+	+	+
+	+	+
+	+	+

ELV 2477 KBSPD 12/12/83 CARD ISSUED 2/16/84 IP P 45 BO & 15 BWPD  
 2469 GL LKC 3999-4003

LOG	Tops	Depth/Datum
ANH	2122+	355
B/ANH	2157+	320
HEEB	3774-	1297
LANS	3815-	1338
BKC	4030-	1553
LTD	4049-	1572
RTD	4050-	1573

API 15-065-21,849  
 8 5/8 " 328/125SX; 4 1/2 " 4049/150SX  
 DST (1) 3838-78 (LANS 35' & 50' ZNS) / 30-30-45-60, GB, REC  
 15' FO, 45' OCWM (15% OIL, 35% W), 540' OCW (9% OIL, 91%  
 W, CHL 59,000 PPM), SIP 504-493#, FP 99-197 / 241-329#,  
 BHT 110°  
 DST (2) 3961-79 (SHAW, LKC 160' ZN) / 30-30-37-30, WB, REC  
 5' M, NS, SIP 55-44#, FP 44-44 / 44-44#, BHT 111°  
 DST (3) 3976-4000 (LKC 180' ZN) / TIMES NA, REC 1' FO, 90'  
 SOCWM (1% OIL, 65% M, 34% W, CHL 24,000 PPM), SIP 548-  
 537#, FP 66-77 / 77-88#  
 DST (4) 3987-4050 (LKC 200' ZN) / 60-45-60-45, WB BLDG TO  
 GB, 330' GIP, REC 70' CL GSY OIL, 80' OCM (13% OIL, 80% M,  
 7% W, CHL 10,000 PPM), SIP 1107-1073#, FP 86-105 / 111-  
 288#, BHT 113°  
 MICT - CO, PF (LKC) 3999-4003 W/3 SPF, AC 1,500G, SWB  
 DWN, GSO, POP, P 45 BO & 15 BWPD (GR 32.1°), 2/9/84

INFO RELEASED: 5/3/84 - WAS OIL WELL - TIGHT HOLE