4-<u>0319</u>88 TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 Operator license# 5145

E-16,043API number: 15-065-20, 367 - 0001

(agent)

Form CP-2/3

<u>82 82 8W</u> /4 SEC. <u>32 , 09 S, 23 W</u> 330 feet from S section line 3960 feet from E section line Lease Butcher A well # 2 Operator: <u>Dreiling Oil Company</u> County <u>Graham</u> Address: P.O. Box 550 Well total depth 4040 feet 1008 Cody Avenue Conductor Pipe: 0 inch 0 0 feet Hays, Kansas 67601 Surface pipe 8 5/8 Inch @ 176 feet Aband. oil well ____, Gas well ____, Input well _X_, SWD ____, D & A ____ Plugging contractor: <u>Dreiling Oil Company</u> License# 5145 Address: <u>Hays</u>, <u>Kansas</u> 67601 Company to plug at: Hour: A.M. Day: 5 Month: October Year: 94 Plugging proposal received from: <u>Ivan</u> Company: Dreiling Oil Company Phone: Were: Order 300 sxs. 60/40 pozmix - 10% gel - 500# hulls. Allied Cement Company. Plugged fresh water well with 8 sxs. cement blend. Plugging Proposal Received by: <u>Carl Goodrow</u> Plugging operations attended by agent? All[X], Part[], None[] Completed: Hour: 11:00A.M, Day: 5 , Month: October , Year: 94 Actual plugging report: 8 5/8" set @176'w/135 sxs. 5 1/2" set @4038'w/100 sxs. Prod. perfs 3939' - 3942'. Squeezed and circulated to surface from 2055' w/300 sxs. Squeezed 5 1/2" w/232 sxs. cement blend w/450# hulls mixed in to Max. P.S.I. 800#. Close in P.S.I. 200#. Squeezed 8 5/8" W/60 sxs. cement blend to Max. P.S.I. 300#. Close in P.S.I. 300#. Plug complete. I did No 16 hole] observe the plugging. Carl Hoodsour 410