

KANSAS CORPORATION COMMISSION  
OIL & GAS CONSERVATION DIVISION

ORIGINAL

Form ACO-1  
September 1999  
Form Must Be Typed

*Can  
Dm  
1-20-08*

WELL COMPLETION FORM

WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33190  
Name: Noble Energy, Inc.  
Address: 1625 Broadway, Suite 2200  
City/State/Zip: Denver, CO 80202  
Purchaser: \_\_\_\_\_  
Operator Contact Person: Jennifer Barnett  
Phone: (303) 228-4235  
Contractor: Name: Excell Services Inc., Wray, CO  
License: 8273

Wellsite Geologist: none  
Designate Type of Completion:  
 New Well  Re-Entry  Workover  
 Oil  SWD  SIOW  Temp. Abd.  
 Gas  ENHR  SIGW  
 Dry  Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:  
Operator: n/a

Well Name: \_\_\_\_\_  
Original Comp. Date: \_\_\_\_\_ Original Total Depth: \_\_\_\_\_  
 Deepening  Re-perf.  Conv. to Enhr./SWD  
 Plug Back  Plug Back Total Depth  
 Commingled Docket No. \_\_\_\_\_  
 Dual Completion Docket No. \_\_\_\_\_  
 Other (SWD or Enhr.?) Docket No. \_\_\_\_\_

8/22/2008	8/22/2008	11/10/2008
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 023-21080-00-00  
County: Cheyenne  
NE SE SE SW Sec. 13 Twp. 2 S. R. 39  East  West  
475' feet from S N (circle one) Line of Section  
2,400' feet from E W (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:  
(circle one) NE SE NW SW  
Lease Name: Jones Well #: 24-13  
Field Name: Cherry Creek Niobrara Gas Area


Producing Formation: Niobrara  
Elevation: Ground: 3328' Kelly Bushing: 3337'  
Total Depth: 1460' Plug Back Total Depth: 1414'  
Amount of Surface Pipe Set and Cemented at 190' cmt w/ 65 sx Feet  
Multiple Stage Cementing Collar Used?  Yes  No  
If yes, show depth set \_\_\_\_\_ Feet  
If Alternate II completion, cement circulated from n/a  
feet depth to \_\_\_\_\_ w/ \_\_\_\_\_ sx cmt.

Drilling Fluid Management Plan Air I NCR 1-30-09  
(Data must be collected from the Reserve Pit)  
Chloride content \_\_\_\_\_ ppm Fluid volume \_\_\_\_\_ bbls  
Dewatering method used \_\_\_\_\_  
Location of fluid disposal if hauled offsite: \_\_\_\_\_  
Operator Name: \_\_\_\_\_  
Lease Name: \_\_\_\_\_ License No.: \_\_\_\_\_  
Quarter \_\_\_\_\_ Sec. \_\_\_\_\_ Twp. \_\_\_\_\_ S. R. \_\_\_\_\_  East  West  
County: \_\_\_\_\_ Docket No.: \_\_\_\_\_

**INSTRUCTIONS:** An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Jennifer Barnett  
Title: Regulatory Analyst Date: 12/8/08  
Subscribed and sworn to before me this 8<sup>th</sup> day of December, 2008.  
Notary Public: Kira Clausen  
Date Commission Expires: 9/20/09



**KCC Office Use ONLY**

Letter of Confidentiality Received  
If Denied, Yes  Date: \_\_\_\_\_

Wireline Log Received

Geologist Report Received

UIC Distribution

**RECEIVED**  
KANSAS CORPORATION COMMISSION  
**DEC 09 2008**

CONSERVATION DIVISION  
WICHITA, KS

Operator Name: Noble Energy, Inc. Lease Name: Jones Well #: 24-13  
 Sec. 13 Twp. 2 S. R. 39  East  West County: Cheyenne

**INSTRUCTIONS:** Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i>  Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No  Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i>  List All E. Logs Run:  <b>Triple Combo (DEN/NEU/IND), CBL/CCL/GR</b>	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample  Name Top Datum <b>Niobrara 1234'</b>
---	---

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 7/8"	7"	17 Lbs/Ft.	190'	50/50 POZ	65 sx	3% CaCl, .25% Flo-cale
Production	6-1/4"	4-1/2"	10.5 Lbs/Ft.	1456'	Lead Type III	29 sx	12% Gel, 2% CaCl, .25% Polyfaka
					Tail Type III	56 sx	2% Gel, 1% CFL-80

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
3 SPF	Perf Niobrara interval from 1235'-1277'	Niobrara frac'd with 500 gals 7.5% HCL acid, 12,000 gals of	
	(42', 3spf, 126 holes) .41" EHD, 120 degree phase	25% CO2 foamed gel pad; 31,956 gals 25% CO2 foamed	
		gel carrying 96,040 lbs 16/30 sand. ATP- 588 psi; ATR- 14.4 bpm.	

TUBING RECORD	Size	Set At	Packer At	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
---------------	------	--------	-----------	---

Date of First, Resumerd Production, SWD or Enhr. <b>Waiting on hookup</b>	Producing Method <input type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)
--	---

Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity
-----------------------------------	-----------	---------	-------------	---------------	---------

Disposition of Gas  Vented  Sold  Used on Lease *(If vented, Submit ACO-18.)*

METHOD OF COMPLETION

Open Hole  Perf.  Dually Comp.  Commingled  
 Other (Specify) \_\_\_\_\_

Production Interval

# BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102  
 Denver, Colorado 80202  
 Phone: 303-296-3010  
 Fax: 303-298-8143  
 E-mail: bisonoil@qwest.net

INVOICE # 2882

LOCATION C.R. 22 KS.

FOREMAN Eric Tony, Cisco

## TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RGE	COUNTY	FORMATION
8-22-08	Jones 24-13	13	25	39W	Cheyenne	

CHARGE TO <u>M'Pherson Drilling</u>	OWNER
MAILING ADDRESS	OPERATOR <u>scot</u>
CITY	CONTRACTOR <u>M'Pherson</u>
STATE ZIP CODE	DISTANCE TO LOCATION <u>80 miles</u>
TIME ARRIVED ON LOCATION <u>80 mi 7:30</u>	TIME LEFT LOCATION

WELL DATA			PRESSURE LIMITATIONS	
HOLE SIZE	TUBING SIZE	PERFORATIONS	THEORETICAL	INSTRUCTED
<u>9 3/8</u>				
TOTAL DEPTH <u>185</u>	TUBING DEPTH	SHOTS/FT.	SURFACE PIPE ANNULUS LONG	
	TUBING WEIGHT	OPEN HOLE	STRING	
CASING SIZE <u>7"</u>	TUBING CONDITION		TUBING	
CASING DEPTH <u>151</u>		TREATMENT VIA	TYPE OF TREATMENT	TREATMENT RATE
CASING WEIGHT <u>17"</u>	PACKER DEPTH		<input checked="" type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM
CASING CONDITION <u>good</u>			<input type="checkbox"/> PRODUCTION CASING	INITIAL BPM
			<input type="checkbox"/> SQUEEZE CEMENT	FINAL BPM
			<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM
			<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM
			<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM
			<input type="checkbox"/> MISC PUMP	
			<input type="checkbox"/> OTHER	HYD IRR = RATE X PRESSURE X 40.8

PRESSURE SUMMARY		PRESSURE SUMMARY		PRESSURE SUMMARY	
BREAKDOWN or CIRCULATING	psi	AVERAGE	psi		
FINAL DISPLACEMENT	psi	ISIP	psi		
ANNULUS	psi	5 MIN SIP	psi		
MAXIMUM	psi	15 MIN SIP	psi		
MINIMUM	psi				

INSTRUCTIONS PRIOR TO JOB mtrp, safety meeting, est. circ. m'p 65 sks cont yield 1.10  
Density 15.2, Displace 6.6 BBLs H<sub>2</sub>O, shut in well wash up to pit

JOB SUMMARY  
 DESCRIPTION OF JOB EVENTS mtrp (7:30) safety meeting (7:35) est. circ. (7:42) m'p  
65 sks cont (7:44) Displace 6.6 BBLs H<sub>2</sub>O (7:52) shut in well wash up  
to pit (7:53)

5 bbls to pit

RECEIVED  
 KANSAS CORPORATION COMMISSION

DEC 09 2008

CONSERVATION DIVISION  
 WICHITA, KS

[Signature]  
 AUTHORIZATION TO PROCEED

Driller  
 TITLE

8-22-08  
 DATE

Customers hereby acknowledges and specifically agrees to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.

# BISON OIL WELL CEMENTING INC.



1738 Wynkoop St., Ste. 102  
 Denver, Colorado 80202  
 Phone: 303-298-3010  
 Fax: 303-298-8143  
 E-mail: bisonoil@qwest.net

INVOICE # 7845  
 LOCATION CR 22  
 FOREMAN P97  
CLARK  
FRANCISCO

## TREATMENT REPORT

DATE <u>9-23-08</u>	WELL NAME <u>JONES 24-13</u>	SECTION <u>13</u>	TWP <u>25</u>	RGE <u>JRW</u>	COUNTY <u>Cherokee</u>	FORMATION
CHARGE TO <u>EXCEL SERVICES</u>			OWNER <u>NOBLE</u>			
MAILING ADDRESS			OPERATOR			
CITY			CONTRACTOR <u>EXCEL 17</u>			
STATE ZIP CODE			DISTANCE TO LOCATION <u>80 miles</u>			
TIME ARRIVED ON LOCATION <u>9:45 (922-08) ROUNDS 10:30</u>			TIME LEFT LOCATION <u>3:00</u>			

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE <u>6 1/2</u>	TUBING SIZE	PERFORATIONS	THEORETICAL		INSTRUCTED
TOTAL DEPTH <u>1461</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS' LONG		
	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>4 1/2</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>1447</u>		TREATMENT VIA	TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT <u>10.5</u>	PACKER DEPTH		<input type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM	
CASING CONDITION <u>GOOD</u>			<input checked="" type="checkbox"/> PRODUCTION CASING	INITIAL BPM	
			<input type="checkbox"/> SQUEEZE CEMENT	FINAL BPM	
			<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM	
			<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM	
			<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM	
			<input type="checkbox"/> MISC PUMP		
			<input type="checkbox"/> OTHER	HYD HP = RATE X PRESSURE X 40.8	

INSTRUCTIONS PRIOR TO JOB: MIREX, SALT MOUNTAIN, ESTABIC with 30 BBLS MIF  
MHP 2.95KSL CMT 12.0 DENSITY 2.1641 G/G 11 BBLS MIX  
MHP 5.65KSL TFL CMT 13.8 DENSITY 1.8341 G/G 13 BBLS MIX  
DROP PLUG DISPLACE 22.5 BBLS BUMP PLUG 1200 TO 1500 PSI  
Release pressure wash up to PIT R/DOWN

JOB SUMMARY  
 DESCRIPTION OF JOB EVENTS: MIREX 1:00 SALT 1:41 MIF 1:49  
CCM 1:58 DRP 2:03 10AUG 2:07 PSI 200  
20AUG 2:42 PSI 500 22.5 AUG 2:15 PSI 1500  
BBLS TO PT 5

RECEIVED  
 KANSAS CORPORATION CO.  
 DEC 09 2008  
 CONSERVATION DIVISION  
 WICHITA, KS

Joe [Signature]  
 AUTHORIZATION TO PROCEED TITLE DATE

Customers hereby acknowledges and specifically agrees to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.