ORIGINATION Form ACO-1 Porm must be Typed

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 4549	API NO. 15- 067-20109-60-0
Name: Anadarko Petroleum Corporation	County Grant
Address 1201 Lake Robbins Drive	
City/State/Zip <u>The Woodlands, TX 77380</u>	1320 NF Feet from S/N (circle one) Line of Section
Purchaser: <u>Anadarko Energy Services Company</u>	3960 W Feet from E/W (circle one) Line of Section
Operator Contact Person: <u>Diana Smart</u>	Footages Calculated from Nearest Outside Section Corner:
Phone (<u>832</u>) 636-8380	(circle one) NE SE NW SW
Contractor: Name: <u>Midwestern Well Service, Inc</u>	Lease Name Stainbrook Well # A-1
License: 5112	Field Name Hugoton/Panoma
Wellsite Geologist:	Producing Formation Chase/Council Grove
Designate Type of Completion	Elevation: Ground 3013 Kelley Bushing
New Well Re-Entryx Workover	Total Depth 2800 Plug Back Total Depth
Oil SWD SIOW Temp. Abd SIGW	Amount of Surface Pipe Set and Cemented at 609 Feet Multiple Stage Cementing Collar Used? Yes X No
Dry Other (Core, WSW, Expl., Cathodic, etc.)	If yes, show depth setFeet
If Workover/Reentry: Old Well Info as follows:	If Alternate II completion, cement circulated from
Operator: Anadarko Petroleum Corporation	feet depth tow/sx cmt. Drilling Fluid Management Plan
Well Name: Stainbrook A-1	Drilling Fluid Management Plan (Data must be collected from the Reserve Pit)
Original Comp. Date 01/11/1972 Original Total Depth 2800 Deepening Re-perf. Conv. to Enhr./SWD	Chloride content ppm Fluid volume bbls
	Dewatering method used
_X Commingled Docket NoC-164	Location of fluid disposal if hauled offsite:
Dual Completion Docket No	Operator Name
Other (SWD or Enhr?) Docket No.	Lease NameLicense No
10/08/2007 12/14/2007 Spud Date or Date Reached TD Completion Date or	Quarter Sec Twp S R E M
Recompletion Date Recompletion Date	County Docket No
Kansas 67202, within 120 days of the spud date, recompletion, wor Information on side two of this form will be held confidential for a peri 82-3-107 for confidentiality in excess of 12 months). One copy of all CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with All requirements of the state of the second of the secon	th the Kansas Corporation Commission, 130 S. MarkeT - Room 2078, Wichita, kover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. od of 12 months if requested in writing and submitted with the form (see rule wireline logs and geologist well report shall be attached with this form. ALL all plugged wells. Submit CP-111 form with all temporarily abandoned wells. ulate the oil and gas industry have been fully complied with and the statements
Signature Title Staff Regulated Analyst Date 01 Subscribed and swort to before me this 200 day of 500 Notary Public Date Commission Expires 111111111111111111111111111111111111	CONTINUE OF CONSERVATION DIVISION CONTINUE OF CONTINUE OF CONSERVATION DIVISION WICHITA, IS

Operator Name Anad	arko Petrole	m Corpora	tion	Leas	e Nam	e <u>Stainbro</u>	ok	Well #	<u>A-1</u>	
Sec. <u>12</u> Twp. <u>28</u>	3 S.R. <u>37</u>	East	X West	Cou	nty	Grant				
INSTRUCTIONS: Shot tested, time tool open temperature, fluid rec Electric Wireline Logs:	and closed, flowi overy, and flow	ng and shut-i rates if gas	n pressure to surface	es, whether se e during tes	hut-in	pressure reach	ned static level, I	nydrostatic pr	essures, both	om hole
Drill Stem Tests Taken (Attach Additional Sheets.)		Yes	Yes X No		Log		Formation (Top), Depth and Datums Sam			
Samples Sent to Geological Survey		Yes	X No		me	Тор		Dat	Datum	
Cores Taken		Yes	⊠ No							
Electric Log Run (Submit Copy.)		Yes	X No							
List All E.Logs Run:										
Purpose of String	Report	t all strings se Size Cas	sing	New r, surface, in Weight Lbs./Ft.	_	iate, production	n, etc. Type of Cement		Type and Per	cent
	Drilled Set (In O.D.)		LDS./Ft.		Depth	Cement	Used	Additives		
Surface	1	8-5/8"				609'	-			
Production		5-1/2"		15.5		2799'				
Purpose	Depth			1		EZE RECORD				
Perforate Protect Casing Plug Back TD Plug Off Zone	Top Bottom Type of Cement #Sacks Used Type and Percent Additives						es 			
Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated				Acid, Fracture, Shot, Cement Sqeeze Record (Amount and Kind of Material Used) Depth					
2	2649'-2787' (existing perfs)				Acidize w/18 bbl 15% FE acid 2536-2572					
3	2536'-2572' (new perfs)				Frac w/297,000# 12/20 brown sand 2536-2572					
		Set CIBP @	2797' v	while work	ing.	Knocked o	out CIBP 12/1	1/2007.		;
TUBING RECORD	Size 2-3/8"	Set At 275	9'	Packer A	t	Liner Run	☐ Yes 🕱	No		
Date of First, Resumed		VD or Enhr.	Produ	cing Method	ХP	umping Ga	as Lift Oth	er (Explain)	•	
Estimated Production Per 24 Hours	Oil	Bbls.	Gas	Mcf	Wate	er Bbls.	Gas-Oil I	Ratio	Grav	ity
Disposition of Gas:	METHOD	00 · F COMPLETI	ION	347	<u> </u>	11	N/A Production Inter	/al	•	
		_	_	– -						
✓ Vented 🔀 Sold (If vented, submit	Used on Le	ease [_ ·	lole	oration	Dually C	omp. χ Commin	gled 2	2536'-2787'	

- Grant County, Panoma Council Grove Field ,,,,6 7/
 STAINBROOK "A" #1, C SW Section 12-28S-37W, APC 100%:
 (ETD 2785' Council Grove) . . . New location staked 11/11/71. Drlg Contractor Earl F. Wakefield, Inc. 11/14/71: Spudded 12-1/4" hole @ 10:00 a.m. on 11/13/71. Drld to 610'. Dev: 3/4° @ 610'. Ran 19 jts 8-5/8" 24# K-55 smls csg set @ 609'. Cmt'd w/200 sxs Pozmix 2% CC + 200 sxs Common 2% CC. PD @ 8:15 p.m on 11/13/71. Cmt circ. 11/15/71: 1925' trip for bit. Lev: 3/4° @ 1026', 3/4° @ 1925'. Mud: W 9.4, V 33, LCM 6#.
 - Grant County, Panoma Council Grove Field

 STAINBROOK "A" #1, C SW Section 12-28S-37W, APC 100%: //-/6-7/

 (ETD 2785' Council Grove) . . . 2426' drlg. Dev: 3/4° @ 2230'.

 Mud: W 9.5, V 31, LCM 7#.
 - Grant County, Panoma Council Grove Field //-/7/
 STAINBROOK "A" #1, C SW Section 12-28S-37W, APC 100%:
 (ETD 2785' Council Grove) . . . 2733' drlg. Mud: W 9.5, V 38, LCM 8#.
 - Grant County, Panoma Council Grove Field //-/8-7/
 STAINBROOK "A" #1, C SW Section 12-285-37W, APC 100%:
 (ETD 2785' Council Grove) . . . 2898' running 5-1/2" csg after running OH logs. Mud: W 9.7, V 48, WL 8.8, Cl 32,000.
 - Grant County, Panoma Council Grove Field 11-19-7, STAINBROOK "A" #1, C SW Section 12-28S-37W, APC 100%: 2800' RTD . . . 2800' ran 88 jts 5-1/2", 15.5#, K-55 smls csg set @ 2799'. Cmt w/400 sxs Trinity Lite Wate 4% gel, 12-1/2# Gilsonite & 150 sxs salt sat pozmix (BJ Diamix) w/0.5% D-19. Baffle @ 2794.5'. Used 7 cent & 2 cmt baskets. PD @ 11:15 a.m. on 11/18/71, cmt circ. Correction on 11/18/71 report RTD is 2800' instead of 2898'.
 - STAINBROOK "A" #1, C SW Section 12-28S-37W, APC 100%: 11-22-7/2800' RTD . . . WOC.
 - STAINBROOK "A" #1, C SW Section 12-28S-37W, APC 100%: //- 23-2/2800' RTD . . . WOC.
 - STAINBROOK "A" #1, C SW Section 12-28S-37W, APC 100%: //- 24-7/2800' RTD . . . WOC.
 - STAINBROOK "A" #1, C SW Section 12-28S-37W, APC 100%: //- 25 7/ 2800' RTD . . . MI completion unit.

15-067-20109-0001