## 15-051-24588-00-00 4-060773

11-21 API Number: 15-051-24,588-00-00 TO: STATE CORPORATION COMMISSION 100'NW of **SE NW NE** /4 SEC. **28**, **11** S, **20** W CONSERVATION DIVISION - PLUGGING 130 SOUTH MARKET, SUITE 2078 4380 feet from S section line 1700 feet from E section line WICHITA, KANSAS 67202 Operator license# 5259 Lease: \_\_\_\_\_ Keller "D" Well # 2 County: Ellis /a 4.3/ Operator: Mai Oil Operations, Inc. \_ feet Address: P.O. Box 33 Well total depth 3825 Conductor Pipe: 0 inch @ Russell, Kansas 67665 Surface pipe 8 5/8 Inch @ 260 feet Aband. oil well\_x, Gas well\_\_\_\_, Input well\_\_\_, SWD\_\_\_\_, D & A\_\_\_\_ Plugging contractor: Co Tools License#\_\_\_\_\_\_\_ License#\_\_\_\_\_\_ Address:\_\_\_\_\_ Company to plug at: Hour: 9:00 A.M. Day: 21 Month: November Year: 1995 Plugging proposal received from: Allen Bangert Company: Mai Oil Operations, Inc. Phone: 913-483-2169 Were: Order 275 sxs 60/40 posmix - 10% gel and hulls. Tubing and rods pulled prior to plugging. KANSAS CORPORATION COMMISSION CONSERVATION DIVISION Plugging Proposal Received by: Herb Deines WICHITA KS Plugging operations attended by agent? All[ X ], Part[ ], None[ Completed: Hour: 10:00 A.M., Day: 21, Month: November, Year: 1995 Actual plugging report: 8 5/8" to 260' with 165 sxs. 5 1/2" to 3820' with 175 sxs. D.V. at 1565' with 350 sxs cement. Tied onto annulus with instant S.I.P of 300#. Tied onto production casing and pumped 275 sxs cement with 500# hulls. Max. P.S.I. 1000#. S.I.P. 500#. Remarks: <u>Allied Cementing</u>. Condition of casing(in hole): GOOD X BAD Anhy.plug: YES\_\_ X NO\_\_ Bottom plug(in place): YES\_\_\_, CALC\_\_\_X\_, NO\_\_\_\_\_ Dakota plug: YES\_X\_\_, NO\_\_\_\_ Plugged through TUBANG\_\_\_\_, CASING X\_\_\_. Elevation:\_\_\_\_ did not[ ] observe the plugging. (agent) Form CP-2/3