

KANSAS CORPORATION COMMISSION  
OIL & GAS CONSERVATION DIVISION

Form ACO-1  
September 1999  
Form Must Be Typed

WELL COMPLETION FORM  
WELL HISTORY - DESCRIPTION OF WELL & LEASE

\*Final ACO-1

AMENDED

Operator: License # 33190  
 Name: Noble Energy, Inc.  
 Address: 1625 Broadway, Suite 2200  
 City/State/Zip: Denver, CO 80202  
 Purchaser: Southern Star  
 Operator Contact Person: Jennifer Barnett  
 Phone: (303) 228-4235  
 Contractor: Name: Excell Services Inc., Wray, CO  
 License: 8273  
 Wellsite Geologist: none  
 Designate Type of Completion:  
 New Well     Re-Entry     Workover  
 Oil     SWD     SIOW     Temp. Abd.  
 Gas     ENHR     SIGW  
 Dry     Other (Core, WSW, Expl., Cathodic, etc)  
 If Workover/Re-entry: Old Well Info as follows:  
 Operator: n/a  
 Well Name: \_\_\_\_\_  
 Original Comp. Date: \_\_\_\_\_ Original Total Depth: \_\_\_\_\_  
 Deepening     Re-perf.     Conv. to Enhr./SWD  
 Plug Back     Plug Back Total Depth  
 Commingled    Docket No. \_\_\_\_\_  
 Dual Completion    Docket No. \_\_\_\_\_  
 Other (SWD or Enhr.?)    Docket No. \_\_\_\_\_  

<u>9/6/2006</u>	<u>9/7/2006</u>	<u>9/18/2006</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date


API No. 15 - 023-20695-00-00  
 County: Cheyenne  
 SE SE NE SW Sec. 13 Twp. 2 S. R. 39  East  West  
1,621' feet from S N (circle one) Line of Section  
2,416' feet from E W (circle one) Line of Section  
 Footages Calculated from Nearest Outside Section Corner:  
 (circle one) NE SE NW SW  
 Lease Name: Jones Well #: 23-13  
 Field Name: Cherry Creek Niobrara Gas Area  
 Producing Formation: Niobrara  
 Elevation: Ground: 3332' Kelly Bushing: 3344'  
 Total Depth: 1460' Plug Back Total Depth: 1412'  
 Amount of Surface Pipe Set and Cemented at 262' cmt w/ 63 sx Feet  
 Multiple Stage Cementing Collar Used?  Yes  No  
 If yes, show depth set \_\_\_\_\_ Feet  
 If Alternate II completion, cement circulated from n/a  
 feet depth to \_\_\_\_\_ w/ \_\_\_\_\_ sx cmt.

Drilling Fluid Management Plan A1+ I NR 3-4-09  
 (Data must be collected from the Reserve Pit)  
 Chloride content \_\_\_\_\_ ppm Fluid volume \_\_\_\_\_ bbls  
 Dewatering method used \_\_\_\_\_  
 Location of fluid disposal if hauled offsite: \_\_\_\_\_  
 Operator Name: \_\_\_\_\_  
 Lease Name: \_\_\_\_\_ License No.: \_\_\_\_\_  
 Quarter \_\_\_\_\_ Sec. \_\_\_\_\_ Twp. \_\_\_\_\_ S. R. \_\_\_\_\_  East  West  
 County: \_\_\_\_\_ Docket No.: \_\_\_\_\_

**INSTRUCTIONS:** An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Jennifer Barnett  
 Title: Regulatory Analyst Date: 2/3/09  
 Subscribed and sworn to before me this 3<sup>rd</sup> day of FEBRUARY  
 20 09  
 Notary Public: Mendi Larue  
 Date Commission Expires: 9/11/2010



**KCC Office Use ONLY**  
 Letter of Confidentiality Received   
 Denied, Yes  Date: \_\_\_\_\_  
 Wireline Log Received \_\_\_\_\_  
 Geologist Report Received \_\_\_\_\_  
 UIC Distribution \_\_\_\_\_  
**RECEIVED**  
 KANSAS CORPORATION COMMISSION  
**FEB 04 2009**  
 CONSERVATION DIVISION  
 WICHITA

Operator Name: Noble Energy, Inc. Lease Name: Jones Well #: 23-13  
 Sec. 13 Twp. 2 S. R. 39  East  West County: Cheyenne

**INSTRUCTIONS:** Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i>  Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No  Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i>  List All E. Logs Run:  <b>Array Induction w/ Linear Correlation,                  Compensated Neutron Litho Density,                  CBL/CCL/GR</b>	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample  Name <u>Niobrara</u> Top <u>1238'</u> Datum _____
---	---

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 1/2"	7"	17 Lbs/Ft.	262'	Portland cmt lite ASTM	63 sx	n/a
Production	6 1/8"	4 1/2"	10.5 Lbs./Ft.	1454'		75 sx	n/a

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
2 SPF	Perf Niobrara interval from 1239'-1274'	Niobrara frac'd with 500 gals 7.5% HCL acid, 46,079 gals of	
	(35', 2 spf, 70 holes) .41" EHD, 120 degree phase	70 Q foam containing 100,260 lbs 16/30 Brady sand & 295,000 SCF N2.	

TUBING RECORD	Size	Set At	Packer At	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
---------------	------	--------	-----------	---

Date of First, Resumerd Production, SWD or Enhr. <b>1/19/2009</b>	Producing Method <input checked="" type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)
--	--

Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity
	0	70	0	0	

Disposition of Gas:  Vented  Sold  Used on Lease *(If vented, Submit ACO-18.)*

METHOD OF COMPLETION:  Open Hole  Perf.  Dually Comp.  Commingled \_\_\_\_\_

Production Interval:  Other (Specify) \_\_\_\_\_