

ORIGINAL

Form ACO-1
October 2008
Form Must Be Typed

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

1/23/09

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License # 33397
Name: Running Foxes Petroleum
Address 1: 7060 S TUCSON WAY Suite B
Address 2: _____
City: CENTENNIAL State: CO Zip: 80112 + _____
Contact Person: Kent Keppel
Phone: (303) 617-7242
CONTRACTOR: License # 31280 32834
Name: JTC Oil, Inc.
Wellsite Geologist: Mark Machosky
Purchaser: _____

RECEIVED
KANSAS CORPORATION COMMISSION
JAN 23 2009
CONSERVATION DIVISION
WICHITA, KS

Designate Type of Completion:
____ New Well ____ Re-Entry ____ Workover
 Oil ____ SWD ____ SIOW
____ Gas ____ ENHR ____ SIGW
____ CM (Coal Bed Methane) ____ Temp. Abd.
____ Dry ____ Other _____
(Core, WSW, Expl., Cathodic, etc.)

If Workover/Re-entry: Old Well Info as follows:
Operator: _____
Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
____ Deepening ____ Re-perf. ____ Conv. to Enhr. ____ Conv. to SWD
____ Plug Back: _____ Plug Back Total Depth _____
____ Commingled Docket No.: _____
____ Dual Completion Docket No.: _____
____ Other (SWD or Enhr.?) Docket No.: _____
9/25/2008 9/28/2008 Waiting on Completion
Spud Date or Date Reached TD Completion Date or
Recompletion Date Recompletion Date

API No. 15 - 15-011-23398-00-00
Spot Description: _____
NW SE SW NW Sec. 34 Twp. 23 S. R. 22 East West
1991 Feet from North / South Line of Section
715 Feet from East / West Line of Section
Footages Calculated from Nearest Outside Section Corner:
 NE NW SE SW
County: Bourbon
Lease Name: Stewart Well #: 5-34D
Field Name: Wildcat
Producing Formation: Bartlesville
Elevation: Ground: 1017' Kelly Bushing: _____
Total Depth: 838' Plug Back Total Depth: 838'
Amount of Surface Pipe Set and Cemented at: 20 Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set: _____ Feet
If Alternate II completion, cement circulated from: _____
feet depth to: _____ w/ _____ sx cmt.

Drilling Fluid Management Plan Alt II Nov 3-6-09
(Data must be collected from the Reserve Pit)
Chloride content: _____ ppm Fluid volume: _____ bbls
Dewatering method used: _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Kent Keppel
Title: Landman Date: 1-21-2009
Subscribed and sworn to before me this 21st day of January
09
Notary Public: Karla Peterson

KARLA PETERSON
NOTARY PUBLIC
STATE OF COLORADO
My Commission Expires November 9, 2011

KCC Office Use ONLY
 Letter of Confidentiality Received
 If Denied, Yes Date: _____
 Wireline Log Received
 Geologist Report Received
 UIC Distribution

Date Commission Expires:
Nov. 9, 2011

Operator Name: Running Foxes Petroleum Lease Name: Stewart Well #: 5-34D
 Sec. 34 Twp. 23 S. R. 22 East West County: Bourbon

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Gamma Ray, Density Neutron, Dual Induction	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample <table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:60%;">Name</td> <td style="width:20%;">Top</td> <td style="width:20%;">Datum</td> </tr> <tr> <td>Excello</td> <td>441'</td> <td>576'</td> </tr> <tr> <td>Upper Bartlesville</td> <td>630'</td> <td>387'</td> </tr> <tr> <td>Mississippian</td> <td>793'</td> <td>224'</td> </tr> </table>	Name	Top	Datum	Excello	441'	576'	Upper Bartlesville	630'	387'	Mississippian	793'	224'
Name	Top	Datum											
Excello	441'	576'											
Upper Bartlesville	630'	387'											
Mississippian	793'	224'											

CASING RECORD <input type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	12.25"	8.625	24lbs.	21'	Quickset	20	KolSeal
Production	6.75"	4.5"	10.5lbs.	784'	Quickset	85	KolSeal Gel

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input checked="" type="checkbox"/> Perforate				
<input type="checkbox"/> Protect Casing				
<input type="checkbox"/> Plug Back TD				
<input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
	well not perfed yet	well not fraced yet	
		RECEIVED KANSAS CORPORATION COMMISSION	
		JAN 23 2009	
		CONSERVATION DIVISION WICHITA, KS	

TUBING RECORD: Size: _____ Set At: _____ Packer At: _____		Liner Run: <input type="checkbox"/> Yes <input type="checkbox"/> No	
Date of First, Resumed Production, SWD or Enhr. _____		Producing Method: <input type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain) _____	
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls. Gas-Oil Ratio Gravity

DISPOSITION OF GAS: <input type="checkbox"/> Vented <input type="checkbox"/> Sold <input type="checkbox"/> Used on Lease <i>(If vented, Submit ACO-18.)</i>	METHOD OF COMPLETION: <input type="checkbox"/> Open Hole <input type="checkbox"/> Perf. <input type="checkbox"/> Dually Comp. <input type="checkbox"/> Commingled <input type="checkbox"/> Other (Specify) _____	PRODUCTION INTERVAL: _____ _____
--	---	---

FED. ID# _____
 MC#D # _____
 Shop # 165290
 Cellular # 620 437-2661
 Office # 620 437-7582
 Office Fax # 316 685-5908
 Shop Address: 316-685-5926
 3613A Y Road
 Madison, KS 66860

Hurricane Services, Inc.
 P.O. Box 782228
 Wichita, KS 67278-2228

Cement, Acid or Tools
 Service Ticket

02794

DATE 10-8-08

COUNTY BOLCO CITY _____

CHARGE TO Running Foxes

ADDRESS _____ CITY _____ ST _____ ZIP _____

LEASE & WELL NO. Stewart 5-340 CONTRACTOR _____

KIND OF JOB LongString SEC. _____ TWP. _____ RNG. _____

DIR. TO LOC. _____ OLD NEW

Quantity	MATERIAL USED	Serv. Charge	
			700.00
85 SKS	QuickSet cement		1224.00
340 lbs	KOI-SEAL 4" P/SK		102.00
200 lbs	Gel Flush		40.00
2 1/2 Hrs	Water Truck #193		200.00
90	Mileage on Truck #107		135.00
	BULK CHARGE		
4.93 Tns	BULK TRK. MILES		488.07
90	PUMP TRK. MILES		270.00
	Rental on wireline		50.00
1	PLUGS 4 1/2" Top Rubber		35.00
		6.32 SALES TAX	88.26
		TOTAL	3332.33

RECEIVED
 KANSAS CORPORATION COMMISSION
 JAN 23 2009
 CONSERVATION DIVISION
 WICHITA, KS

T.D. 8.38"
 SIZE HOLE 6 3/4"
 MAX. PRESS. _____
 PLUG DEPTH _____
 PLUG USED _____

CSG. SET AT 784" VOLUME 12 1/2 Bbls.
 TBG SET AT _____ VOLUME _____
 SIZE PIPE 4 1/2"
 PKER DEPTH _____
 TIME FINISHED _____

REMARKS: Big up to 4 1/2" casing, Break circulation with fresh water, Pumped 10 Bbl. Gel Flush, circulate Gel around to condition hole. Mixed 85 sks QuickSet cement w/ 4" P/SK of KOI-SEAL. Shut down wash out pump & lines - Release Plug - Displace Plug with 12 1/2 Bbls water. Final Pumping at 450 PSI - Bump Plug to 900 PSI - wait 2 minutes - Release Pressure - Float Held close casing in w/ 0 PSI. Good cement returns to surface w/ 3 1/2 Bbl slurry

EQUIPMENT USED

NAME	UNIT NO.	NAME	UNIT NO.
<u>Kelly Kimberlin</u>	<u>185</u>	<u>Jerry #91, Clayton #193</u>	
<u>Braed Butler</u>		<u>Witnessed by Rick</u>	
HSI REP.		OWNER'S REP.	

FED# 165290
 MC ID # 620 437-2661
 Shop # 620 437-7582
 Cellular # 316 685-5908
 Office # 316-685-5926
 Office Fax # 3613A Y Road
 Shop Address: Madison, KS 66860

Hurricane Services, Inc.
 P.O. Box 782228
 Wichita, KS 67278-2228

Cement, Acid or Tools
 Service Ticket
 02794

COPY

DATE 10-8-08

COUNTY BOLCO CITY _____

CHARGE TO Running Foxes
 ADDRESS _____ CITY _____ ST _____ ZIP _____
 LEASE & WELL NO. Stewart 5-340 CONTRACTOR _____
 KIND OF JOB Longstring SEC. _____ TWP. _____ RNG. _____
 DIR. TO LOC. _____ OLD NEW

Quantity	MATERIAL USED	Serv. Charge	
		700.00	
85 SKs	QuickSet cement	1224.00	
340 lbs	KOI-SEAL 4" P/SK	102.00	
200 lbs	Gel Flush	40.00	
2 1/2 Hrs	Water Truck #193	200.00	
90	Mileage on Truck #107	135.00	
	BULK CHARGE		
4.93 Trk	BULK TRK. MILES	488.07	
90	PUMP TRK. MILES	270.00	
	Rental on wireline	50.00	
1	PLUGS 4 1/2" Top Rubber	35.00	
		6.32 SALES TAX	88.26
		TOTAL	3332.33

T.D. 838'
 SIZE HOLE 6 3/4"
 MAX. PRESS. _____
 PLUG DEPTH _____
 PLUG USED _____

CSG. SET AT 784' VOLUME 12 1/2 Bbls.
 TBG SET AT _____ VOLUME _____
 SIZE PIPE 4 1/2"
 PKER DEPTH _____
 TIME FINISHED _____

REMARKS: Big up to 4 1/2" casing, Break circulation with fresh water, Pumped 10 Bbl Gel Flush, circulate Gel around to condition hole, Mixed 85 SKs QuickSet cement w/ 4" P/SK of KOI-SEAL, Shut down washout pump & lines - Release Plug - Displace Plug with 12 1/2 Bbls water, Final Pumping at 450 PSI - Bump Plug to 900 PSI - wait 2 minutes - Release Pressure - Float Hold close casing in w/ 0 PSI Good cement returns to surface w/ 3 1/2 Bbl slurry

EQUIPMENT USED

NAME	UNIT NO.	NAME	UNIT NO.
<u>Kelly Kimberlin</u>	<u>185</u>	<u>Jerry #91, Clayton #193</u>	
<u>Brad Butler</u>		<u>Witnessed by Rick</u>	
HSI REP.		OWNER'S REP.	

FED. ID#
 MC ID # 165290
 Shop # 620 437-2661
 Cellular # 620 437-7582
 Office # 316 685-5908
 Office Fax # 316-685-5926
 Shop Address: 3613A Y Road
 Madison, KS 66860

Hurricane Services, Inc.
 P.O. Box 782228
 Wichita, KS 67278-2228

Cement, Acid or Tools
 Service Ticket

COPY 02794

DATE 10-8-08

COUNTY BOLCO CITY _____

CHARGE TO Running Foxes

ADDRESS _____ CITY _____ ST _____ ZIP _____

LEASE & WELL NO. Stewart 5-340 CONTRACTOR _____

KIND OF JOB LongString SEC. _____ TWP. _____ RNG. _____

DIR. TO LOC. _____ OLD NEW

Quantity	MATERIAL USED	Serv. Charge	
		700.00	
85 SKs	QuickSet cement	1224.00	
340 lbs	KD1-SEAL 4" P/SK	102.00	
200 lbs	Gel Flush	40.00	
2 1/2 Hrs	Water Truck #193	200.00	
90	Mileage on Truck #107	135.00	
	BULK CHARGE		
4.93 Trk	BULK TRK. MILES	488.07	RECEIVED KANSAS CORPORATION OF ENGINEERS
90	PUMP TRK. MILES	270.00	JAN 23 2009
	Rental on wireline	50.00	
1	PLUGS 4 1/2" Top Rubber	35.00	CONSERVATION DIVISION WICHITA, KS
		88.26	6.3% SALES TAX
		3332.33	TOTAL

T.D. 838'

SIZE HOLE 6 3/4"

MAX. PRESS. _____

PLUG DEPTH _____

PLUG USED _____

CSG. SET AT 784' VOLUME 12 1/2 Bbls.

TBG SET AT _____ VOLUME _____

SIZE PIPE 4 1/2"

PKER DEPTH _____

TIME FINISHED _____

REMARKS: Rig up to 4 1/2" casing, Break circulation with fresh water, Pumped 10 Bbl Gel Flush, circulate Gel around to condition hole, Mixed 85 sks QuickSet cement w/ 4" P/SK of KD1-SEAL, Shut down wash out pump & lines - Release Plug - Displace Plug with 12 1/2 Bbls water. Final Pumping at 450 PSI - Bump Plug to 900 PSI - wait 2 minutes - Release Pressure - Float Held close casing in w/ 0 PSI Good cement returns to surface w/ 3 1/2 Bbl slurry

EQUIPMENT USED

NAME Kelly Kimberlin UNIT NO. 185

NAME Jerry #91, Clayton #193 UNIT NO. _____

Brad Butler
 HSI REP.

Witnessed by Rick
 OWNER'S REP.