15-065-20390-0000

PETROLEUM GEOLOGIST P. O. BOX 503 . HAYS, KANSAS 67601

November 10, 1970

GEOLOGIC REPORT

Don Pratt No. 4 George Nickelson

NE SE SE 29-9-24W

Graham County, Kansas

Commenced: 11/2/70

11/10/70 Completed:

Pipe Record:

8 5/8 @ 252' w/150 sacks

4½ @ 4138 w/225 sacks

Anhydrite: 2212-49

Dreiling Rig 1 Drilled by:

ELEVATION 2551 K.B.

2546 Ground

2548 D.F.

FORMATION DATA (Corrected to Welex Log)

FORMATION							-			MINUS DAT	Α]	DEPTH
Topeka •	_	_	_	_	_				۰	-1081	•	•	•	•		۰	•	•	•	•	3632
Heebner .												۰		۰	۰	•	٠	•	•		3850
Toronto .										4000											
Lansing .										4004											
Kansas Cit																					
	-																				
Total Dept	n	•	•	•	•	•	•	•	•	-1011	•	•	•	•	•	•	•	•	•	•	

From 3186-93 calculates 20 to 22% porosity and 21 to 25% NOTICE: water. Test the top 2 feet if you have a cement job before abandoning unless other wells, which look better on this bench, have already condemned it.

Cores: None

Electric Logs: Welex Radiation-Guard-Frac Finder

Drill Stem Tests: Five (Depths not corrected to Welex Log)

_ FORMATION DESCRIPTION_ (Depths Corrected to Welex Log)

This well was two feet lower on Welex tops, compared with NOTICE: drill time log tops (eg.) T.D. drilled 4160 feet. This well thinned two feet from "G" base to total depth compared with No. 3.

Topeka 3632-3850:

There was ample porosity but I did not find any oil shows. There were two places with positive calculations (3758-60 and 3799-3802). Both were parts of continuous benches which are very wet below the calculations.

AS SOUNT