## 15-195-20644-00-00

Wichita, Kansas

4-<u>031937</u>

5-31

TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	API number: 15-195-20,644-00-00  NW SE NW /4 SEC. 17 , 11 S, 22 W  3630 feet from S section line 3630 feet from E section line
Operator license#_4767_	Lease Lloyd Nilhas "B" well # 1
Operator: Ritchie Exploration, Inc.	Well total depth 3925 feet 127,56
Address: 125 N. Market Suite 1000 Wichita, Kansas 67202	Well total depth 3925 feet Conductor Pipe: 0 inch 0 0 feet Surface pipe 8 5/8 Inch 0 194 feet
Aband. oil well <u>X</u> , Gas well <u></u> , Input well <u></u> , SWD <u></u> , D & A <u></u>	
Plugging contractor: Allied Cement Company License# -	
Address: Hays, Kansas 67601	
Company to plug at: Hour: A.M. Day:	31 Month: May Year: 94
Plugging proposal received from: John	
Company: Ritchie Exploration, Inc. Phone:	
Were: Order 250 sxs. 60/40 pozmix - 10% gel - 500# hulls.	
	- 1-44-1-5
Plugging Proposal Received by: <u>Carl Goodrow</u> Plugging operations attended by agent? All[ X ], Part[ ], None[ ]	
Completed: Hour: 8:30A.M., Day: 31, Month: May, Year: 94	
Actual plugging report: 8 5/8" set @ 194' w/150 sxs. cwc. 4 1/2" set @ 3869' w/175 sxs. Prod. Perf. 3460' - 3800'. Squeezed w/200 sxs. @ 1140'. Casing bad 900' to 2200'. Pulled rods and tubing - low fluid level.  Mixed and pumped down 4 1/2" w/200 sxs. cement blend w/500# hulls mixed in to Max. P.S.I. 900#. Close in P.S.I. 100#. Squeezed 8 5/8" w/50 sxs. cement blend to Max. P.S.I. 200#. Close in P.S.I. 200#. Plug complete.	
Remarks:  Condition of casing(in hole):GOOD BAD Anhy.plug:YES NO  Bottom plug(in place):YES ,CALC NO Dakota plug:YESX ,NO  Plugged through TUBING , CASING  Elevation: GL	
I did [ ] observe the p	olugging.  STATE CORPORATION COMMISSION
DATE 6-16-94 4NV. NO. 40575	JUN 1 5 1994 Form CP-2/3
INV. NO. 40575	G-15-1994 CONSERVATION DIVISION