

\*Subsequent ORIGINAL  
(Logging added)

KANSAS CORPORATION COMMISSION  
OIL & GAS CONSERVATION DIVISION

Form ACO-1  
September 1999  
Form Must Be Typed

WELL COMPLETION FORM  
WELL HISTORY - DESCRIPTION OF WELL & LEASE

AMENDED

Operator: License # 33190  
Name: Noble Energy, Inc.  
Address: 1625 Broadway, Suite 2200  
City/State/Zip: Denver, CO 80202  
Purchaser: Kinder Morgan/Cherry Creek  
Operator Contact Person: Jennifer Barnett  
Phone: (303) 228-4235  
Contractor: Name: Excell Services Inc., Wray, CO  
License: 8273

Wellsite Geologist: none

Designate Type of Completion:  
 New Well  Re-Entry  Workover  
 Oil  SWD  SIOW  Temp. Abd.  
 Gas  ENHR  SIGW  
 Dry  Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:

Operator: n/a

Well Name: \_\_\_\_\_

Original Comp. Date: \_\_\_\_\_ Original Total Depth: \_\_\_\_\_

Deepening  Re-perf.  Conv. to Enhr./SWD

Plug Back  Plug Back Total Depth

Commingled  Docket No. \_\_\_\_\_

Dual Completion  Docket No. \_\_\_\_\_

Other (SWD or Enhr.?)  Docket No. \_\_\_\_\_

8/13/2008 8/14/2008 9/2/2008  
Spud Date or Date Reached TD Completion Date or  
Recompletion Date Recompletion Date

API No. 15 - 023-21084-0000

County: Cheyenne

NW NE SW SW Sec. 33 Twp. 3 S. R. 41  East  West

1,010' feet from S N (circle one) Line of Section

870' feet from E W (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:

(circle one) NE SE NW SW

Lease Name: Zweygardt Well #: 14-33B

Field Name: Cherry Creek Niobrara Gas Area

Producing Formation: Niobrara

Elevation: Ground: 3588' Kelly Bushing: 3597'

Total Depth: 1600' Plug Back Total Depth: 1525'

Amount of Surface Pipe Set and Cemented at 250' cmt w/ 87 sx Feet

Multiple Stage Cementing Collar Used?  Yes  No

If yes, show depth set \_\_\_\_\_ Feet

If Alternate II completion, cement circulated from n/a

feet depth to \_\_\_\_\_ w/ \_\_\_\_\_ <sup>sx cmt</sup>

Alt-1-Dlg-4/8/09

Drilling Fluid Management Plan

(Data must be collected from the Reserve Pit)

Chloride content \_\_\_\_\_ ppm Fluid volume \_\_\_\_\_ bbls

Dewatering method used \_\_\_\_\_

Location of fluid disposal if hauled offsite: \_\_\_\_\_

Operator Name: \_\_\_\_\_

Lease Name: \_\_\_\_\_ License No.: \_\_\_\_\_

Quarter \_\_\_\_\_ Sec. \_\_\_\_\_ Twp. \_\_\_\_\_ S. R. \_\_\_\_\_  East  West

County: \_\_\_\_\_ Docket No.: \_\_\_\_\_

**INSTRUCTIONS:** An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Jennifer Barnett

Title: Regulatory Analyst Date: 3/18/09


Subscribed and sworn to before me this 18 day of MARCH

20 09

Notary Public: Mendi Larue

My Commission Expires 09/11/2010

Date Commission Expires: \_\_\_\_\_



KCC Office Use ONLY

Letter of Confidentiality Received

If Denied, Yes  Date: \_\_\_\_\_

Wireline Log Received

Geologist Report Received

UIC Distribution

KANSAS CORPORATION COMMISSION

MAR 19 2009

RECEIVED

Operator Name: Noble Energy, Inc. Lease Name: Zweygart Well #: 14-33B  
 Sec. 33 Twp. 3 S. R. 41  East  West County: Cheyenne

**INSTRUCTIONS:** Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i>  Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No  Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i>  List All E. Logs Run:  <b>Triple Combo (DEN/NEU/IND), CBL/CCL/GR</b>	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample  Name <u>Niobrara</u> Top <u>1352'</u> Datum _____
---	---

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 7/8"	7"	17 Lbs/Ft.	250'	50/50 POZ	87 sx	3% CaCl, .25% Flo-cel
Production	6 1/4"	4 1/2"	10.5 Lbs./Ft.	1569'	Lead Type III	34 sx	12% Gel, 2% CaCl, .25% Polyflake
					Tail Type III	56 sx	2% Gel, 1% CFL-80

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
3 SPF	Perf Niobrara interval from 1352'-1390'	Niobrara frac'd with 500 gals 7.5% HCL acid, 12,000 gals of	
	(38', 3spf, 114 holes) .42" EHD, 120 degree phase	25% CO2 foamed gel pad; 31.893 gals 25% CO2 foamed	
		gel carrying 100,060 lbs 16/30 sand. ATP- 617 psi; ATR- 12.8 bpm.	

TUBING RECORD		Size <u>2-3/8"</u>	Set At <u>1,444'</u>	Packer At <u>n/a</u>	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Date of First, Resumerd Production, SWD or Enhr. <b>9/19/2008</b>		Producing Method <input checked="" type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)			
Estimated Production Per 24 Hours	Oil Bbbs. <u>0</u>	Gas Mcf <u>106</u>	Water Bbbs. <u>0</u>	Gas-Oil Ratio <u>0</u>	Gravity

Disposition of Gas  Vented  Sold  Used on Lease *(If vented, Submit ACO-18.)*

METHOD OF COMPLETION  Open Hole  Perf.  Dually Comp.  Commingled

Production Interval  Other (Specify) \_\_\_\_\_