

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-051-21301-00-00
Spot: NWNESE Sec/Twnshp/Rge: 19-12S-18W
2310 feet from S Section Line, 990 feet from E Section Line
Lease Name: CRATHORNE Well #: 1
County: ELLIS Total Vertical Depth: 3785 feet

Operator License No.: 5030
Op Name: VESS OIL CORPORATION
Address: 1700 WATERFRONT PKWY BLDG 500
WICHITA, KS 67206

String	Size	Depth (ft)	Pulled (ft)	Comment
PROD	4.5	3783	0	w/150 sxs cmt
SURF	8.625	225	0	w/160 sxs cmt

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 03/17/2009 9:30 AM
Plug Co. License No.: 99996 Plug Co. Name: ALLIED CEMENT COMPANY
Proposal Rcvd. from: JOEL STULL Company: VESS OIL CORPORATION Phone: (785) 483-9169

Proposed Plugging Method: Ordered 350 sxs 60/40 pozmix - 4% gel - 500# hulls.
Squeezed casing leaks at 743' - 1150' w/200 sxs.
CIBP at 3704'. Packer left in the hole at 3361'.
123.01

Plugging Proposal Received By: RICHARD WILLIAMS WitnessType: COMPLETE (100%)
Date/Time Plugging Completed: 03/17/2009 12:30 PM KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

Ran tubing to 3275'. Allied pumped 100 sxs 60/40 pozmix - 4% gel neat.
Pulled tubing to 1750'. Allied pumped 100 sxs 60/40 pozmix - 4% gel with 400# hulls - cement circulated.
PTOH. Squeezed 25 sxs cement.
Max. P.S.I. 300#. S.I.P. 300#.
Hooked up to backside and pumped 50 sxs cement with 100# hulls.
Max. P.S.I. 100#. S.I.P. 100#.

Perfs:

Top	Bot	Thru	Comments
3429	3683		

INVOICED

DATE 4-21-09
INV NO. 2009061428

RECEIVED
MAR 20 2009
KCC WICHITA

Remarks: ALLIED CEMENTING COMPANY-TICKET #37429.

Plugged through: TBG

District: 04

Signed Richard Williams
(TECHNICIAN)

CM

PKT

MAR 19 2009

KANSAS ENERGY EXCHANGE, INC. 19-12-18W
 1540 NO. BROADWAY, SUITE 205F #1 CRATHORNE NW NE SE
 WICHITA, KS.

CONTR BERGMAN DRLG. CO. CTY ELLIS

GEOL _____ FIELD HYACINTH

E 2175 KB CM 3/21/77 CARD ISSUED 3/30/78 IP OIL WELL
 INTERVAL NOT RELEASED

+	+	+
+	+	+
+	+	+

API 15-051-21,301

LOG	TOPS	DEPTH	DATUM
GR HAV	2880	- 705	
DOVER LS	2947	- 772	
TARK	2982	- 807	
FLM LS	3032	- 857	
TOP	3173	- 998	
HEFB	3406	-1231	
LANS	3452	-1277	
BKC	3694	-1519	
CONG SD	3736	-1561	
RTD	3785	-1610	

8-5/8" 225/160sx, 4" 3783/150sx
 DST (1) 3354-3385/30-30-30-30, 110' MSW
 W/FSO, SIP 1213-1213#, FP 64-103#
 DST (2) 3413-3440/30-30-30-30, 10'M,
 SIP 38-38#, FP 38-38#
 DST (3) 3471-3490/30-30-30-30, 60' HOCM
 430' FO, 120' OCW, 190'SW, SIP
 1123-1084#, FP 103-297#
 DST (4) 3574-3600/30-30-30-30, 540'M
 W/SP O, SIP 774-772#, FP NA
 (MIS-RUN)
 MICT - CO & TSTD - WELL IS POP