KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION WELL COLLEGE

Form ACO-1 September 1999 Form Must Be Typed

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33583	API No. 15 - 099-23926-00-90 6
Name: Admiral Bay (USA) Inc.	County: Labette
Address: 7060B South Tucson Way	1.55
City/State/Zip: Centennial, CO 80112	1959' feet from S / (circle one) Line of Section
Purchaser: Southern Star	2038' feet from E / (W) (circle one) Line of Section
Operator Contact Person: Karla Peterson	Footages Calculated from Nearest Outside Section Corner:
Phone: (303) 350-1255	(circle one) NE SE (NW) SW
Contractor: Name: HAT Drilling	Lease Name: O'Brien Well #: 6-35
License: 33734	Field Name: Mound Valley
Wellsite Geologist: Greg Bratton	Producing Formation: Summit, Excello
Designate Type of Completion:	Elevation: Ground: 834' Kelly Bushing:
New Well Re-Entry Workover	Total Depth: 905' Plug Back Total Depth:
OilSWDSIOWTemp. Abd.	Amount of Surface Pipe Set and Cemented at 20' Feet
✓ Gas ENHR Ø SIGW	Multiple Stage Cementing Collar Used? Yes No
Dry Other (Core, WSW, Expl., Cathodic, etc)	If yes, show depth setFeet
If Workover/Re-entry: Old Well Info as follows:	If Alternate II completion, cement circulated from 895
Operator:	feet depth to \mathcal{D} w/ loo sx cmt.
Well Name:	Alt 2-DIS 6/6/08
Original Comp. Date: 7/26/06 Original Total Depth: 905	Drilling Fluid Management Man (Data must be collected from the Reserve Pit)
Deepening Re-perf Conv. to Enhr./SWD	
Plug Back Plug Back Total Depth	Chloride content ppm Fluid volume bbls Dewatering method used _air dry
Commingled Docket No.	
Dual Completion Docket No	Location of fluid disposal if hauled offsite:
Other (SWD or Enhr.?) Docket No	Operator Name:
	Lease Name: License No.:
Z/148/06- 2- 7-07 7/19/06 Z/26/06- 12/17/07 Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R East West
Recompletion Date Recompletion Date	County: Docket No.:
Per Oper	
1266 5013	
· · · · · · · · · · · · · · · · · · ·	th the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, ver or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply.
	12 months if requested in writing and submitted with the form (see rule 82-3-
	s and geologist well report shall be attached with this form. ALL CEMENTING
TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells	s. Submit CP-111 form with all temporarily abandoned wells.
	late the oil and gas industry have been fully complied with and the statements
nerein are complete and correct to the best of my knowledge.	
Signature:	KCC Office Use ONLY
Poll & alpha	N'
Title: Date: 4///01	Letter of Confidentiality Received
Subscribed and sworn to before me this Holday of April 1	If Denied, Yes Date: RECEIVED Wireline Log Received KANSAS CORPORATION COMMISSI
20 08.	
Notary Public: Lina M Jung &	Geologist Report Received APR 1 8 2008
5-21-08	- J of Significant
Date Commission Expires:	CONSERVATION DIVISION WICHITA, KS

Side Two

onerator Name. Adi	Name: Admiral Bay (USA) Inc.					O'Brien	•	Well #: <u>6-35</u>			
Sec. 35 Twp. 33 S. R. 18 ✓ East ☐ West					County: Labette						
NSTRUCTIONS: S ested, time tool ope emperature, fluid red Electric Wireline Log	n and closed, flowir covery, and flow rat	ng and shut es if gas to	t-in pressure surface test	s, whether , along with	shut-in pre	essure reached	I static level, hyd	rostatic press	ures, botte	om hole	
Drill Stem Tests Taken (Attach Additional Sheets) Samples Sent to Geological Survey Yes ✓ No Cores Taken Yes ✓ No					V	.og Forma	tion (Top), Depth	and Datum	Sample		
					Nam		Тор	Datum			
					Exce		321'	513'			
Electric Log Run				Riverton				791' 43'			
ist All E. Logs Run:					Miss	sissippian		805'		29'	
High Resolution Co Gamma Ray/Neutro Dual Induction LL3/ Mud Log	on/CCL	y Neutron I	Log								
		Repo		G RECORD		ew Used	ction, etc.				
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)		W	/eight s. / Ft.	Setting Depth	Type of Cement	# Sacks Used		Type and Percent Additives	
Surface	9 5/8"	8 5/8"		20 LB		20'	Portland			7.44.4.05	
Production	6 3/4"	4 1/2"	4 1/2"		.В	898'	Thickset	100	Kol &	Kol & Flo seal; gel	
			ADDITIONA	AL CEMEN	TING / SQL	JEEZE RECOR	D				
Purpose: Perforate Protect Casing Plug Back TD Plug Off Zone	Depth Type of Cement Top Bottom Protect Casing Plug Back TD			ks Used			Type and Percent Additives				
Shots Per Foot			ID - Bridge Pl		 De		acture, Shot, Cemer		ord		
Specify Footage of Each Interval Perforated 4 291-196'; 320-326'					(Amount and Kind of Material Used) Depth 3700# 20/40; 440 bbls water; 280 gal 7.5% HCL 291-196; 320-326						
					-	3700# 20/40	; 440 bbls wate	r; 280 gal 7.	5% HCL	291-196'; 320-326'	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,											
		and the same state of the same									
TUBING RECORD	Size	Set At		Packer	· At	Liner Run					
h h				. 30101			Yes No)	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Date of First, Resumero	Production, SWD or I	Enhr.	Producing Me	ethod	Flowing	Pump	ing Gas Li	ift 📋 Ot	her <i>(Explain</i>)	
Estimated Production Per 24 Hours	Oil	Bbis.	Gas	Mcf	Wate	er E	Bbls.	Gas-Oil Ratio		Gravity	
Disposition of Gas	METHOD OF	COMPLETIO	N			Production Inte	rval	K		RECEIVED RPORATION CO	
								I,	・***ひれる しし	MEDICALION CO	