

JOHN JAY DARRAH, JR.
 PHONE 316-263-2243
 SUITE 1010, CENTURY PLAZA BUILDING
 WICHITA, KANSAS 67202

ROGERS #1 A WORKOVER (Salt Water Disposal)

8/21/79 Move in CT. Found 2 bridges semi-solid at 3576', drill to 3584', bail heavy drilling mud.

8/22/79 Clean out to 3600', perf. 3264' to 3267, 4 per foot, swab hole down. Show oil. Shut down.

8/23/79 ONFU - 25' oil. Acid w/250 BDA, treat 100#, load of 89 bbls. SW down, raw acid coming back.
 Swab test: 12 PM - 1.74 bbls 25% O
 1 PM - .74 bbls 70% O
 2 PM - .30 bbls 70% O
 3 PM - .30 bbls 70% O
 Acid must be channeled.

8/24/79 ONFU - 150' clean, 35.1' gassy oil. Swabbed w/10sx cement, held OK, shut down. (we will evaluate this zone at a later date.)

8/25/79 Sb hole dw - cement 3242', drlg to DBP @ 3326' - knock DBP down.

8/27/79 Drlg on DBP, drlg insert + 3' cement, total 3606 SD

8/28/79 Drlg to 3625' SD, samples shaley.

8/29/79 Drlg to 3628', dolomite in samples, Sb down, drilling to 3631', rig up to run tubing w/drill collars & bit to drill with reverse circulation, SD.

8/30/79 Ran tubing w/2 drill collars & 4-7/8" bit. Drlg new hole from 3621' to 3626'.

8/31/79 Drlg to 3656'.

9/1/79 Pulled tubing, put on new bit, SD.

9/4/79 Drlg from 3656' to 3702'.

9/5/79 Changed bit, added 4 more drill collars.

9/6/79 Drlg very hard and slow, made 2.5', TD now 3706', bit went bad, pulled up into 5 1/2", finally located Button bit.

9/7/79 Shut down.

9/8/79 Pulled tubing, waiting for arrival of bit.

9/9/79 Ran button bit, drlg to 3743', water loss increased to 25 bbls per hour, SD.

9/10/79 Drlg to 3781, water loss increase to 80 BPH.

9/11/79 Fluid 1200', SB, could not lower, ran retrieval to 2920', perf. 995', 4 shots, ran tubing and packer to 1053', start cement, 185sx light, 100 sx conn to cement circ, stage, stage, stage, stage, test 1000#, cement circulated.

9/12/79 Drilled 50' cement, hole dry, retrieved bridge plug.

9/15/79 Running fiberglass tubing.

NOTE: This SWD will be expensive, but should be a good one.