

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

* Final ACO-1
ORIGINAL
Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

AMENDED

Operator: License # 33190
 Name: Noble Energy, Inc.
 Address: 1625 Broadway, Suite 2200
 City/State/Zip: Denver, CO 80202
 Purchaser: Southern Star
 Operator Contact Person: Jennifer Barnett
 Phone: (303) 228-4235
 Contractor: Name: Excell Services Inc., Wray, CO
 License: 8273
 Wellsite Geologist: none
 Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SIOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., Cathodic, etc)
 If Workover/Re-entry: Old Well Info as follows:
 Operator: n/a
 Well Name: _____
 Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back Plug Back Total Depth
 Commingled Docket No. _____
 Dual Completion Docket No. _____
 Other (SWD or Enhr.?) Docket No. _____

9/16/2008	9/17/2008	11/18/2008
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 023-21027-00-00
 County: Cheyenne
 NE SW NW SE Sec. 7 Twp. 2 S. R. 38 East West
1,830' feet from S N (circle one) Line of Section
2,190' feet from E W (circle one) Line of Section
 Footages Calculated from Nearest Outside Section Corner:
 (circle one) NE SE NW SW
 Lease Name: Keller Farms Well #: 33-7
 Field Name: Cherry Creek Niobrara Gas Area
 Producing Formation: Niobrara
 Elevation: Ground: 3340' Kelly Bushing: 3346'
 Total Depth: 1463' Plug Back Total Depth: 1414'
 Amount of Surface Pipe Set and Cemented at 245' cmt w/ 115 sx Feet
 Multiple Stage Cementing Collar Used? Yes No
 If yes, show depth set _____ Feet
 If Alternate II completion, cement circulated from n/a
 feet depth to _____ w/ _____ sx cmt.

Drilling Fluid Management Plan Air I nur 3-5-09
 (Data must be collected from the Reserve Pit)
 Chloride content _____ ppm Fluid volume _____ bbls
 Dewatering method used _____
 Location of fluid disposal if hauled offsite: _____
 Operator Name: _____
 Lease Name: _____ License No.: _____
 Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
 County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Jennifer Barnett
 Title: Regulatory Analyst Date: 1/22/09
 Subscribed and sworn to before me this 22 day of JANUARY
09
 Notary Public: Mendi Jar
 Date Commission Expires: My Commission Expires 09/11/2010

KCC Office Use ONLY


Letter of Confidentiality Received **RECEIVED**

If Denied, Yes Date: _____

Wireline Log Received **KANSAS CORPORATION COMMISSION**

Geologist Report Received **JAN 26 2009**

UIC Distribution **CONSERVATION DIVISION**
WICHITA, KS



Operator Name: Noble Energy, Inc. Lease Name: Keller Farms Well #: 33-7
 Sec. 7 Twp. 2 S. R. 38 East West County: Cheyenne

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Triple Combo (DEN/NEU/IND), CBL/CCL/GR	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample Name Top Datum Niobrara 1274'
---	---

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 7/8"	7"	17 Lbs/Ft.	245'	50/50 POZ	115 sx	3% CaCl, .25% Flo-cele
Production	6-1/4"	4-1/2"	9.5 Lbs/Ft.	1449'	Lead Type III	29 sx	12% gel, 2% CaCl, .25% Polyflake
					Tail Type III	56 sx	2% gel, 1% CFL-80

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate				
<input type="checkbox"/> Protect Casing				
<input type="checkbox"/> Plug Back TD				
<input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
3 SPF	Perf Niobrara interval from 1274'-1308'	Niobrara frac'd with 500 gals 7.5% HCL acid, 12,000 gals of	
	(34', 3spf, 102 holes) .41" EHD, 120 degree phase	25% CO2 foamed gel pad; 31,831 gals 25% CO2 foamed	
		gel carrying 100,020 lbs 16/30 sand. ATP-552 psi; ATR-12.3 bpm.	

TUBING RECORD	Size	Set At	Packer At	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
---------------	------	--------	-----------	---

Date of First, Resumerd Production, SWD or Enhr. 1/19/2009		Producing Method <input checked="" type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)			
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity
	0	78	0	0	

Disposition of Gas Vented Sold Used on Lease *(If vented, Submit ACO-18.)*

METHOD OF COMPLETION Open Hole Perf. Dually Comp. Commingled Other (Specify) _____

Production Interval _____

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-298-3010
 Fax: 303-298-8143
 E-mail: bisonoil1@qwest.net

INVOICE # 7903
 LOCATION C.R. 22nd W Ks
 FOREMAN Eric, Tom, Matt

TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RGE	COUNTY	FORMATION
9-16-08	Keller Farms 33-7	7	2 ^s	38 ^w	Cheyenne	
CHARGE TO <u>Excel Services</u>			OWNER <u>by</u>			
MAILING ADDRESS			OPERATOR <u>mark</u>			
CITY			CONTRACTOR <u>Rip J</u>			
STATE ZIP CODE			DISTANCE TO LOCATION <u>60 miles</u>			
TIME ARRIVED ON LOCATION <u>2:45</u>			TIME LEFT LOCATION			

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE	TUBING SIZE	PERFORATIONS		THEORETICAL	INSTRUCTED
<u>9 3/8</u>					
TOTAL DEPTH <u>250</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
<u>Set @ 245</u>	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>7"</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>239</u>		TREATMENT WA	TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT <u>17^z</u>	PACKER DEPTH		<input checked="" type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM	
CASING CONDITION <u>good</u>			<input type="checkbox"/> PRODUCTION CASING	INITIAL BPM	
PRESSURE SUMMARY			<input type="checkbox"/> SQUEEZE CEMENT	FINAL BPM	
BREAKDOWN or CIRCULATING psi	AVERAGE psi		<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM	
FINAL DISPLACEMENT psi	ISIP psi		<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM	
ANNULUS psi	5 MIN SIP psi		<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM	
MAXIMUM psi	16 MIN SIP psi		<input type="checkbox"/> MISC PUMP	HYD HP = RATE X PRESSURE X 4.08	
MINIMUM psi			<input type="checkbox"/> OTHER		

INSTRUCTIONS PRIOR TO JOB met R.P., safety meeting, Est. circ. in P 115 stks amt (13 bbls mix water) yield 1.13
Density 15.2, Displace 9 bbls H₂O, shut in well wash up to pit

JOB SUMMARY
 DESCRIPTION OF JOB EVENTS met R.P. (2:50) safety meeting (3:00) Est. circ. + 3:05 + met R.P. 115 stks amt (12.97)
Displace 9 bbls H₂O (3:13) shut in well wash up to pit (3:49)

RECEIVED
 KANSAS CORPORATION COMMISSION
 JAN 26 2009
 CONSERVATION DIVISION
 WICHITA, KS

Am Grady AUTHORIZATION TO PROCEED Paul TITLE 9-16-08 DATE

Customers hereby acknowledge and specifically agree to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-298-8143
 E-mail: bisonoil1@qwest.net

INVOICE # 7904
 LOCATION c.r. 22 + W Ks
 FOREMAN Eric, Tom, Matt

TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RSE	COUNTY	FORMATION
9-17-08	Keller Farms 33-7	7	25	39	Cheyenne	
CHARGE TO <u>Edge H Services</u>			OWNER			
MAILING ADDRESS			OPERATOR <u>Joe</u>			
CITY			CONTRACTOR <u>Edge H</u>			
STATE ZIP CODE			DISTANCE TO LOCATION <u>60 miles</u>			
TIME ARRIVED ON LOCATION <u>5:00</u>			TIME LEFT LOCATION			

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE	TUBING SIZE	PERFORATIONS	THEORETICAL		INSTRUCTED
<u>6 1/4</u>					
TOTAL DEPTH <u>1452</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
<u>P&A 1414</u>	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>4 1/2</u>	TUBING CONDITION	TREATMENT VIA	TUBING		
CASING DEPTH <u>1442</u>	PACKER DEPTH		TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT			<input type="checkbox"/> SURFACE PIPE		BREAKDOWN BPM
CASING CONDITION <u>good</u>			<input checked="" type="checkbox"/> PRODUCTION CASING		INITIAL BPM
			<input type="checkbox"/> SOBBE CEMENT		FINAL BPM
			<input type="checkbox"/> ACID BREAKDOWN		MINIMUM BPM
			<input type="checkbox"/> ACID STIMULATION		MAXIMUM BPM
			<input type="checkbox"/> ACID SPOTTING		AVERAGE BPM
			<input type="checkbox"/> MISC PUMP		
			<input type="checkbox"/> OTHER		HYD HHP = RATE X PRESSURE X 40.8

PRESSURE SUMMARY			
BREAKDOWN or CIRCULATING	psi	AVERAGE	psi
FINAL DISPLACEMENT	psi	ISIP	psi
ANNULUS	psi	5 MIN SIP	psi
MAXIMUM	psi	15 MIN SIP	psi
MINIMUM	psi		

INSTRUCTIONS PRIOR TO JOB MTRP, safety meeting, 30 BBL mud Flush, m + P 29 SK's cement yield 2.64 Density 1.2, m + P 56 SK's cement yield 1.83 Density 1.28 Drop Plug, Displace 22.9 BBLs H₂O, Set Plug @ 1400-1500 psi.

JOB SUMMARY
 DESCRIPTION OF JOB EVENTS MTRP (5:55) - safety meeting (7:03) - 30 BBL mud Flush (7:05) - m + P 29 SK's cement (7:09) - m + P 56 SK's cement (7:14) - Drop Plug (7:20) - Displace 22.9 BBLs H₂O (7:24) - Set Plug @ 1400-1500 psi (7:36)

Time	Flow	psi	
7:27	10	200	
7:32	20	400	
7:35	22.9	1500	4 bbls to pit

RECEIVED
 KANSAS CORPORATION COMMISSION
 JAN 26 2009
 CONSERVATION DIVISION
 WICHITA, KS

Joe Heltner
 AUTHORIZATION TO PROCEED TITLE DATE
 9-17-08

Customers hereby acknowledge and specifically agree to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.