

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. \_\_\_\_\_

LOCATION SE NW NE

SEC. 17 TWP. 9 RGE. 26 W

Dry Hole X Abandoned Oil Well \_\_\_\_\_ Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 5 Lease \_\_\_\_\_ Mills \_\_\_\_\_

Operator G-M-R Oil Co Address Wichita, Kans

Field \_\_\_\_\_ County Sheridan

Total Depth 4000 Feet.

(Describe briefly the manner in which the well was plugged)

8 5/8" at 300' circulated with cement - 5 1/2" at 4050' with  
100 sax cement behind - perforations at 4022'.

Filled with chat to 4010', set 4 sax cement with dump bailer,  
pulled 3400' 5 1/2", mud to 300', set rock and 10 sax cement,  
mud to 35', set rock and 10 sax cement to bottom cellar.

RECEIVED  
STATE CORPORATION COMMISSION  
2-19-53  
FEB 19 1953  
CONSERVATION DIVISION  
Wichita, Kansas

District Conservation Agent  
Date 2-14-53

**PLUGGING**  
FILE SEC 17 T 9 R 26 W  
BOOK PAGE 80 LINE 13