## Kansas Corporation Commission Oil & Gas Conservation Division



## **WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE**

Operator: License # 5056	API No. 15 - 151-22,043 - CCC I
Name: F.G. Holl Company, L.L.C.	County: Pratt
Address: 9431 East Central, Suite #100	
City/State/Zip: Wichita, Kansas 67206-2543	feet from (S) / N (circle one) Line of Section
Purchaser: NCRA	1980 feet from (E)/ W (circle one) Line of Section
Operator Contact Person: Franklin R. Greenbaum	Footages Calculated from Nearest Outside Section Corner:
Phone: (316_) 684-8481	(circle one) NE (SE) NW SW
Contractor: Name: Sterling Drilling Company	Lease Name: DORIS LAMBERT "B" Well #: 1-31
License: 5142	Field Name: Jem
Wellsite Geologist: Jeff Klock	Producing Formation: Mississippian Kinderhook Chert
Designate Type of Completion:	Elevation: Ground: 1892' Kelly Bushing: 1901'
New Well Re-Entry Workover	Total Depth: 4765' Plug Back Total Depth: 4630'
OilSWDSIOWX_Temp. Abd.	Amount of Surface Pipe Set and Cemented at 213' KB Feet
Gas ENHR SIGW RECEIVE	Multiple Stage Cementing Collar Used?
Dry Other (Core, WSW, Expl., Cathodic, etc)	If yes, show depth setFeet
If Workover/Re-entry: Old Well Info as follows: JUL 1 5 2004	If Alternate II completion, cement circulated from
Operator: F.G. Holl Company, L.L.C.	feet depth tosx cmt.
Well Name: DORIS LAMBERT "B" No. 1-31 KCC WICH	Drilling Fluid Management Plan
Original Comp. Date: 04/27/1991 Original Total Depth: 4765'	(Data must be collected from the Reserve Pit)
Deepening Re-perf Conv. to Enhr./SWD	Chloride contentppm Fluid volumebbls
Plug Back Plug Back Total Depth	Dewatering method used
Commingled Docket No	Location of fluid disposal if hauled offsite:
Dual Completion Docket No	·
Other (SWD or Enhr.?) Docket No	Operator Name:
RU: 05/17/2004 -03/34/4991 RD: 06/03/2004	Lease Name: License No.:
Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R East West
Recompletion Date Recompletion Date	County: Docket No.:
INSTRUCTIONS: An original and two copies of this form shall be filed with Kansas 67202, within 120 days of the spud date, recompletion, workove	
Information of side two of this form will be held confidential for a period of 1.	2 months if requested in writing and submitted with the form (see rule 82-3-
107 for confidentiality in excess of 12 months). One copy of all wireline logs: TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells.	*
All requirements of the statutes, rules and regulations promulgated to regula	
herein are complete and correct to the best of my knowledge.	
Signature:	KCC Office Use ONLY
Title: Exploration Manager Date: 07/13/2004	Letter of Confidentiality Attached
Subscribed and sworn to before me this	If Denied, Yes Date:
Brown & North and	Wireline Log Received
Betty B. Herring	Geologist Report Received
Notary Public:	UIC Distribution
D	olic – State of Kansas
	1. Exp. 450 500

Operator Name: F.0						OORIS LAM	BERT "B"	_ Well #: <del>1-</del> 3	31		
Sec. 31 Twp. 2	29 s. R. <u>13</u>	East	✓ West	Count	y: <u>Pra</u>	tt					
INSTRUCTIONS: Si tested, time tool oper temperature, fluid red Electric Wireline Log	n and closed, flowing covery, and flow rate	and shuts if gas to	in pressures, surface test, a	whether s along with	hut-in pre	ssure reached	static level, hydro	static pressur	es, bottom h	nole	
Drill Stem Tests Take	✓ Yes  No			[V.	✓ Log Formation (Top), Depth and Datum				Sample		
Samples Sent to Geo	<b></b> ✓ Ye	s 🗌 No		Nam	<b>e</b>	•	Тор	Dat	tum		
Cores Taken Electric Log Run (Submit Copy)		☐ Ye	. <u>~</u>		See	original					
List All E. Logs Run:			·		·				·		
•											
				RECORD	✓ Ne						
	Size Hole		t all strings set- e Casing	1	surface, inte	rmediate, produc	Type of	# Sacks	Type and	l Percent	
Purpose of String	Drilled	Set	(In O.D.)	Lbs	. / Ft.	Depth	Cement	Used	<del> </del>	tives	
Surface	17-1/4"	13-3/8"		48#		213'KB	60/40 Poz	225sx	2% gel		
Production 7-7/8"		4-1/2"		10.5#	0.5# 4764'KB Lite			100sx	Salt, Gilsonite		
							50/50 Poz	125sx			
		· T	ADDITIONAL	L CEMENT	ING / SQL	JEEZE RECOR					
Purpose:  — Perforate — Protect Casing — Plug Back TD — Plug Off Zone	Depth Top Bottom	Туре	of Cement	#Sack	s Used		Type and F	Percent Additives	· .		
Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated					Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)  Depth					
4 SPF	4450', 4452', 4454', 4456', & 4458'. Mississippian					Treat w/ 1000 gal 7-1/2% dsfe acid.					
	Kinderhook CH	CHert				Treat w/ 1000 gal 10% dsfe acid.					
4 SPF	4450'-4458' Re	4450'-4458' Reperf Missi-Kinderhook Chert					Frac w/ 3000# 100 Mesh sand, 12000# Otta				
	CIBP @4630'					wa sand, 7000# 12/20 Brady sand & 3000#					
	4524'-4530', 45	4524'-4530', 4534'-4542' Viola, 4638-4640Simp S.				AcFrac CR -400 12/20 (25000# total Prpt.)					
TUBING RECORD	Size 2-3/8"	Set At		Packer	At	Liner Run	Yes 🗸 No				
Date of First, Resumed	d Production, SWD or E	nhr.	Producing Met	thod	Flowin	g Pump	ing Gas Li	ft Oth	ner (Explain)		
Estimated Production Per 24 Hours	Oil	Bbis.	Gas	Mcf	Wat	er (	3bls. (	Gas-Oil Ratio		Gravity	
Disposition of Gas	METHOD OF	COMPLETIC	)N	·		Production Inte	rval				
Vented Sold	Used on Lease		Open Hole		rf. 🔲 l	Dually Comp.	Commingled			;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;	