

15-109-20638-00-00  
4-061038

1-21

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Number: 15-109-20,638-00-00

ES  
5/27/09

S2 N2 SW /4 SEC. 20 / 22, 11 S, 33 W  
1650 feet from S section line  
3960 feet from E section line

Operator license# 31120

Lease Regan Well # 1

Operator: Pelican Hill Oil & Gas, Inc.

County: Logan 147.38

Address: 1401 N. ElCamino Rd. #203  
San Clemente, CA 92672

Well total depth 4535 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8 5/8 Inch @ 257 feet

Aband. oil well\_\_\_, Gas well\_\_\_, Input well\_\_\_, SWD\_\_\_, D & A X

Plugging contractor: Abercrombie RTD, Inc. License# 30684

Address: Wichita, Kansas 67202

Company to plug at: Hour: 10:00 A.M. Day: 21 Month: January Year: 1997

Plugging proposal received from: Tony

Company: Abercrombie RTD, Inc. Phone: \_\_\_\_\_

Were: Order 190 sxs 60/40 posmix - 6% gel with 1/4# floseal per sack.  
Space all plugs with heavy drilling mud through drill pipe.

1-27-1997  
1997 JAN 21 P 3:09

Plugging Proposal Received by: Herb Deines

Plugging operations attended by agent? All[ ], Part[ ], None[ X ]

Completed: Hour: 12:00 P.M., Day: 21, Month: January, Year: 1997

Actual plugging report: \_\_\_\_\_

- 1st. Plug at 2650' w/25 sxs. Anhydrite 2617' - 2695'.
- 2nd. Plug at 1650' w/100 sxs. Dakota 1338' - 1638'.
- 3rd. Plug at 310' w/40 sxs. Surface pipe at 257'.
- 4th. Plug at 40' w/10 sxs.
- 15 sxs in rathole.

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD\_\_\_ BAD\_\_\_ Anhy.plug: YES X NO\_\_\_  
Bottom plug(in place): YES\_\_\_, CALC\_\_\_, NO X Dakota plug: YES X, NO\_\_\_  
Plugged through TUBING\_\_\_, CASING\_\_\_ Elevation: 1638 GL

I did[ ] / did not[ X ] observe the plugging.

[Signature]  
DH (agent)  
Form CP-2/3

INVOICED

DATE JAN 28 1997

INV. NO. 47460  
1-21 MAR 27 1997