1-2815-063-21184-00-00 40

6-<u>Ø31656</u>

10:	API number: 15-965-21, 184
STATE CORPORATION COMMISSION	
CONSERVATION DIVISION - PLUGGING	<u>SESENE</u> /4 SEC. 11 , 11 S, 31 W
200 COLORADO DERBY BUILDING	3010 feet from S section line
WICHITA, KANSAS 672Ø2	
Operator license# <u>5123</u>	Lease <u>Lockwood Trust A</u> well # <u>2</u>
Operator: Pickrell Drilling Co. Inc.	County Gove
Address trace	Well total depth 4600 feet Conductor Pipe: inch @ feet
Address: IIØ N. Market	. Well total depth <u>4600</u> feet) "
wichita, Ks.	Conductor Pipe: inch @ feet
	Surface pipe 8 5/8 Inch @ 358 feet
Aband. oil well <u>xx</u> , Gas well <u>,</u> in	
Plugging contractor: A	Ilied Cement Co. License# 6050
Address: <u>Ness City, Ks.</u>	
Company to plug at: Hour: PM Day	
Plugging proposal received from: <u>Ed M</u>	ondero
Company: Pickrell	nhone.
	phone:
4 1/2 cemented from 1600 to surface.	note open to pert.
	RECEIVED
	STATE COORDINATION COMMINSSION
Plugging Proposal Received by:	FEB 1 4 1992
Plugging operations attended by agenta	Carl Goodrow 2-14-1992
Plugging operations attended by agent?	ATTEX J. Part[], Nonceftvation Division
Completed: Hour: <u>1:45PM</u> , Day <u>28</u> , Mo	wichita, Kansas
, Day 28 , MO	onth <u>January</u> , Year: <u>92</u>
Actual plugging: 8 5/8 at 358 w/190 sk	'e 112 of 4500 miles
Top perf at 4100. Plugged bottom w/sa	3. 4 1/2 at 4509 W/150 sks.
Squeezed 4 1/2. Tested 8 5/8 to 500 1	hs cement at ourfoce
	DS. Cement at Surface.
Remarks:	
Condition of casing (in hole): GOOD x	BAD Anhy, plug. VES v. No.
Condition of casing (in hole): GOOD x Bottom plug (in place): YES x , CALC	NO Dakota plum VEO
Bottom plug(in place):YES <u>x</u> , CALC	_, NO Dakota plug:YES, NO
thread thread housing, CASING _x	_, NO Dakota plug:YES, NO Elevation: 2947 GL
TALL THE A LANGE OF T	Dakota plug:YES, NO Elevation: 2947 GL lugging Call Southous
the gangual ing, CASING_x_	_, NO Dakota plug:YES, NO Elevation: 2947 GL