API number: 15-063-21,451

5-21

STATE CORPORATION COMMISSION	NR NR NR /4 GEG 44 44 G 44 U
CONSERVATION DIVISION - PLUGGING	<u>NE NW NW</u> /4 SEC. 10 , 11 S, 31 W
200 COLORADO DERBY BUILDING	4950 feet from S section line
WICHITA, KANSAS 67202	4290 feet from E section line
Operator license# 5422	Lease <u>Johnson Trust</u> well # 1
Operator: Abercrombie Drilling, Inc.	County <u>Gove</u> /53.95
Address: 150 N. Main	Well total depth <u>4737</u> feet
Suite #801	Conductor Pipe: 0 inch 0 0 feet
Wichita, Kansas 67202	Conductor Pipe: 0 inch 0 0 feet Surface pipe 8 5/8 Inch 0 283 feet
Aband. oil well, Gas well, Inp	out well, SWD, D & A _X_
Plugging contractor: Abercrombie RTD,	Inc. License# 30684
Address: Wichita, Kansas 67202	
Company to plug at: Hour: Day:	21 Month: May Year: 93
Plugging proposal received from: Bill	Craig
Company: Abercrombie RTD, Inc.	Phone: 316-262-1841
Were:Order 190 sxs. 60/40 posmix -	· 6% gel with 1/4# flocele.
	pipe with heavy mud.
Agent reported by Abercrombie	RTD, Inc. as giving orders was
Brush Beacon. Due to passage	of time, responsible agent in
office not identified. The p	olugs were reviewed and found to be
place correctly and in accord	lance with KCC District #4 criteria.
Plugging Proposal Received by:	
Plugging operations attended by agent?	
Completed: Hour:, Day:_21_, Mo	onth: <u>May</u> , Year: <u>1993</u>
Actual plugging report: 8 5/8" to 28	31.
1st. plug at 2560' w/25 sxs Anhyd	rite 2540' - 2567'.
2nd. plug at 1700' w/100 sxs Dakot	is a 1395' - 1695'. STATE RECEIVED
3rd. plug at 330' w/40 sxs Surfa	ice pipe to 283'.
4th. plug at 40' w/10 sxs.	TEB 100 100 100 100 100 100 100 100 100 10
Rathole with 15 sxs.	
	CONS. 1902
	Wichita ON Dur
Remarks:	CONSERVATION DIVISION
Condition of casing(in hole):GOODB	
Bottom plug(in place):YES,CALC Plugged through TUBING, CASING	,NO_X _Dakota plug:YES_X_,NO . Elevation: 2995GL
	
I did(V) did not [x] observe the p	olugging.
CATE 2-4-94	(agent)
39870	Form CP-2/3
WY. NO. STANDER	