STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

J. Lewis Brock
Administrator
500 Insurance Building
Wichita, Kansas 67202

15-195-20126-00-00

RECEIVED
STATE CORPORATION COMMISSION

AUG 1 5 1969

CONSERVATION DIVISION
Wichita, Kansas

18-15-1969

Operator's Full Name		Highway Corel			1969	•
Lease Name		nighway, ocial			*-	
			-			
Location		Sec.				
County	Trego		Total De	pth	4010	
Abandoned Oil Well_	Gas Well_	Input Well	swD	We11	D & A	X
Other well as herea	fter indicated					
Plugging Contractor	H-30 Drilling.	Incorporated.				•
Address 200 Nor		•		No		
		· '''				
The above well was p	olugged as follows:			<u>8</u>	Year <u>l</u>	969
The above well was p Ph7!8 5/8" Burface Top of Dakota section	olugged as follows: e casing, cement ciron @ 900'.	rculated with]	L75 S x.			
The above well was policy 8 5/8" Surface Fop of Dakota section in the control of the control	plugged as follows: e casing, cement cir on @ 900'. n heavy mud. Pulled	rculated with 1	175 Sx.	d 100 S	x. cement	thr
The above well was policy 8 5/8" Furface Fop of Dakota section inculated hole with the BP from 1130' to 80'	plugged as follows: e casing cement ciron @ 900'. h heavy mud. Pulled	rculated with l d DP to 1130' a 75' and displac	175 Sx. and displace eed 20 Sx. c	d 100 S ement t	x. cement hru DP fr	thr
The above well was policy 8 5/8" Furface Fop of Dakota section inculated hole with the BP from 1130' to 80'	plugged as follows: e casing cement ciron @ 900'. h heavy mud. Pulled	rculated with l d DP to 1130' a 75' and displac	175 Sx. and displace eed 20 Sx. c	d 100 S ement t	x. cement hru DP fr	thr
The above well was policy and the section of Dakota section circulated hole with the section of	plugged as follows: e casing cement ciron @ 900'. h heavy mud. Pulled	rculated with l d DP to 1130' a 75' and displac	175 Sx. and displace eed 20 Sx. c	d 100 S ement t	x. cement hru DP fr	thr
Operation Completed: The above well was possible. The above well was possi	plugged as follows: e casing cement ciron @ 900'. h heavy mud. Pulled	rculated with l d DP to 1130' a 75' and displac	175 Sx. and displace eed 20 Sx. c	d 100 S ement t	x. cement hru DP fr	thr
The above well was policy in the above well was policy in the section of Dakota sect	plugged as follows: e casing cement ciron @ 900'. h heavy mud. Pulled	rculated with l d DP to 1130' a 75' and displac	175 Sx. and displace eed 20 Sx. c	d 100 S ement t	x. cement hru DP fr	thr