



Kansas Corporation Commission Oil & Gas Conservation Division

Form ACO-1 October 2008 Form Must Be Typed

CONSERVATION DIVISION WICHITA, KS

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License # 33937	API No. 15 - 051-05576-00-02
Name: Meridian Energy Inc.	
Address 1: 1475 N. Ward Cr.	
Address 2:	990 Feet from 🕡 North / 🛄 South Line of Section
City: Franktown State: CO Zip: 80116 +	
Contact Person: Neal LaFon	
Phone: (303) 688-4022	
CONTRACTOR: License #_32810	County: Ellis
Name: Professional Pulling Service LLC	E 1 11
Wellsite Geologist:	Field Name: Bemis-Shuyts
Purchaser:	Arbuoklo
Designate Type of Completion:	Elevation: Ground: 1934 Kelly Bushing:
New Well Re-Entry Workover	Total Depth: 3500 Plug Back Total Depth:
Oil swp slow	Amount of Surface Pipe Set and Cemented at: Feet
Gas ENHR SIGW	Multiple Stage Cementing Collar Used? Yes No
CM (Coal Bed Methane) Temp. Abd.	If yes, show depth set:Feet
Dry Other	If Alternate II completion, cement circulated from:
(Core, WSW, Expl., Cathodic, etc.)	feet depth to:w/sx cmt.
If Workover/Re-entry: Old Well Info as follows:	
Operator: Virginia Drilling Inc.	Drilling Fluid Management Plan 0000 - AI+ I NOC
Well Name: #1 Feldkamp Original Comp. Date: 11/15/41 Original Total Depth: 3483	(Data must be collected from the Reserve Pit) 5-29-09
Original Comp. Date: 11/45/41 Original Total Depth: 3463	Chloride content: ppm Fluid volume: bbls
Deepening Re-perf Conv. to Enhr Conv. to SWD	Dewatering method used:
Plug Back: Plug Back Total Depth	Location of fluid disposal if hauled offsite:
Commingled Docket No.:	Operator Name:
Dual Completion Docket No.:	
Other (SWD or Enhr.?) Docket No.:	QuarterSecTwpS. R East West
7/3o/o 8 8/18/08 i//2/08 Spud Date or Date Reached TD Completion Date or	-
Spud Date or Date Réached TD Completion Date or Recompletion Date	County: Docket No.:
Kansas 67202, within 120 days of the spud date, recompletion, workover of side two of this form will be held confidential for a period of 12 months if	with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information requested in writing and submitted with the form (see rule 82-3-107 for confident well report shall be attached with this form. ALL CEMENTING TICKETS MUST of form with all temporarily abandoned wells.
All requirements of the statutes, rules and regulations promulgated to regula are complete and correct to the best of my knowledge.	ate the oil and gas industry have been fully complied with and the statements herein
Signature: Walk ton	, KCC Office Use ONLY
Title: President Date: 12/31/08	1/
	Letter of Confidentiality Received
Substribed and Sworn to before the this day of	, If Denied, Yes Date:
20 09	Wireline Log Received RECEIVED
Notary Public: KENDALLA BACICA Sa	
Date Commission Expires: STATE OF COLORADO	UIC Distribution AN 1 2 2009
DATE COMMISSION EXPIRED. STATE OF CULURADO	My Continuesion Expires
	07/26/2010 CONSERVATION DIVISION

Side Two

perator Name: Meri	dian Energy Inc.		Lease Name: .	Feldkamp		_ Well #: _#1	
		East West	County: Ellis	County: Ellis			
me tool open and clo	sed, flowing and shues if gas to surface to	nd base of formations put-in pressures, whethe est, along with final cha report.	enetrated. Detail all r shut-in pressure rea	cores. Report al ached static leve	l, hydrostatic pres	sures, bottom h	nole temperature, fluid lectric Wireline Logs
Drill Stem Tests Taken (Attach Additional Sheets) Samples Sent to Geological Survey ☐ Yes ☑ No			Log Formation (Top), D			□ Sample ZM	
		☐ Yes ☑ No	Nar	ne	le Top Datum		
Cores Taken Electric Log Run (Submit Copy)		☐ Yes					Sample ZAR Datum Une 194 Nee Rec
ist All E. Logs Run:							
:			NG RECORD Net-conductor, surface, in	New Used	ition, etc.		
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Liner		3 1/2		3500	mdc	225	Type and Percent Additives
		ADDITION	IAL CEMENTING /SC	NUEEZE DECODE			
Purpose: Depth Type of Cement Perforate Protect Casing Plug Back TD		#Sacks Used	#Sacks Used Type and Percent Additives			;	
Plug Off Zone							
Shots Per Foot		ION RECORD - Bridge P Footage of Each Interval	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used) Depth				
4 3473-3481				acidized 30	acidized 3000 gal HCL - polymer 4200 bbls.		
	,						RECENTED
						KAN	ISAS COFPORATION CO
							JAN 1 2 2009
TUBING RECORD:	NG RECORD: Size: Set At: Packer At:			Liner Run: Yes No WICKTYA, KA			
Date of First, Resumed	Production, SWD or Er	nhr. Producing N	fethod:	ing 🔽 Pump	ing Gas L	ift 🔲 Oth	er (Explain)
Estimated Production Per 24 Hours	Oil 10	Bbls. Gas	Mcf Wa	90	Bbls.	Gas-Oil Ratio	Gravity
DISDOCITIE	ON OF GAS:		METHOD OF COMPI			PRODUCTION	ON INTERVAL:
Vented Sold	_	Open Hale	Perf. Dual		ommingled 34	173-3481	SIGNATED VAC.
	omit ACO-18.)	Other (Specify)			_		