

To: STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, Kansas 67202

API NUMBER 15-~~124~~-19724-00-00<sup>205</sup>  
NE SE NW Sec/Twp/Rge 16-29-17E  
3803 (GPS) feet from south section line  
2957 (GPS) feet from east section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 101  
Operator: State Of Kansas Fec Funds  
Name & Mary F. Douglas Lease Project  
Address \_\_\_\_\_  
AB oil well XXXXXX Gas Well \_\_\_\_\_

Lease/Well# Douglas, Mary F. GPS #19  
County Wilson  
Well Total Depth 860 feet  
Production Pipe: 2 Size Feet 860  
Surface Casing: 12 Size Feet NA  
SWD Well/ Input Well \_\_\_\_\_ D & A \_\_\_\_\_

Other well as hereinafter indicated: \_\_\_\_\_

Plugging Contractor: Kepley Well Service, LLC Lic. # 33749

Address: 19245 Ford Road, Chanute, Kansas 66720

Company to plug at: \_\_\_\_\_ Hour: \_\_\_\_\_ Day: 4 Month: 2 2009

Plugging proposal received from: Mike Kepley

Company Name: Kepley Well Service, LLC Phone: \_\_\_\_\_

Were: Clean well to TD and pump full of cement thru cement string.

Plugging Proposal Received by: Alan M. Dunning

Plugging attended by Agent: All \_\_\_\_\_ Part XXXXXX <sup>TECHNICIAN</sup> None \_\_\_\_\_

Operations Completed: Hour: \_\_\_\_\_ Day: 4 Month: 2 2009

Actual Plugging Report: A 1" cement string was washed down the outside of the 2" production pipe to 860'. A 1" cement string was washed down the inside of the 2" production pipe to 800'. The well was pumped full of cement from btm to top thru these cement strings. A total of 208 sacks of portland cement were used to plug well. The well was cut off below plow depth and the location restored.

RECEIVED  
KANSAS CORPORATION COMMISSION

FEB 19 2009

Remarks: Control # 20090005-019  
(If additional description is necessary, use BACK of this form.)

CONSERVATION DIVISION  
WICHITA, KS

I partially observed this plugging

Signed:

Alan M. Dunning  
TECHNICIAN

*PKT*