

To: STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, Kansas 67202

API NUMBER 15-~~198~~<sup>205</sup>-19710-00-00  
NW SE NW Sec/Twp/Rge 16-29-17E  
3937 (GPS) feet from south section line  
3860 (GPS) feet from east section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 101  
Operator: State Of Kansas Fee Funds  
Name & Mary F. Douglas Lease Project  
Address \_\_\_\_\_  
AB oil well XXXXXX Gas Well \_\_\_\_\_

Lease/Well# Douglas, Mary F. GPS #05  
County Wilson  
Well Total Depth 1000 (est) feet  
Production Pipe: NA Size Feet NA  
Surface Casing: 10 Size Feet NA  
SWD Well/ Input Well \_\_\_\_\_ D & A \_\_\_\_\_

Other well as hereinafter indicated: \_\_\_\_\_

Plugging Contractor: Kepley Well Service, LLC Lic. # 33749

Address: 19245 Ford Road, Chanute, Kansas 66720

Company to plug at: \_\_\_\_\_ Hour: \_\_\_\_\_ Day: 17 Month: 3 2009

Plugging proposal received from: Mike Kepley

Company Name: Kepley Well Service, LLC Phone: \_\_\_\_\_

Were: Clean well to TD and pump full of cement thru cement string.

Plugging Proposal Received by: Alan M. Dunning

Plugging attended by Agent: All \_\_\_\_\_ Part \_\_\_\_\_ None XXXXXX

Operations Completed: Hour: \_\_\_\_\_ Day: 17 Month: 3 2009

Actual Plugging Report: The well was washed to 30' where the pipe hit solid. The drilling rig was moved to the location and drilled to 80' thru steel. A 1" cement string was then washed to 80' where the pipe hit solid. The well was pumped full of cement thru this cement string. A total of 30 sacks of portland cement were used to plug well. The well was cut off below plow depth and the location restored.

RECEIVED  
KANSAS CORPORATION COMMISSIO

APR 02 2009

Remarks: Control # 20090005-005

(If additional description is necessary, use BACK of this form.)

CONSERVATION DIVISION  
WICHITA, KS

I  did not observe this plugging.

Signed:

Alan M. Dunning  
TECHNICIAN