

To: STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, Kansas 67202

API NUMBER 15-~~183~~-19721-00-00 <sup>205</sup>  
SW SW NW Sec/Twp/Rge 16-29-17E  
2950 (GPS) feet from south section line  
4702 (GPS) feet from east section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 101  
Operator: State Of Kansas Fee Funds  
Name & Mary F. Douglas Lease Project  
Address \_\_\_\_\_  
AB oil well XXXXXX Gas Well \_\_\_\_\_

Lease/Well# Douglas, Mary F. GPS #16  
County Wilson  
Well Total Depth 850 feet  
Production Pipe: 4 Size Feet 850  
Surface Casing: NA Size Feet NA  
SWD Well/ Input Well \_\_\_\_\_ D & A \_\_\_\_\_

Other well as hereinafter indicated: \_\_\_\_\_

Plugging Contractor: Kepley Well Service, LLC Lic. # 33749

Address: 19245 Ford Road, Chanute, Kansas 66720

Company to plug at: \_\_\_\_\_ Hour: \_\_\_\_\_ Day: 30 Month: 12 2008

Plugging proposal received from: Mike Kepley

Company Name: Kepley Well Service, LLC Phone: \_\_\_\_\_

Were: Clean well to TD and pump full of cement thru cement string.

Plugging Proposal Received by: Alan M. Dunning

Plugging attended by Agent: All \_\_\_\_\_ Part \_\_\_\_\_ Technician XXXXXX

Operations Completed: Hour: \_\_\_\_\_ Day: 30 Month: 12 2008

Actual Plugging Report: A swedge was lowered to 850' where it hit solid. The swedge was then removed and the well perforated at 300' and 150'. A 1" cement string was lowered to 850' and the well pumped full of cement from btm to top. A total of 78 sacks of portland cement were used to plug well. The well was cut off below plow depth and the location restored.

RECEIVED  
KANSAS CORPORATION COMMISSION  
JAN 23 2009

CONSERVATION DIVISION  
WICHITA, KS

Remarks: Control # 20090005-016

(If additional description is necessary, use BACK of this form.)

I did not observe this plugging.

Signed:

Alan M. Dunning  
TECHNICIAN

*[Handwritten initials/signature]*