15-109-ZOZG7-00-00 AFFIDAVIT OF COMPLETION R

MILDAVII OF CONFIEI	· (REV) ACO-1
This form shall be filed in duplicate with the Kansrado Derby Building, Wichita, Kansas 67202, within the well, regardless of how the well was completed. Attach separate letter of request if the information on side two will then be held confidential. Circle one: Oil, Gas, Dry SWD, OWWO, Injection. Applications must be filed for dual completion, commattach wireline logs (i.e. electrical log, sonice KCC # (316) 263-3238. (Rules 82-2-105 & 82-2-125)	ten days after the completion of ation is to be held confidential. If side one will be of public record and Type and complete ALL sections. Type and complete ALL sections.
OPERATOR First Energy Corporation	API NO. 15-109-20.267-00-00
ADDRESS 633 North State St., P.O. Box 2066	COUNTY_Logan
Jackson, Mississippi 39205	FIELDNW Winona
**CONTACT PERSONGerry W. Brown	PROD. FORMATION
PHONE308-345-2480	LEASE Kronvall
PURCHASER	WELL NO. #43-4
ADDRESS	
	WELL LOCATION C NE SE
DRILLING Murfin Drilling CONTRACTOR	2200 Ft. from South Line and
ADDRESS 617 Union Center	600 Ft. from <u>East</u> Line of
Wichita, Kansas 67202	the <u>SE/4 SEC. 4 TWP.11S RGE. 36W</u>
PLUGGING Murfin Drilling CONTRACTOR	WELL PLAT
ADDRESS 617 Union Center	KCC KGS
Wichita, Kansas 67202	(Office
TOTAL DEPTH 5040' PBTD	Use)
SPUD DATE 12-13-82 DATE COMPLETED 12-21-82	4
ELEV: GR 3380 DF KB	
DRILLED WITH 《公共版》(ROTARY)(《本文》)TOOLS	
Amount of surface pipe set and cemented 300'	. DV Tool Used? No
STATE OF Nebraska	•
Gerry W. Brown	Willow SS, I,
Gerry W. Brown OF LAWFUL AGE, BEI	NG FIRST DULY SWORN UPON HIS OATH,
DEPOSES THAT HE IS Representative (FOR)()	OFN First Energy Corporation
OPERATOR OF THE Kronvall LEASE,	AND IS DULY AUTHORIZED TO MAKE
THIS AFFIDAVIT FOR AND ON THE BEHALF OF SAID OPERATOR	, THAT WELL NO. 43-4 ON
SAID LEASE HAS BEEN COMPLETED AS OF THE 21st DAY OF	F December , 19 82 , AND THAT
ALL INFORMATION ENTERED HEREIN WITH RESPECT TO SAID WE	ELL IS TRUE AND CORRECT.
FURTHER AFFIANT SAITH NOT.	h 110
SUBSCRIBED AND SWORN BEFORE ME THIS 27th DAY OF	Gerry W. Brown
GENERAL NOTARY - State of Nebraska	Kathlien SAESENED MISSION
MY COMMISSION EXPIRES: My Comm. Exp. Nov. 21, 1883	NOTARSTANGE BLIC Kathleen Shaffer
**The person who can be reached by phone regarding any	questions concerning this infor-

**T required if the well produces more than 25 BOPD or is located in a Basic With Pool. WELL LOG

EDE TWU

WELL LOG

Show all important zones of parosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

FORMATIO	N DESCRIPTION,	CONTENTS ST						
TORMATIO	N DESCRIPTION,	CONTENTS, ETC	······································	ТОР		воттом	NAME	DEPT
			i			1		
			'					į
					- 1			
				1	- 1			
				1				1
					1			İ
				1	- 1			
					1			
				1	- 1			
					I	·		
			٠.			فمعرو فالمحاف		
			1 .					
	*	•		1.				İ
	*					*		
								j
					1	j		
					- 1			
				1		,		•
						· [ŀ
								:
		•						
						1		
					ľ			j
			•					
							-	
		•						1
			•					
• .			•				magnisms of	
· .		• سند					ws with	
· .							wid in e	
			•				ers man e	
							and seems of m	
Report of all string:			production, el	c CASING	REC	ORD (New		4X
Report of all strings	s set — surface,	intermediate,			T	ORD (New) or 英俊英英	
Purpose of string	s set — surface, Size hole drilled	intermediate, Size casing set (in O.D.)	Weight lbs/ft.	Setting depth		Type cement) or ≹∯∛∛ Sacks	Type and percei
Purpose of string	s set — surface,	intermediate,) or ≹∯∛∛ Sacks	
Purpose of string	s set — surface, Size hole drilled	intermediate, Size casing set (in O.D.)	Weight lbs/ft.	Setting depth		Type cement) or ≹∯∛∛ Sacks	Type and percei additives
Purpose of string	s set — surface, Size hole drilled	intermediate, Size casing set (in O.D.)	Weight lbs/ft.	Setting depth		Type cement) or ≹∯∛∛ Sacks	Type and percei additives
Purpose of string	s set — surface, Size hole drilled	intermediate, Size casing set (in O.D.)	Weight lbs/ft.	Setting depth		Type cement) or ≹∯∛∛ Sacks	Type and percei additives
Purpose of string	s set — surface, Size hole drilled	intermediate, Size casing set (in O.D.)	Weight lbs/ft.	Setting depth		Type cement) or ≹∯∛∛ Sacks	Type and percei additives
Purpose of string	s set — surface, Size hole drilled	intermediate, Size casing set (in O.D.)	Weight lbs/ft.	Setting depth		Type cement) or ≹∯∛∛ Sacks	Type and percei additives
Purpose of string	s set — surface, Sixe hole drilled 12 1/4"	intermediate, Size casing set (in O.D.) 8 5/8"	Weight lbs/ft.	Setting depth		Type cement 40 Pozmix) or 美族委 Sacks 250	Type and perceind additives 3% CaCl
Purpose of string Urface	s set — surface, Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in 0.D.) 8 5/8"	Weight lbs/ff.	Setting depth	60:	Type cement 40 Pozmix PERFOR	or ************************************	Type and perceind additives 3% CaCl
Purpose of string Urface	s set — surface, Sixe hole drilled 12 1/4"	intermediate, Size casing set (in O.D.) 8 5/8"	Weight lbs/ff.	Setting depth		Type cement 40 Pozmix PERFOR) or 美族委 Sacks 250	Type and perceind additives 3% CaCl
Purpose of string Urface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in 0.D.) 8 5/8"	Weight lbs/ff.	Setting depth	60:	Type cement 40 Pozmix PERFOR	or ************************************	Type and perceind additives 3% CaCl
Purpose of string Unface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in 0.D.) 8 5/8"	Weight lbs/ff.	Setting depth	60:	Type cement 40 Pozmix PERFOR	or ************************************	Type and perceind additives 3% CaCl
Purpose of string Urface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in 0.D.) 8 5/8"	Weight lbs/ff.	Setting depth	60:	Type cement 40 Pozmix PERFOR	or ************************************	Type and perceind additives 3% CaCl
Purpose of string Urface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8" RD Sacks ca	Weight lbs/ff. 24# ement	Setting depth 300 '	60:	Type cement 40 POZMIX PERFOR	or ************************************	Type and perceind additives 3% CaCl
Purpose of string Urface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8" RD Sacks ca	Weight lbs/ff. 24# ement	Setting depth 300 '	60:	Type cement 40 POZMIX PERFOR	or ************************************	Type and perceind additives 3% CaCl
Purpose of string Urface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8" RD Sacks ca	Weight lbs/ff. 24# pment wet at URE, SHOT,	Setting depth 300 '	60:	Type cement 40 POZMIX PERFOR	or 教教教 Sacks 250 ATION RECOR	Type and perceind additives 3% CaCl
Purpose of string Unface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8 RD Sacks ca	Weight lbs/ff. 24# pment wet at URE, SHOT,	Setting depth 300 '	60:	Type cement 40 POZMIX PERFOR	or 教教教 Sacks 250 ATION RECOR	Type and perceindditives 3% CaCl
Purpose of string Unface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8 RD Sacks ca	Weight lbs/ff. 24# pment wet at URE, SHOT,	Setting depth 300 '	60:	Type cement 40 POZMIX PERFOR	or 教教教 Sacks 250 ATION RECOR	Type and perceindditives 3% CaCl
Purpose of string Unface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8 RD Sacks ca	Weight lbs/ff. 24# pment wet at URE, SHOT,	Setting depth 300 '	60:	Type cement 40 POZMIX PERFOR	or 教教教 Sacks 250 ATION RECOR	Type and perceindditives 3% CaCl
Purpose of string Unface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8 RD Sacks ca	Weight lbs/ff. 24# pment wet at URE, SHOT,	Setting depth 300 '	per ft	PERFOR SI	or 教教教 Sacks 250 ATION RECOR	Type and perceindditives 3% CaCl
Purpose of string Urface , ft. B	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8 RD Sacks ca	Weight lbs/ff. 24# pment wet at URE, SHOT,	Setting depth 300 '	per ft	Type cement 40 POZMIX PERFOR	or 教教教 Sacks 250 ATION RECOR	Type and perceindditives 3% CaCl
Purpose of string Unface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8" RD Sacks ca	Weight lbs/ff. 24# pment wet at URE, SHOT,	Setting depth 300 ' Shors	per ft	PERFOR SI	Sacks 250 ATION RECOR	Type and perceived additives 3% CaCl Depth interval
Purpose of string Unface	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8" RD Sacks ca	Weight lbs/ff. 24# Ement URE, SHOT, material used	Setting depth 300 ' Shors	per ft	PERFOR SI	or 教教教 Sacks 250 ATION RECOR	Type and perceived additives 3% CaCl Depth interval
Purpose of string Furface Fig. 8 Solution of first production	Size hole drilled 12 1/4" LINER RECOR	intermediate, Size casing set (in O.D.) 8 5/8" RD Sacks ca	Weight lbs/ff. 24# Ement URE, SHOT, material used	Setting depth 300 ' Shors	per ft	PERFOR SI	Sacks 250 ATION RECOR	Type and perceived additives 3% CaCl Depth interval