

6 070526

NOV 20 1986

API NUMBER 15-109-20,427-00-00

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

SW-NW-NE, SEC. 25, T 11 S, R 32 W

4290 feet from S section line

2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5422

Lease Name ENGLE Well # 1

Operator: FIBERCROMBIE DRILLING, INC.

County LOGAN 152.59

Name & Address 801 UNION CENTER

Well Total Depth 4695 feet

WICHITA, KANS. 67202

Conductor Pipe: Size 0 feet

JACK PARTRIDGE

Surface Casing: Size 8 5/8" feet 235

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated TAG #180

Plugging Contractor FIBERCROMBIE DRILLING, INC. License Number 5422

Address 801 UNION CENTER, WICHITA, KANS. 67202

Company to plug at: Hour: 2:45 PM Day: 20th Month: Nov Year: 1986

Plugging proposal received from WALLEY TOWN'S.

(company name) FIBERCROMBIE DRILLING (phone) 316-268-3201

were: 8 5/8" - 335' SR CUC 1/250 3/40 Formix 2% GEL ALSO 1" to 70' 1/50' 3/40' 2% GEL

Cemented By B.J. Titan RECOMMENDATION - 200 3/40' Formix GEL, C&L

1 3/4" CELLO 5/8" PLUG SPOT WITH DRILL STEM RECONDITION HOLE, HEAVY MUD BETWEEN ALL PLUGS.

ELV. 3003, ANHY 2520', NO CIRCULATION PROBLEMS, MUD CONDITION 47 Vis, 9.4 Wt/Lt,

9.6 LOSS, (DISPLACE 1st TWO PLUGS / MUD) 25' @ 2530', 100' @ 1600' 1/3 3/40' 2% GEL

40' @ 360' 10' BRIDGE @ 40' Plugging Proposal Received by M. Schmidt (TECHNICIAN)

15' Rat Hole (Circ.) 10' Mouse Hole (Circ.) Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 2:45 PM Day: 20th Month: Nov Year: 1986

ACTUAL PLUGGING REPORT ORDERED 200 3/40' Formix 2% GEL - 1 3/4" Cello + 5/8" Plug

SPOTTED WITH DRILL STEM - RECONDITIONED HOLE, HEAVY MUD BETWEEN ALL PLUGS.

DISPLACED FIRST TWO PLUGS WITH MUD 1st PLUG @ 2530' 1/25' 3/40' 2% GEL

2nd PLUG @ 1600' 1/100' 3/40' 2% GEL 1/3 CELLO 3rd PLUG @ 360' 1/40' 3/40' 2% GEL

4th PLUG SOLID BRIDGE HULLS - PLUG @ 40' 1/10' 3/40' 2% GEL 15' Rat Hole

(CIRCULATE) 10' MOUSE HOLE (CIRCULATE) 15-05-1986

Remarks: CEMENTED BY B.J. TITAN (If additional description is necessary, use BACK of this form.)

INVOICED could observe this plugging.

DATE 12-8-86

Signed M. Schmidt (TECHNICIAN)

CHK. NO. 15502

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 11-11-86 month day year

API Number 15-109-20,427-00-00

OPERATOR: License # 5422
Name Abercrombie Drilling, Inc.
Address 801 Union Center
City/State/Zip Wichita, KS 67202
Contact Person Jack Partridge
Phone (316) 263-3201

SW NW NE Sec. 25 Twp. 11 S, Rg. 32 X West
4290 Ft. from South Line of Section
2310 Ft. from East Line of Section
(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5422
Name Abercrombie Drilling, Inc.
City/State Wichita, Kansas

Nearest lease or unit boundary line 330 feet
County Logan
Lease Name Engle Well # 1
Ground surface elevation 2599 est 2995 top feet MSL
Domestic well within 330 feet yes X no
Municipal well within one mile yes X no
Surface pipe by Alternate 1 2 X
Depth to bottom of fresh water 250' 200
Depth to bottom of usable water 1600'
Surface pipe planned to be set 300
Projected Total Depth 4650 feet
Formation Mississippian

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
Gas Inj Pool Ext Air Rotary
OWWO Expl Wildcat Cable

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.
cementing will be done immediately upon setting production casing.
Date 11-04-86 Signature of Operator or Agent Title Vice President

For KCC Use:
Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per Alt. 4 @
This Authorization Expires 5-5-87 Approved By 11-5-86

Spud 11/13/86 300 + S.P. Hauling water
Wally Town PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Table with 3 columns: Plug location, feet depth with, and quantity (sxs) of material. Includes entries for 1st, 2nd, 3rd, 4th, and 5th plugs, and (2) Rathole with.

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging.
Important: Call district office after well is either plugged or production casing is cemented in.
(Call 7 a.m. to 5 p.m. workdays)

District office use only:
API #15-109-20,427 Legal
Surface casing of feet set with sxs at hours
Alternate 1 or 2 surface pipe was used.
Alternate 2 cementing was completed @ ft. depth with sxs on
Hole plugged 19, agent

RECEIVED KCC
NOV 6 1986
SLATE CORPORATION DISTRICT OFFICE 1086 Form C-1 6/85
DLS 8 503
12-08-1986
CONSERVATION DIVISION
Wichita, Kansas