4- 090564

TO:	API number: 15-109-20, 647 - 00 - 00
STATE CORPORATION COMMISSION	60'W.of
CONSERVATION DIVISION - PLUGGING	N2 NW SW /4 SEC. 28 , 11 S, 32 W
130 SOUTH MARKET, SUITE 2078	feet from S section line
WICHITA, KANSAS 67202	4680 feet from E section line
	rece from a section fine
Operator license#_3447	Lease: <u>Dreiling</u> Well #1-28_
Operator: Ranken Energy Corporation	County: <u>Logan</u> 154.64
Address: 601 N. Kelly - Suite #103	Well total depth 4758 feet
Edmond, OK 73003-4855	Conductor Pipe: 0 inch @ 0 feet
Edmond, OR /3003-4855	Surface pipe 8% Inch @ 259 feet
	Surface pipe 678 filen w
Aband. oil well, Gas well, Input we	ell, SWD, D & A_X
Plugging contractor: Abercrombie RTD, Inc.	License#30684
Address: Wichita, Kansas 67202	
Company to plug at: Hour:_P.M. Day:8	Month: August Year: 1997
Plugging proposal received from: Syl Rome	
Company: Abercrombie RTD, Inc.	Phone:
Moro: Order 100 and 60/40 magning 69 and	A
Were: Order 190 sxs 60/40 posmix - 6% gel. Spot all plugs through drill pipe with heavy	
spoc arr progs chronding drive price meavy	mud between all plugs.
Plugging Proposal Received by: Ed Schumach	
Plugging operations attended by agent? All[], Part[], None[X]
Completed: Hour: 8:00 A.M., Day: 13,	Month: August , Year: 1997
National columnians or control	
Actual plugging report:	
1st. Plug at 2615' w/25 sxs cement.	
2nd. Plug at 1675' w/100 sxs cement. 3rd. Plug at 310' w/40 sxs cement.	
4th. Plug at 40' w/10 sxs cement.	
15 sxs in rathole.	
24_W33W,_000_2.M.Y43V_1	
Arbuckle - no - Anhydrite 2601'.	
Remarks: Allied Cementing.	
Condition of casing(in hole): GOODB	AD Anhy.plug: YES_X NO
Bottom plug(in place): YES, CALC	, NO Dakota plug: YESX_, NO
Plugged through TUBING, CASING	Elevation:3077GL
I did[] / did not[x] observe the plugging	ng. Ed Achumacher
	(agent)
INVOICED	Form CP-2/3
	iyp) ·
8-19-91	/V
DATE	
CMM M3 488/1	