

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

ORIGINAL
Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33190
Name: Noble Energy, Inc.
Address: 1625 Broadway, Suite 2200
City/State/Zip: Denver, CO 80202
Purchaser: Kinder Morgan
Operator Contact Person: Jennifer Barnett
Phone: (303) 228-4235
Contractor: Name: Excell Services Inc., Wray, CO
License: 8273
Wellsite Geologist: none
Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SIOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., Cathodic, etc)
If Workover/Re-entry: Old Well Info as follows:
Operator: n/a
Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back Plug Back Total Depth
 Commingled Docket No. _____
 Dual Completion Docket No. _____
 Other (SWD or Enhr.?) Docket No. _____

<u>2/09/2008</u>	<u>2/11/2008</u>	<u>3/13/2008</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No: 15 - 023-20970-0000
County: Cheyenne
S2 NW SW NW Sec. 31 Twp. 3 S. R. 41 East West
1750' feet from S (circle one) Line of Section
330' feet from E (circle one) Line of Section
Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE NW SW
Lease Name: Zimbelman Well #: 12-31
Field Name: Cherry Creek
Producing Formation: Niobrara
Elevation: Ground: 3654' Kelly Bushing: 3663'
Total Depth: 1749' Plug Back Total Depth: 1694'
Amount of Surface Pipe Set and Cemented at 302' cmt w/ 104 sx Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from n/a
feet depth to _____ sx cmt.

Drilling Fluid Management Plan
(Data must be collected from the Reserve Pit)
Chloride content _____ ppm Fluid volume _____ bbls
Dewatering method used _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

Atk - Dig - w/ 9/8/08

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.


All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Jennifer Barnett
Title: Permit Representative Date: 4/10/08
Subscribed and sworn to before me this 10th day of April
2008
Notary Public: Erin K Lindley Joseph
Date Commission Expires: My Commission Expires Aug. 20, 2008

KCC Office Use ONLY

Letter of Confidentiality Received Denied, Yes Date: _____
Wireline Log Received
Geologist Report Received
Distribution

RECEIVED
KANSAS CORPORATION COMMISSION
APR 14 2008
CONSERVATION DIVISION
WICHITA, KS



Operator Name: Noble Energy, Inc. Lease Name: Zimbelman Well #: 12-31
 Sec. 31 Twp. 3 S. R. 41 East West County: Cheyenne

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Triple Combo (Array Induction/ Comp. Neutron/ Litho Density), CBL/GR/CCL	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample Name Niobrara Top Datum 1506'
--	--

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs./Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 7/8"	7"	17 Lbs./Ft.	302'	50/50 POZ	104 sx	3% CaCl, .25% Flo-cel
Production	6 1/4"	4 1/2"	11.6 Lbs./Ft.	1729'	Lead, Type III	42 sx	12%gel, 2%CaCl, .25 Flo-cel
					Tail, 50/50 POZ	56 sx	3%CaCl, .25% flo-cel

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
3 spf	Perf Niobrara interval from 1506'-1544'	Niobrara frac'd with 500 gals 7.5% HCL acid, 12,000 gals of	
	(38', 3spf, 114 holes) .41" EHD, 120 degree phase.	25% CO2 foamed gel pad; 31,989 gals 25% CO2 foamed	
		gel carrying 100,020 lbs 16/30 sand. AIP-606 psi; AIR-13.4 bpm.	

TUBING RECORD	Size	Set At	Packer At	Liner Run
				<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

Date of First, Resumerd Production, SWD or Enhr. 3/24/2008	Producing Method <input checked="" type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)
--	---

Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity
	0	75	0	0	

Disposition of Gas Vented Sold Used on Lease *(If vented, Submit ACO-18.)*

METHOD OF COMPLETION Open Hole Perf. Dually Comp. Commingled

Production Interval Other (Specify) _____

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-298-8143
 E-mail: blsonoil1@qwest.net

INVOICE # 6914
 LOCATION Zimbelman 12-31
 FOREMAN Jose Tom Pitt

TREATMENT REPORT

DATE <u>3/4/08</u>	WELL NAME <u>Zimbelman 12-31</u>	SECTION	TWP	RGE	COUNTY <u>Cheyenne</u>	FORMATION
-----------------------	-------------------------------------	---------	-----	-----	---------------------------	-----------

CHARGE TO <u>Excell Services</u>	OWNER
MAILING ADDRESS	OPERATOR
CITY	CONTRACTOR <u>Mepherston Drilling</u>
STATE ZIP CODE	DISTANCE TO LOCATION <u>70 Miles</u>
TIME ARRIVED ON LOCATION <u>3:30</u>	TIME LEFT LOCATION

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE <u>9 7/8</u>	TUBING SIZE	PERFORATIONS		THEORETICAL	INSTRUCTED
TOTAL DEPTH <u>396</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>7"</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>393</u>		TREATMENT VIA	TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT <u>17#</u>	PACKER DEPTH		<input checked="" type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM	
CASING CONDITION <u>Good</u>			<input type="checkbox"/> PRODUCTION CASING	INITIAL BPM	
			<input type="checkbox"/> SQUEEZE CEMENT	FINAL BPM	
			<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM	
			<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM	
			<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM	
			<input type="checkbox"/> MISC PUMP		
			<input type="checkbox"/> OTHER	HYD HHP = RATE X PRESSURE X 40.8	

PRESSURE SUMMARY			
BREAKDOWN or CIRCULATING psi	AVERAGE psi		
FINAL DISPLACEMENT psi	ISIP psi		
ANNULUS psi	5 MIN SIP psi		
MAXIMUM psi	15 MIN SIP psi		
MINIMUM psi			

INSTRUCTIONS PRIOR TO JOB MIRU, Safety meeting, Est. Circu, M/P 104 SKS Cement
yield 1.13 Density 15.2, Displace 11 BBLS H2O shut in well
wash to Pit

JOB SUMMARY
 DESCRIPTION OF JOB EVENTS (3:30) MIRU, (3:45) Safety meeting, (3:53) Est. Circu,
(4:10) M/P 104 SKS cement, (4:24) Displace 11 BBLS H2O,
(4:30) shut in well wash to pit
5 BBLS to Pit

RECEIVED
 KANSAS CORPORATION COMMISSION

APR 14 2008

CONSERVATION DIVISION
 WICHITA, KS.

Billy S. McSh...

3/9/08

AUTHORIZATION TO PROCEED

TITLE

DATE

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-298-8143
 E-mail: bisonoil1@qwest.net

INVOICE # 6918
 LOCATION Zumbelman 13-31
 FOREMAN Jose whiky Clarence

TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RGE	COUNTY	FORMATION
2/11/08	Zumbelman 13-31				Cheyenne	

CHARGE TO <u>Excell Services</u>	OWNER
MAILING ADDRESS	OPERATOR
CITY	CONTRACTOR <u>Excell Rig #17</u>
STATE ZIP CODE	DISTANCE TO LOCATION <u>70 miles</u>
TIME ARRIVED ON LOCATION <u>6:00 Request 6:30</u>	TIME LEFT LOCATION <u>9:00</u>

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE	TUBING SIZE	PERFORATIONS		THEORETICAL	INSTRUCTED
<u>6 7/8</u>					
TOTAL DEPTH <u>1749</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
<u>P/B 1694</u>	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>7 1/2</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>1719-50 - 1728 1/2</u>	TREATMENT VIA		TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT <u>14.6</u>	PACKER DEPTH		<input type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM	
CASING CONDITION <u>Good</u>			<input checked="" type="checkbox"/> PRODUCTION CASING	INITIAL BPM	
			<input type="checkbox"/> SQUEEZE CEMENT	FINAL BPM	
			<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM	
			<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM	
			<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM	
			<input type="checkbox"/> MISC PUMP		
			<input type="checkbox"/> OTHER	HYD HHP = RATE X PRESSURE X 40.8	

PRESSURE SUMMARY			
BREAKDOWN or CIRCULATING	psi	AVERAGE	psi
FINAL DISPLACEMENT	psi	ISIP	psi
ANNULUS	psi	5 MIN SIP	psi
MAXIMUM	psi	15 MIN SIP	psi
MINIMUM	psi		

INSTRUCTIONS PRIOR TO JOB MIRU, Safety meeting, Est. circ, Pump 3c BBLS Mud Flush
M/P 42 SKS lead cement, yield 2.64 Density 12 M/P 56 SKS Tail cement
yield 1.83 Density 13.8 Drop Plug, Displace 26.2 BBLS KCl water,
Set Plug between 1000 & 1500 PSI wash to pit Rig Down

JOB SUMMARY
 DESCRIPTION OF JOB EVENTS (6:30) MIRU, (7:20) Safety meeting, (8:10) Est. circ, Pump 30 BBLS
Mud Flush, (8:20) M/P 42 SKS lead cement, (8:25) M/P 56 SKS Tail cement
(8:30) Drop plug, (8:33) Displace 26.2 BBLS # KCl water,
(8:36) 10 BBLS Away 200 PSI
(8:40) 20 BBLS Away 500 PSI
(8:45) Set Plug at 1500 PSI

6 BBLS to PIP

RECEIVED
 KANSAS CORPORATION COMMISSION

APR 14 2008

CONSERVATION DIVISION
 WICHITA, KS

[Signature]

2/11/08

AUTHORIZATION TO PROCEED

TITLE

DATE

Customers hereby acknowledges and specifically agrees to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.