

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

ORIGINAL

Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33190
Name: Noble Energy, Inc.
Address: 1625 Broadway, Suite 2200
City/State/Zip: Denver, CO 80202
Purchaser: Kinder Morgan
Operator Contact Person: Jennifer Barnett
Phone: (303) 228-4235
Contractor: Name: Excell Services Inc., Wray, CO
License: 8273
Wellsite Geologist: none

Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SIOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:
Operator: n/a

Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back _____ Plug Back Total Depth _____
 Commingled _____ Docket No. _____
 Dual Completion _____ Docket No. _____
 Other (SWD or Enhr.?) _____ Docket No. _____

<u>2/10/2008</u>	<u>2/12/2008</u>	<u>3/11/2008</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 023-20966-0000
County: Cheyenne
NE NE NE NE Sec. 2 Twp. 4 S. R. 42 East West
330' feet from S N (circle one) Line of Section
330' feet from E W (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE NW SW
Lease Name: Stimbert Well #: 41-2
Field Name: Cherry Creek

Producing Formation: Niobrara
Elevation: Ground: 3633' Kelly Bushing: 3642'
Total Depth: 2078' Plug Back Total Depth: 2015'
Amount of Surface Pipe Set and Cemented at 313', cmt w/ 207 sx Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from n/a
feet depth to _____ w/ _____ sx cmt.
ATF 1 - Dlg - 9/8/08

Drilling Fluid Management Plan
(Data must be collected from the Reserve Pit)
Chloride content _____ ppm Fluid volume _____ bbls
Dewatering method used _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Jennifer Barnett
Title: Permit Representative Date: 5/20/08
Subscribed and sworn to before me this 20 day of May
08
Notary Public: Chris Lindley, Joseph
Date Commission Expires: My Commission Expires Aug. 20, 2008

KCC Office Use ONLY

LINDLEY

Letter of Confidentiality Received
 If Denied Yes Date: _____
 Wireline Log Received
 Geologist Report Received
 UIC Distribution

RECEIVED
KANSAS CORPORATION COMMISSION
MAY 21 2008

CONSERVATION DIVISION
WICHITA, KS

Operator Name: Noble Energy, Inc. Lease Name: Stimbert Well #: 41-2
 Sec. 2 Twp. 4 S. R. 42 East West County: Cheyenne

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Triple Combo (Array Induction/ Comp. Neutron/ Litho Density), CBL/GR/CCL	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample Name <u>Niobrara</u> Top <u>1468'</u> Datum _____
--	---

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 7/8"	7"	20 Lbs./Ft.	313'	50/50 POZ	207 sx	3% CaCl, .25% Flo-cele
Production	6 1/4"	4 1/2"	11.6 Lbs./Ft.	2057'	Lead, Type III	57 sx	12% gel, 2% CaCl, .25 Flo-cele
					Tail, 50/50 POZ	56 sx	3% CaCl, .25% flo-cele

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
3 spf	Perf Niobrara interval from 1468'-1505'	Niobrara frac'd with 500 gals 7.5% HCL acid, 12,000 gals of	
	(37', 3spf, 111 holes) .41" EHD, 120 degree phase.	25% CO2 foamed gel pad; 31,965 gals 25% CO2 foamed	
		gel carrying 100,020 lbs 16/30 sand. AIP-607 psi; AIR-13.4 bpm.	

TUBING RECORD	Size	Set At	Packer At	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
---------------	------	--------	-----------	---

Date of First, Resumard Production, SWD or Enhr. 3/26/2008	Producing Method <input checked="" type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Exp:ain)
Estimated Production Per 24 Hours	Oil Bbls. 0 Gas Mcf 107 Water Bbls. 0 Gas-Oil Ratio 0 Gravity

Disposition of Gas Vented Sold Used on Lease *(If vented, Submit ACO-18.)*

METHOD OF COMPLETION

Production Interval Open Hole Perf. Dually Comp. Commingled Other (Specify) _____

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-298-8143
 E-mail: bisonoil1@qwest.net

INVOICE # 6830
 LOCATION St. Francis KS
 FOREMAN ERIC R. STIMPSON
 ERIC
 GLEH

TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RGE	COUNTY	FORMATION
2-10-08	Stimpert 2207 GARDT 41-2				CHEYENNE	

CHARGE TO <u>McPherson</u>	OWNER
MAILING ADDRESS	OPERATOR <u>Bill</u>
CITY	CONTRACTOR <u>McPherson Drilling</u>
STATE ZIP CODE	DISTANCE TO LOCATION
TIME ARRIVED ON LOCATION <u>4:14</u>	TIME LEFT LOCATION

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE <u>9 1/8</u>	TUBING SIZE	PERFORATIONS		THEORETICAL	INSTRUCTED
TOTAL DEPTH <u>307</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>7</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>304</u>		TREATMENT VIA	TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT <u>20</u>	PACKER DEPTH		<input checked="" type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM	
CASING CONDITION <u>good</u>			<input type="checkbox"/> PRODUCTION CASING	INITIAL BPM	
PRESSURE SUMMARY			<input type="checkbox"/> SQUEEZE CEMENT	FINAL BPM	
BREAKDOWN or CIRCULATING psi	AVERAGE psi		<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM	
FINAL DISPLACEMENT psi	ISIP psi		<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM	
ANNULUS psi	5 MIN SIP psi		<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM	
MAXIMUM psi	15 MIN SIP psi		<input type="checkbox"/> MISC PUMP		
MINIMUM psi			<input type="checkbox"/> OTHER	HYD HHP = RATE X PRESSURE X 40.8	

INSTRUCTIONS PRIOR TO JOB MIRu SAFTY MEETING SET-CIRC
m-p 207 SKS 50/50/202 3% BCCA-1 .25% BFLA-1
Displace 110 RBIS H2O shut in well washup TO PIT. R.G. down

JOB SUMMARY
 DESCRIPTION OF JOB EVENTS MIRu (4:14) SAFTY (4:23)
m-p cement (4:32) Displace (4:40)
RBIS TO PIT (6)
shut in well (4:45)

RECEIVED
 KANSAS CORPORATION COMMISSION

MAY 21 2008

CONSERVATION DIVISION
 WICHITA, KS

Bill McPherson
 AUTHORIZATION TO PROCEED

TITLE

DATE

Customers hereby acknowledges and specifically agrees to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-298-8143
 E-mail: bisonoil1@qwest.net

INVOICE # 6919
 LOCATION Staubert 41-2
 FOREMAN Case Whitey, Alice FRAN

TREATMENT REPORT

DATE <u>2/13/08</u>	WELL NAME <u>Staubert 41-2</u>	SECTION	TWP	RGE	COUNTY	FORMATION
CHARGE TO <u>Excell Services</u>		OWNER				
MAILING ADDRESS		OPERATOR				
CITY		CONTRACTOR <u>Excell Rig #17</u>				
STATE/ZIP CODE		DISTANCE TO LOCATION <u>70 miles</u>				
TIME ARRIVED ON LOCATION <u>11:30 Request 11:30-12:30</u>		TIME LEFT LOCATION				

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE <u>6 1/4</u>	TUBING SIZE	PERFORATIONS	THEORETICAL		INSTRUCTED
TOTAL DEPTH <u>2083</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
<u>P/B 2015</u>	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>4 1/2</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>2057</u>		TREATMENT VIA	TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT <u>1116</u>	PACKER DEPTH		<input type="checkbox"/> SURFACE PIPE		BREAKDOWN BPM
CASING CONDITION <u>Good</u>			<input checked="" type="checkbox"/> PRODUCTION CASING		INITIAL BPM
			<input type="checkbox"/> SOOZE CEMENT		FINAL BPM
			<input type="checkbox"/> ACID BREAKDOWN		MINIMUM BPM
			<input type="checkbox"/> ACID STIMULATION		MAXIMUM BPM
			<input type="checkbox"/> ACID SPOTTING		AVERAGE BPM
			<input type="checkbox"/> MISC PUMP		
			<input type="checkbox"/> OTHER		HYD HHP = RATE X PRESSURE X 40.8

INSTRUCTIONS PRIOR TO JOB H/R, Safety Meeting, Est. Circu, Pump 30 BBLS KCl Mud Flush
M/P 57 SKS lead cement yield 2.64 Density 12, M/P 56 SKS Tail cement
yield 1.83 Density 13.8, Drop Plug, Displace 31.2 BBLS KCl water
Set Plug Between 1200 & 1500 PSI, wash to pit, Rig Down

JOB SUMMARY
 DESCRIPTION OF JOB EVENTS (12:00) H/R, (2:45) Safety, (2:55) Est. Circu, Pump 30 BBLS M/F
(3:08) M/P 56 SKS lead, (3:10) M/P 56 SKS Tail, (3:18) Drop plug,
(3:20) Displace, 31.2
(3:20) 10 Away 200 PSI
(3:30) 20 Away 300 PSI
(3:40) 30 Away 800 PSI
~~3:45~~ 3:45 Set the Plug at 1450
5 BBLS to pit

RECEIVED
 KANSAS CORPORATION COMMISSION

MAY 21 2008

CONSERVATION DIVISION
 WICHITA, KS

[Signature] AUTHORIZATION TO PROCEED TITLE DATE 2/13/08

Customers hereby acknowledges and specifically agrees to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.