

ORIGINAL

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33190
Name: Noble Energy, Inc.
Address: 1625 Broadway, Suite 2200
City/State/Zip: Denver, CO 80202
Purchaser: Kinder Morgan
Operator Contact Person: Jennifer Barnett
Phone: (303) 228-4235
Contractor: Name: Excell Services Inc., Wray, CO
License: 8273

Wellsite Geologist: none
Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SIOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:
Operator: n/a

Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back _____ Plug Back Total Depth _____
 Commingled _____ Docket No. _____
 Dual Completion _____ Docket No. _____
 Other (SWD or Enhr.?) _____ Docket No. _____

<u>7/17/2008</u>	<u>7/20/2008</u>	<u>8/19/2008</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 023-21055-0000
County: Cheyenne
W2 SW SE SE Sec. 6 Twp. 4 S. R. 41 East West
330' feet from S N (circle one) Line of Section
1,115' feet from E W (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE NW SW
Lease Name: Zimbelman Well #: 44-6
Field Name: Cherry Creek


Producing Formation: Niobrara
Elevation: Ground: 3580' Kelly Bushing: 3589'
Total Depth: 1644' Plug Back Total Depth: 1565'
Amount of Surface Pipe Set and Cemented at 254' cmt w/ 88 sx Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from n/a
feet depth to _____ w/ _____ sx cmt.

Drilling Fluid Management Plan Alt I NCR
(Data must be collected from the Reserve Pit) 11-6-08
Chloride content _____ ppm Fluid volume _____ bbls
Dewatering method used _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Jennifer Barnett
Title: Permit Representative Date: _____
Subscribed and sworn to before me this 24th day of September
2008
Notary Public: Denise Milet
Date Commission Expires: 11/09/08



KCC Office Use ONLY
 Letter of Confidentiality Received
If Denied, Yes Date: _____
 Wireline Log Received
 Geologist Report Received
 UIC Distribution
RECEIVED
KANSAS CORPORATION COMMISSION
SEP 25 2008

My Commission Expires 11/09/2008

Operator Name: Noble Energy, Inc. Lease Name: Zimbelman Well #: 44-6
 Sec. 6 Twp. 4 S. R. 41 East West County: Cheyenne

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Triple Combo (DEN/NEU/IND), CBL/CCL/GR	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample Name <u>Niobrara</u> Top <u>1406'</u> Datum _____
---	---

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 7/8"	7"	17 Lbs./Ft.	254'	50/50 POZ	88 sx	3% CaCl, .25% Flo-celc
Production	6 1/4"	4 1/2"	11.6 Lbs./Ft.	1607'	Lead Type III	36 sx	12% Gel, 2% CaCl, .25% Polyflake
					Tail Type III	56 sx	2% Gel, 1% CFL-80

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
3 spf	Perf Niobrara interval from 1406'-1442'	Niobrara frac'd with 500 gals 7.5% HCL acid, 12,840 gals of	
	(36', 3spf, 108 holes) .41" EHD, 120 degree phase	25% CO2 foamed gel pad; 30,812 gals 25% CO2 foamed gel carrying 100,600 lbs 16/30 sand. ATP-568 psi; ATR-15.8 bpm.	

TUBING RECORD	Size	Set At	Packer At	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
---------------	------	--------	-----------	---

Date of First, Resumerd Production, SWD or Enhr. 8/29/2008	Producing Method <input checked="" type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)
--	--

Estimated Production Per 24 Hours	Oil Bbls. 0	Gas Mcf 65	Water Bbls. 0	Gas-Oil Ratio 0	Gravity
-----------------------------------	--------------------	-------------------	----------------------	------------------------	---------

Disposition of Gas Vented Sold Used on Lease *(If vented, Submit ACO-18.)*

METHOD OF COMPLETION Open Hole Perf. Dually Comp. Commingled Other (Specify) _____

Production Interval _____

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-298-8143
 E-mail: bisonoil1@qwest.net

VOICE # 7812
 LOCATION C.R. 6 St. Francis KS
 FOREMAN Eric, Cisco, Justin

TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RGE	COUNTY	FORMATION
7-20-08	Zimbelman 44-6				Cherokee	
CHARGE TO <u>Excell Services</u>			OWNER			
MAILING ADDRESS			OPERATOR <u>Greg</u>			
CITY			CONTRACTOR <u>Excell Rig 17</u>			
STATE ZIP CODE			DISTANCE TO LOCATION <u>70 miles</u>			
TIME ARRIVED ON LOCATION <u>6:30</u>			TIME LEFT LOCATION			

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE	TUBING SIZE	PERFORATIONS	THEORETICAL		INSTRUCTED
6 1/4					
TOTAL DEPTH <u>1645</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
<u>PBA @ 1565</u>	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>4.5</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>1598</u>		TREATMENT VIA	TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT	PACKER DEPTH		<input type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM	
CASING CONDITION <u>good</u>			<input checked="" type="checkbox"/> PRODUCTION CASING	INITIAL BPM	
PRESSURE SUMMARY			<input type="checkbox"/> SOOZE CEMENT	FINAL BPM	
BREAKDOWN or CIRCULATING psi	AVERAGE psi		<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM	
FINAL DISPLACEMENT psi	ISIP psi		<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM	
ANNULUS psi	5 MIN SIP psi		<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM	
MAXIMUM psi	15 MIN SIP psi		<input type="checkbox"/> MISC PUMP		
MINIMUM psi			<input type="checkbox"/> OTHER	HYD HHP = RATE X PRESSURE X 40.8	

INSTRUCTIONS PRIOR TO JOB mtrp, safety meeting, 30 BBL mud flush, m+p 36 sks tcmty yield
2.64 Density 12, m+p 56 sks tcmty yield 1.83 Density 13.8, Drop Plug Displace
24.3 BBL H₂O, set Plug @ 1400-1500 psi

JOB SUMMARY
 DESCRIPTION OF JOB EVENTS mtrp-7:15 safety meeting-7:30 30 BBL mud flush-7:35 m+p
36 sks tcmty-7:40 m+p 56 sks tcmty-7:53 Drop Plug-8:07 Displace 24.3
BBL H₂O-8:09 set Plug @ 1400-1500 psi-8:22

Time	Flow	PSI
8:15	10	100
8:19	20	400
8:22	24.3	1500

6 bbls to pit

RECEIVED
 KANSAS CORPORATION COMMISSION
 SEP 25 2008
 CONSERVATION DIVISION
 WICHITA, KS

[Signature]
 AUTHORIZED TO PROCEED TITLE DATE
7-20-08

Customers hereby acknowledges and specifically agrees to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-298-8143
 E-mail: bisonoil1@qwest.net

INVOICE # 7790

LOCATION CLL

FOREMAN FRANK ZACHAR

TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RGE	COUNTY	FORMATION
7-17-08	Z-100000000000-0				Cheyenne	

CHARGE TO <u>EXCEL SERVICES</u>	OWNER <u>NOBLE</u>
MAILING ADDRESS	OPERATOR
CITY	CONTRACTOR <u>McPherson</u>
STATE ZIP CODE	DISTANCE TO LOCATION <u>70 MILES</u>
TIME ARRIVED ON LOCATION <u>4:15</u>	TIME LEFT LOCATION <u>5:15</u>

WELL DATA

PRESSURE LIMITATIONS

HOLE SIZE <u>9.875</u>	TUBING SIZE	PERFORATIONS	THEORETICAL	INSTRUCTED
TOTAL DEPTH <u>250</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG	
	TUBING WEIGHT	OPEN HOLE	STRING	
CASING SIZE <u>7"</u>	TUBING CONDITION		TUBING	
CASING DEPTH <u>245</u>		TREATMENT VIA	TYPE OF TREATMENT	
CASING WEIGHT <u>17</u>	PACKER DEPTH		<input checked="" type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM
CASING CONDITION <u>Good</u>			<input type="checkbox"/> PRODUCTION CASING	INITIAL BPM
			<input type="checkbox"/> SQUEEZE CEMENT	FINAL BPM
			<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM
			<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM
			<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM
			<input type="checkbox"/> MISC PUMP	
			<input type="checkbox"/> OTHER	HYD HHP = RATE X PRESSURE X 40.8

PRESSURE SUMMARY

BREAKDOWN OF CIRCULATING	psi	AVERAGE	psi
FINAL DISPLACEMENT	psi	ISIP	psi
ANNULUS	psi	5 MIN SIP	psi
MAXIMUM	psi	15 MIN SIP	psi
MINIMUM	psi		

INSTRUCTIONS PRIOR TO JOB WILL SHUT meeting EST. CLL M.P. 88 S. K5 LEAD 2000
15.2 DEN. 5.14 1.13 YIELD 10 DDGS MIX WATER DISPLACE 9 BDCS
SHOT 14 well VBSL W/PT RT DOWN

JOB SUMMARY

DESCRIPTION OF JOB EVENTS WELL 4158 SHUT meeting 4:52
CLL 4158 DD 504 SHOT 14 well 5:08
BDCS RT 5

RECEIVED
 KANSAS CORPORATION COMMISSION

SEP 25 2008

CONSERVATION DIVISION
 WICHITA, KS

[Signature]
 AUTHORIZATION TO PROCEED

[Signature]
 driller

7-17-08
 DATE