KANSAS CORPORATION COMMISSION OR / G/NAL

	Form ACO-1
	September 1999
1	Form Must Be Typed

WELL COMPL	ETION FORM
WELL HISTORY - DESCRIP	PTION OF WELL & LEASE
1	005 00450 00 00

Operator: License #	API No. 15 - 205-26458-00-00
Name: Cherokee Wells, LLC	County: Wilson
Address: 4916 Camp Bowie Blvd., Suite 204	CSW_NE4Sec. 8 Twp. 28 S. R. 15
City/State/Zip: Fort Worth, TX 76107	1980 feet from S N (circle one) Line of Section
Purchaser: Southeastern Kansas Pipeline	1980 feet from E W (circle one) Line of Section
Operator Contact Person: Rhonda Wilson	Footages Calculated from Nearest Outside Section Corner:
Phone: (620) 378-3650	(circle one) (NE) SE NW SW
Contractor: Name: Well Refined Drilling	Lease Name: F Seiwart Well #: A-6
License: 33072	Field Name: Cherokee Basin Coal
Wellsite Geologist: n/a	Producing Formation: Mississippian
Designate Type of Completion:	Elevation: Ground: unknown Kelly Bushing: n/a
New Well Re-Entry Workover	Total Depth: 1306 Plug Back Total Depth: 1294
Oil SWD SIOWTemp. Abd.	Amount of Surface Pipe Set and Cemented at 40 Feet
Gas ENHR SIGW	Multiple Stage Cementing Collar Used?
Dry Other (Core, WSW, Expl., Cathodic, etc)	If yes, show depth setFeet
If Workover/Re-entry: Old Well Info as follows:	If Alternate II completion, cement circulated from bettom casing 1296
Operator:	feet depth to surface w/ 28 /40 sx cmt.
Well Name:	Alt C-012 - 9/30/08
Original Comp. Date: Original Total Depth:	Drilling Fluid Management Plan (Data must be collected from the Reserve Pit)
Deepening Re-perf Conv. to Enhr./SWD	Chloride content ppm Fluid volume bbls
Plug Back Plug Back Total Depth	Dewatering method used
Commingled Docket No.	
Dual Completion Docket No	Location of fluid disposal if hauled offsite:
Other (SWD or Enhr.?) Docket No	Operator Name:
7/18/06 7/20/06 3/22/07	Lease Name: License No.:
Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R East West
Recompletion Date Recompletion Date	County: Docket No.:
Information of side two of this form will be held confidential for a period of	th the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, ver or conversion of a well. Rule 82-3-130 52-5106 52-3-107 apply. 12 months if requested in writing and submitted with this form. ALL CEMENTING and geologist well report shall be attached with this form. ALL CEMENTING s. Submit CP-111 form with all temporarily abandoged by s.
All requirements of the statutes, rules and regulations promulgated to regulate herein are complete and correct to the best of my knowledge.	late the oil and gas industry have been GUISESYADION DWISION the statements WICHITA, KS
Signature: Mhonde Illion	KCC Office Use ONLY
Title: Office Mar ager Date: 4/27/07	Letter of Confidentiality Received
77 1-11	Letter of Confidentiality Received
Subscribed and sworn to before me this 2 1 day of 77001	Wireline Log Received
20 07	Genlogist Report Received
Notary Public: YACY MULLI TRACY M	ILLER UIC Distribution
Date Commission Expires: Notary Public - State Not	e of Kansas

Operator Name: Cherokee Wells, LLC				Lease Name: F Seiwert			Well #: A-6		
Sec. 8 Twp. 28			West	County	: Wilson	า			
INSTRUCTIONS: She tested, time tool open temperature, fluid reco Electric Wireline Logs	and closed, flowing overy, and flow rate	g and shut s if gas to	-in pressures, surface test, a	whether sh long with fi	nut-in pre	ssure reached s	static level, hydros	static pressure	es, bottom hole
Drill Stem Tests Taken (Attach Additional S		☐ Y€	es ✓ No		L	og Formatio	on (Top), Depth ar	nd Datum	Sample
Samples Sent to Geol	,	□ Ye	es 🗹 No		Nam	е		Тор	Datum
Cores Taken Electric Log Run (Submit Copy)		_ Y€	_						
List All E. Logs Run:									
Electric Log Er	nclosed								
		Repo		RECORD	✓ Ne urface, inte	ew Used ermediate, product	ion, etc.		
Purpose of String	Size Hole Drilled	Siz	e Casing (In O.D.)	Weig	ght	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	11 1/4"	8 5/8"		26#		40'	Portland	60	
Long String	6 3/4"	4 1/2"		13.2#		1296	Thick Set Cement	140	
			ADDITIONAL	CEMENTI	NG / SQL	JEEZE RECORD			
Purpose: Perforate Protect Casing Plug Back TD Plug Off Zone	Depth Top Bottom	Туре	of Cement	#Sacks				ercent Additives	
	PERFORATI	ON BECOR	ID - Bridge Plug	s Set/Tyne		Acid Frac	cture, Shot, Cement	Squeeze Recor	rd
Shots Per Foot			Each Interval Per		 		nount and Kind of Mat		Depth
							KANSA	RECE IS CORPORAT	IVED TON COMMISSION
								MAY 0 2	2007
TUBING RECORD	Size	Set At		Packer A	t	Liner Run	Yes No	ONSERVATION WICHITA	
Date of First, Resumerd	Production, SWD or E	inhr.	Producing Met	hod	Flowing	g Pumpir	ng Gas Lift	Othe	er (Explain)
Estimated Production Per 24 Hours	Oil	Bbls.	Gas	Mcf	Wate	er Bl	bls. Ga	as-Oil Ratio	Gravity
Disposition of Gas	METHOD OF C	OMPLETIC	N .			Production Inter	val		
Vented Sold	Used on Lease		Open Hole Other (Spec	Perf.		Dually Comp.	Commingled		

CONSOLIDATED OIL WELL SERVICES, INC. P.O. BOX 884, CHANUTE, KS 66720 620-431-9210 OR 800-467-8676

TICKET NUM	BER	<u>10337</u>	
LOCATION_	Ence	ka	
FOREMAN_	Troy.	Strickler	

TREATMENT REPORT & FIELD TICKET CEMENT

Cote as The	COUNTY	COL	RANGE	TOWNSHIP	SECTION	BER	NAME & NUM	WEL	CUSTOMER#	DATE
TRUCK # DRIVER TRUCK # DRIVER MAILING ADDRESS P.O. BOX 960 CITY STATE ZIP CODE Macker OK 74855 JOB TYPE Longstring HOLE SIZE 64' HOLE DEPTH 1305' CASING SIZE & WEIGHT 45" 10.5" CASING DEPTH 1296' DRILL PIPE TUBING OTHER SLURRY WEIGHT 13.2" SLURRY VOL 42 161 WATER gallak 8" CEMENT LEFT in CASING O' DISPLACEMENT 20.5 84 DISPLACEMENT PSI 400 MIX PSI 1100 Bure Phy RATE REMARKS: Safety Meeting: Rig up to 42" CASING. Break Circulation will 258 Aump 45k Cal - Flick 108k Oye wife. Mixed 1405k Thick Set Comm Left 15 kol-Seal 105k @ 13.2 164, wash out floor Page 15 and 1405k Thick Set Comm Left 15 kol-Seal 105k @ 13.2 164, wash out floor Page 15 and 1405k Thick Set Comm Left 15 kol-Seal 105k @ 13.2 164, wash out floor Page 15 and 1405k Thick Set Comm Left 15 kol-Seal 105k @ 13.2 164, wash out floor Page 15 and 1405k Thick Set Comm Left 15 kol-Seal 105k @ 13.2 164, wash out floor Page 15 and 164.	ilson	wils				-6	ieward A	Frank ;	3070	
P.O. Box 960 CITY STATE ZIP CODE 439 Jin 462/Tis Jin HOLE SIZE Lift HOLE DEPTH 1305' CASING SIZE & WEIGHT 45" CASING SIZE & WEIGHT TUBING OTHER SLURRY WEIGHT 13.2" SLURRY VOL 42 151 WATER gallak WATER gallak REMARKS: Safety Meeting: REMARKS: Safety Meeting: Rig up to 42" Casing. Sieck Circulation w/ 258 Auno 45k Casing. Sieck Circulation w/ 258 Casing Size & Weight 446 439 Jin 462/Tis Jin OTHER OTHER OTHER REMARKS: Safety Meeting: Rig up to 45" Casing. Sieck Circulation w/ 258 Auno 45k Casing. Sieck Circulation w/ 258 Casing Size & Weight Vin Casing. Casing. Sieck Circulation w/ 258 Casing Size & Weight 450.55 Casing Size & Weight 45 / 10.55 Casing Size & Weight 45 / 10.			Art Contract	医神经性 化二二二甲基甲基				,		
P.O. Box 960 CITY STATE STATE ZIP CODE 439 JINTHA 431 JOHN Meeter OK 74855 HOLE SIZE 64' HOLE DEPTH 1305' CASING SIZE & WEIGHT 45" 10-5 CASING DEPTH 1296' DRILL PIPE SLURRY WEIGHT SLURRY VOL 42 861 WATER gallak 8' CEMENT LEFT in CASING O' DISPLACEMENT PSI PREMARKS: Safety Meeting: Rig up to 42" CASING. BIECK CIPCULATION WI 258 RAMP 454 CASING.	RIVER	DRI	TRUCK#	DRIVER	TRUCK #	Į		Tabel .	enay 111	MARING ADDRE
Meeter OK 74855 JOB TYPE Longstring HOLE SIZE 64" HOLE DEPTH 1305" CASING SIZE & WEIGHT 45" 10.5" CASING DEPTH 1296" DRILL PIPE TUBING OTHER SLURRY WEIGHT 13.2" SLURRY VOL 42 1661 WATER gallak 8" CEMENT LEFT in CASING O' DISPLACEMENT 20.5 84 DISPLACEMENT PSI 600 MIX PSI 1100 Burn Ply RATE REMARKS: Safety Meeting: Rig up to 4%" Casing. Break Circulation wil 258 Plamp 45k Col - Flich 108h Ove Left. Mixed 1405ts Thick Set Comment of St Kol-Seal Mixt 8 13.2" Affel. Wash Outh Plans times Palous				Catin	446					
Mecker OK 74855 JOB TYPE Langstring HOLE SIZE 64" HOLE DEPTH 1305" CASING SIZE & WEIGHT 45" 10.5 CASING DEPTH 1296" DRILL PIPE TUBING OTHER SLURRY WEIGHT 13.2" SLURRY VOL 42 861 WATER gallak 8" CEMENT LEFT in CASING O' DISPLACEMENT 20.5 84 DISPLACEMENT PSI 600 MIX PSI 1/00 Rump Ply RATE REMARKS: Safely Meeting: Rig up to 45" Casing. Break Circulation w/ 258 Ramp 45k Col - Flich, 1084 Dye Left. Mixed 1405ks Thick Set Comm L/ 5t Kol-Seal Mist 8 13.2" Affel, wash out from times Paloue		1		Justin	439		·			P.O.
CASING DEPTH 1296' DRILL PIPE TUBING OTHER SLURRY WEIGHT 13.2" SLURRY VOL 42 861 WATER GAILER & CEMENT LEFT IN CASING O' DISPLACEMENT 20.5 84 DISPLACEMENT PSI 600 MIX PSI 1/00 Rump Ply RATE REMARKS: Safety Meeting: Rig up to 42" Casing. Break Circulation w/ 258 Ramp 45k Col - Flich, 1084 Dye Left. Mixed 1405ks Thick Set Comm L/ 5t Kol-Seal 19/5t & 13.2" Refel. Wash out August I lives Palous	"	1		John	436		ZIP CODE	STATE		_
CASING DEPTH 1296' DRILL PIPE TUBING OTHER SLURRY WEIGHT 13.2" SLURRY VOL 42 861 WATER gallak 8" CEMENT LEFT IN CASING O' DISPLACEMENT 20.5 84 DISPLACEMENT PSI 600 MIX PSI 1100 Burn Ply RATE REMARKS: Safety Meeting: Rig up to 45" Casing. Break Circulation wil 258 Aump 45k Col - Flich, 1084 Ove wester. Mixed 140sts Thick Set Comm L/ 5# Kol-Seal Mist @ 13.2" Augst. Wash out Aum + lines Palouse.	*			ست	462/143]	74855	OK		Meeter
CASING DEPTH 1296' DRILL PIPE TUBING OTHER SLURRY WEIGHT 13.2" SLURRY VOL 42 861 WATER gallak 8" CEMENT LEFT IN CASING O' DISPLACEMENT 20.5 84 DISPLACEMENT PSI 600 MIX PSI 1100 Burp Ply RATE REMARKS: Safety Meeting: Rig up to 4%" Casing. Break Circulation w/ 258 Rump 45k Col - Flich, 106k Dre Left, Mixed 140sks Thick Set Comm L/ 5# Kol-Seal 19/5k 8 13.24 hefel, wash out func times Paloue	· #	10.54	HT 45"	CASING SIZE & WE	1305'	HOLE DEPTH	634.	HOLE SIZE	<u> </u>	
SLURRY WEIGHT 13.2 SLURRY VOL 42 166 WATER gallak 8° CEMENT LEFT in CASING O' DISPLACEMENT 20.5 By DISPLACEMENT PSI 600 MIX PSI 1100 Burne Ply RATE REMARKS: Safety Meeting: Rig up to 45" Casing. Break Circulation wil 25B Ramp 45k Cocl - Flich, 10 By Dye Lefty. Mixed 1405ks Thick Set Comm L/ 5t Kol-Seal Mist @ 13.2 Refel. Wash out August lives Palouse						TUBING		DRILL PIPE	1296'	CASING DEPTH_
DISPLACEMENT 20.5 By DISPLACEMENT PSI 600 MIX PSI 1100 Burp By RATE REMARKS: Safety Meeting: Rig up to 4½" Casing. Break Circulation w/ 25A Rump 4sk Coel-Flich, 1000 Dre Late. Mixed 140sts Thick Set Comme L/ 5# Kol-Seal Prist @ 13.2# Agel. Wash out Augus times Palace A	····			CEMENT LEFT in C	<u>. 8</u> *	WATER gal/si	12 1341	SLURRY VOL_		
REMARKS: Safety Meeting: Rig up to 45" Casing. Break Circulation w/ 250 Runp 45k Coel-Flich, 1000 Dre water. Mixed 140sts Thick Set Comment 5t Kol-Seal Profit @ 13.2" Augst. Wash out Augs times lalouse				RATE	O Burne Ole	MIX PSI 1/D	PSI 400	DISPLACEMENT	20.5 84	DISPLACEMENT_
the st Kol-Seal Portst @ 13.24 Aught, wash out from times lalowed	M 1 4 . a . d	2		reck Crowlet	Casine. Re	45"	up to	time: Ric	afety Mes	REMARKS:
bel 5# Kol-Smal Portet @ 13.2# Aughel, wash out from + lines Palaces	61474	<u> </u>	- W	Wash The	Moved	Later	OU Dre	Flich . 16	sk Cal -	Aumo 4.
			0-1-	And I be	- Cust	. Labor	3.2# Aug			
	Tig.	<u> </u>	A Kelec	1 CO OCT	4					
1100 RSI. Wait 2007S. Release Pressure. Float Held. Good Coment	, ,	Heg to	Chara !	E. BOUTOL	P FIEND	One con	Qalages	2005	T List	
Surface - 786) Story to Pit.	70	ent t	_Cee	THE Ed. Good	E- F1061	FIESSU	A-I	the see se	7841	Sections
					2 1	T-1 C		WITY TO	- /90/ 3	CAST TALE
Job Complete.					41 . 1	184 / -				

ACCOUNT CODE	QUANTITY or UNITS	PUMP CHARGE KANSAS CORPORATION COMMI	SHOUNT PRICE	TOTAL
5401		PUMP CHARGE PUMP CHARGE	8000	800.00
5406	40	MILEAGE A 2008	3.15	126.00
		MILEAGE MAR 19 2008		12000
1126A	140545	Thick Set Coment CONSERVATION DIVISE Kal-Sel Se Mal	14.65	2051.00
IJIOA	700 #	Kal-Soul 5 # Argal WICHIA S	.35*	252.00
1118A	200*	Gel-Flush	. 14 *	28.00
5407		Ton- Milege Bulk Truck	mk	275.00
SSOIC	4403	Transport	98.00	392.00
5502C	4hrs	SORI KC. TACK	90.00	340.00
1123	500gul	C:ty hater	12.80	64.00
4404		450 Top Rubber Ply	40.00	40.00
4129		45° Contralizer	36.00	36.00
4156	1	45" Flapper Type Float Shoe	201.00	208.00
		Thenk Kou!	Sub Total	4632.00
		632	SALES TAX	168.77

AUTHORIZATION CALLED by Ris. TITLE DATE DATE