

STATE OF KANSAS  
STATE CORPORATION COMMISSION

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division  
State Corporation Commission  
800 Bitting Building  
Wichita, Kansas

WELL PLUGGING RECORD  
OR  
FORMATION PLUGGING RECORD

Strike out upper line  
when reporting plugging  
of formations.

NORTH


Locate well correctly on above  
Section Plat

Rooks County, Sec. 36 Twp. 10 Rge. (E) 17 (W)  
 Location as "NE 1/4 NW 1/4 SW 1/4" or footage from lines 990' W & 330' N of Cen. of Sec.  
 Lease Owner **Cities Service Oil Company**  
 Lease Name **August** Well No. **1**  
 Office Address **Bartlesville, Okla.**  
 Character of Well (completed as Oil, Gas or Dry Hole) **Dry Hole**  
 Date well completed **6-22-42** 19  
 Application for plugging filed **6-22-42** 19  
 Application for plugging approved **6-22-42** 19  
 Plugging commenced **6-23-42** 19  
 Plugging completed **6-23-42** 19  
 Reason for abandonment of well or producing formation **Dry**  
 If a producing well is abandoned, date of last production 19  
 Was permission obtained from the Conservation Division or its agents before plugging was commenced? **Yes**

Name of Conservation Agent who supervised plugging of this well **C.T. Alexander**  
 Producing formation **Arbuckle Lime** Depth to top **3668'** Bottom Total Depth of Well **3701'** Feet  
 Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
<b>Arbuckle Lime</b>	<b>Dry</b>			<b>8-5/8"</b>	<b>290'</b> <b>Cemented</b>	<b>None</b>

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet to \_\_\_\_\_ feet for each plug set.

**Filled with mud from T.D. 3701' to 290', set wood plug, dumped 30' of cement to 260', mud to 26', 20' of cement to 6', mud and dirt to surface.**

36' 10" 17W  
38 45

(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to **R. C. Hauber**  
Address **Cities Service Oil Company, Great Bend, Kansas**

STATE OF **Kansas**, COUNTY OF **Russell**, ss.

*J. A. Clancy* (employee of owner) ~~employee of owner~~ of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) *J. A. Clancy*  
**Cities Service Oil Co., Russell, Kansas**  
(Address) **7-13-42**

SUBSCRIBED AND SWORN TO before me this **17** day of **June** 19**42**

My commission expires **My Commission Expires Sept. 26, 1942** *[Signature]* Notary Public.

WELL RECORD

Company Cities Service Oil Co. Well No. 1 Farm August  
 Location 330' North and 990' West of Center Sec. 36 T. 10 R. 17W  
 Elevation 2078 County ooks State Kansas  
 Drig. Comm. June 2, 1942 Contractor Helm Drilling Company  
 Drig. Comp. June 22, 1942 Acid None  
 T. D. 3701' Initial Prod. Dry - Plugged and Abandoned

CASINO RECORD:

8-5/8" 290' cas. 100 ex Ideal & 2 ex C. C.

FORMATION RECORD:

Rock, white, hard 0-25  
 shale & shells 130  
 shale, grey 278  
 shale & shells 290  
 shale, dark, soft 365  
 iron hard 368  
 shale & shells 688  
 lime, light, hard 763  
 lime & iron, hard 772  
 sandy shale & shells 832  
 sand & shells 940  
 sandy shale & shells 1085  
 shale & iron shells 1230  
 shale & shells 1285  
 anhydrite, hard 1325  
 shale, red & shells 1420  
 shale & shells 1623  
 salt, shale & shells 1810  
 shale & shells 1855  
 lime & shale breaks 2042  
 lime, grey, hard 2130  
 lime & shale breaks 2152  
 lime, grey, hard 2200  
 lime & shale 2210  
 lime & shale breaks 2285  
 lime, hard 2305  
 lime, light, med. 2410  
 lime, light, hard 2457  
 lime broken 2534  
 lime, grey, hard 2558  
 shale & shells 2570  
 lime, grey, hard 2640  
 shale & shells 2655  
 lime & shale breaks 2673  
 lime, light, hard 2740  
 shale & shells, blue, soft 2795  
 shale, dark & shells 2815  
 lime & shale breaks 2850  
 lime, light, hard 2940

shale & shells 3068  
 shale & lime shells 3080  
 lime, light, hard 3377  
 lime, light, med. 3420  
 lime, light, hard 3529  
 lime 3572  
 lime, light, hard 3589  
 chert 3593  
 conglomerate 3605  
 conglomerate & chert 3618  
 conglomerate 3626  
 conglomerate & chert 3668  
 lime light, hard 3701 T. D.

Top Arbuckle 3668'  
 Penetration 33'  
 Total Depth 3701'

Byfo: 500' 0°  
 1000' 0°  
 1500' 0°  
 2000' 0°  
 2500' 0°  
 3000' 0°

36 10 17W  
 38 45