

ORIGINAL

KANSAS CORPORATION COMMISSION  
OIL & GAS CONSERVATION DIVISION  
WELL COMPLETION FORM  
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Form ACO-1  
September 1999  
Form Must Be Typed

Operator: License # 33741  
Name: Energex Kansas, Inc.  
Address: Commerce Plaza 1 Center, 7300 W. 110th Street, 7th Floor  
City/State/Zip: Overland Park, KS 66210  
Purchaser: Shell Trading U. S. Company  
Operator Contact Person: Marcia Littell  
Phone: (913) 693-4608  
Contractor: Name: Birk Petroleum  
License: 31280

Wellsite Geologist: \_\_\_\_\_  
Designate Type of Completion:  
 New Well     Re-Entry     Workover  
 Oil     SWD     SIOW     Temp. Abd.  
 Gas     ENHR     SIGW  
 Dry     Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:  
Operator: \_\_\_\_\_

Well Name: \_\_\_\_\_  
Original Comp. Date: \_\_\_\_\_ Original Total Depth: \_\_\_\_\_  
 Deepening     Re-perf.     Conv. to Enhr./SWD  
 Plug Back     Plug Back Total Depth  
 Commingled    Docket No. \_\_\_\_\_  
 Dual Completion    Docket No. \_\_\_\_\_  
 Other (SWD or Enhr.?)    Docket No. \_\_\_\_\_

<u>June 25, 2008</u>	<u>June 26, 2008</u>	<u>August 14, 2008</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 091-23269-00-00  
County: Johnson  
SE SE NW SE Sec. 8 Twp. 14 S. R. 22  East  West  
1530 feet from (S) N (circle one) Line of Section  
1640 feet from (E) W (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:  
(circle one) NE (SE) NW SW  
Lease Name: Voigts Well #: 83  
Field Name: Gardner  
Producing Formation: Bartlesville  
Elevation: Ground: 994' Kelly Bushing: \_\_\_\_\_  
Total Depth: 889' Plug Back Total Depth: 874'  
Amount of Surface Pipe Set and Cemented at 20 Feet  
Multiple Stage Cementing Collar Used?  Yes  No  
If yes, show depth set \_\_\_\_\_ Feet  
If Alternate II completion, cement circulated from 874  
feet depth to surface w/ 120 sx cmt.

Drilling Fluid Management Plan AIT II NR  
(Data must be collected from the Reserve Pit) 10-15-08  
Chloride content \_\_\_\_\_ ppm Fluid volume \_\_\_\_\_ bbls  
Dewatering method used \_\_\_\_\_  
Location of fluid disposal if hauled offsite: \_\_\_\_\_  
Operator Name: \_\_\_\_\_  
Lease Name: \_\_\_\_\_ License No.: \_\_\_\_\_  
Quarter \_\_\_\_\_ Sec. \_\_\_\_\_ Twp. \_\_\_\_\_ S. R. \_\_\_\_\_  East  West  
County: \_\_\_\_\_ Docket No.: \_\_\_\_\_

**INSTRUCTIONS:** An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Marcia Littell

Title: Compliance Coordinator Date: September 8, 2008

Subscribed and sworn to before me this 8 day of September

2008

Notary Public: M. J. White

Date Commission Expires: 6/2/09

**KCC Office Use ONLY**  
N  
Letter of Confidentiality Received  
If Denied, Yes  Date: \_\_\_\_\_  
Wireline Log Received  
Geologist Report Received  
UIC Distribution  
**RECEIVED**  
KANSAS CORPORATION COMMISSION  
**SEP 10 2008**

MICHELLE R. WHITE  
Notary Public  
State of Kansas  
My Appointment Expires 6/2/09

CONSERVATION DIVISION  
WICHITA, KS

Operator Name: Energex Kansas, Inc. Lease Name: Voigts Well #: 83  
 Sec. 8 Twp. 14 S. R. 22  East  West County: Johnson

**INSTRUCTIONS:** Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i>  Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No  Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i>  List All E. Logs Run:  <b>Gamma Ray/Neutron</b>	<input type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample  Name Top Datum
--	---

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 7/8"	7"	23.0#	20'	Portland	8	
Production	5 7/8"	2 7/8"	5.8#	874'	O.W.C.	120	

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
___ Perforate				
___ Protect Casing				
___ Plug Back TD				
___ Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
4 SPF	839-848'	Spot 75 gal. 15% HCL	839-848'
		127 bbls. city H2o w KCL, 300# 20/40, 3700# 12/20	

**RECEIVED**  
 KANSAS CORPORATION COMMISSION  
**SEP 10 2008**  
 CONSERVATION DIVISION  
 WICHITA, KS

TUBING RECORD		Size	Set At	Packer At	Liner Run		
						<input type="checkbox"/> Yes	<input type="checkbox"/> No
Date of First, Resumerd Production, SWD or Enhr.			Producing Method				
			<input type="checkbox"/> Flowing <input checked="" type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)				
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity		

Disposition of Gas      **METHOD OF COMPLETION**      Production Interval

Vented    Sold    Used on Lease    Open Hole    Perf.    Dually Comp.    Commingled  
*(If vented, Submit ACO-18.)*       Other (Specify) \_\_\_\_\_

**B & B COOPERATIVE VENTURES**  
**900 South 4<sup>th</sup>**  
**Burlington, Ks 66839**  
**620-364-1311**

<b>DATE: 06/26/08</b>	<b>Lease: VOIGTS</b>
Operator: EnerJex Kansas, Inc	Well No.: 83
7300 W. 110 <sup>th</sup> St Floor 7	API: 15-091-23269-0000
Overland Park, Ks 66210	Description: 8-14-22 Jo. Co.; 1530' FSL, 1640' FEL
Spud: 06/25/208      T.D.: 06/26/08	County: Johnson

Formations	From	To	Formations	From	To
Top Soil/Clay	0	10	Lime	318	323
River Gravel	10	21	Black Shale	323	333
Lime	21	43	Lime	333	354
Black Shale	43	51	Black Shale	354	358
Lime	51	59	Lime	358	363
Shale	59	64	Shale	363	367
Lime	64	66	Lime	367	373
Shale	66	70	Shale	373	525
Lime	70	85	Lime	525	526
Shale	85	102	Shale	526	548
Lime	102	174	Lime	548	553
Shale	174	177	Shale	553	565
Lime	177	178	Lime	565	568
Shale	178	214	Shale	568	591
Lime	214	224	Lime	591	594
Shale	224	240	Shale	594	610
Lime	240	249	Lime	610	612
Shale	249	253	Red Shale	612	633
Shaley Lime	253	260	Shale	633	692
Lime	260	267	Lime	692	693
Shale	267	270	Shale	693	728
Lime	270	272	Lime	728	740
Shale	272	289	Shale	740	791
Lime	289	290	Lime	791	800
Shale	290	299	Shale	800	839
Lime	299	317	Oil Sand	839	846
Shale	317	318	Shale	846	889

**RECEIVED**  
**KANSAS CORPORATION COMMISSION**  
**SEP 10 2008**  
**CONSERVATION DIVISION**  
**WICHITA, KS**

Surface bit: 9 7/8"      Length: 20'      Size: 7"      Cement: 8 sx circ. To surface  
Drill bit: 6"      T.D.: 889'      Long String: 2 7/8" set at 874'

