KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

WELL PLUGGING APPLICATION

Please TYPE Form and File ONE Copy

Form CP-1 September 2003 This Form must be Typed Form must be Signed All blanks must be Filled

State: Kansas Lease: Peterman - NW - NW - NW Spot Location / QQQQ County: 330 Feet (in exact footage) From North / South (from nearest 330 Feet (in exact footage) From East / West (from nearest 4 Mest) Check One: Oil Well Gas Well D&A Cathodic West Swyd Docket # ENHR Docket # ENHR Docket # Surface Casing Size: None Set at: Surface Casing Size: 8 5/8" Set at: 309' Production Casing Size: 5 1/2" Set at: 3334' List (ALL) Perforations and Bridgeplug Sets: Elevation: 1862 (Gal./ N.B.) T.D.: 3340 PBTD: 3290' Anhy	Sec. 17 Twp. 17 S. R. 10 East we Ellsworth St outside section corner) Line of Section (Not Lease Line) St outside section corner) Line of Section (Not Lease Line) Water Supply Well Cemented with: Cemented with: Sact Cemented with: 175 Sact Sact Cemented with: 175 Sact Sact Sact Sact Sact Cemented with: 175 Sact
State: Kansas	Contact Phone: (620) 564 - 2240 Sec. 17 Twp. 17 S. R. 10 East we Ellsworth It outside section corner) Line of Section (Not Lease Line) St outside section corner) Line of Section (Not Lease Line) Water Supply Well Other: Cemented with: Sack Cemented with: 175 Sack ydrite Depth: 625' (+1237) (Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
Lease: Peterman - NW - NW - NW Spot Location / QQQQ County: 330 Feet (in exact tootage) From North / South (from nearest 330 Feet (in exact tootage) From East / West (from nearest 340 Feet (in exact tootage) From East / West (from nearest 240 Feet (in exact tootage) From East / West (from nearest 240 Feet (in exact tootage) From East / West (from nearest 240 Feet (in exact tootage) From East / West (from nearest 240 Feet (in exact tootage) From East / West (from nearest 240 Feet (in exact tootage) From East / West (from nearest 240 Feet (in exact tootage) From East / West (from nearest 240 Feet (in exact tootage) From East / West (from nearest 240 Feet (in exact tootage) From East / West (from nearest 24	Sec. 17 Twp. 17 S. R. 10 East we Ellsworth Stoutside section corner) Line of Section (Not Lease Line) Stoutside section corner) Line of Section (Not Lease Line) Water Supply Well Cemented with: Cemented with: Sact Cemented with: 175 Sact ydrite Depth: 625' (+1237) (Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
	Ellsworth st outside section corner) Line of Section (Not Lease Line) st outside section corner) Line of Section (Not Lease Line) Water Supply Well Cemented with: Cemented with: Cemented with: 175 Saction Cemented with: Saction Cemente
South (from nearest South South (from nearest 330	toutside section corner) Line of Section (Not Lease Line) at outside section corner) Line of Section (Not Lease Line) Water Supply Well Cemented with: Cemented with: Cemented with: 175 Sacl Other: Cemented with: 175 Sacl Sacl Sacl Sacl Sacl Sacl Sacl Other: Cemented with: 175 Sacl Sacl Sacl Other: Cemented with: 175 Sacl Sacl Other: Sacl Sacl Other: Sacl Sacl Sacl Other: Sacl Sacl Other: Sacl Sacl Other: Sacl Sacl Sacl Other: Sacl Other: Sacl Sacl Other: Other: Sacl Other: Other: Sacl Other: Sacl Other: Other: Other: Sacl Other:
330 Feet (in exact tootage) From East / ✓ West (from nearest Check One: ✓ Oil Well Gas Well D&A Cathodic Well SWD Docket # ENHR Docket # ENHR Docket # Surface Casing Size: None Set at: Surface Casing Size: 8 5/8" Set at: 309' Production Casing Size: 5 1/2" Set at: 3334' List (ALL) Perforations and Bridgeplug Sets: Elevation: 1862 (□G.L./ ▼K.B.) T.D.: 3340 PBTD: 3290' Anhy Condition of Well: ✓ Good □ Poor □ Casing Leak □ Junk Proposed Method of Plugging (attach a separate page if additional space is needed): We place	Nater Supply Well Cemented with: Cemented with: Cemented with: Sack Cemented with: 175 Sack Sack Sack Cemented with: Sack Cemented with: 175 Sack S
Check One:	Vater Supply Well Cemented with: Sack Cemented with: 250 Sack Cemented with: 175 Sack ydrite Depth: 625' (+1237) (Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
SWD Docket # ENHR Docket # ENHR Docket # Conductor Casing Size: None Set at: Set at: Set at: 309' Production Casing Size: 5 1/2" Set at: 3334' List (ALL) Perforations and Bridgeplug Sets: Set at: 3334' Elevation: 1862 (G.L./	Cemented with: Sack Cemented with: 250 Sack Cemented with: 175 Sack ydrite Depth: 625' (+1237) (Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
Conductor Casing Size: None Set at: Surface Casing Size: 8 5/8" Set at: 309' Production Casing Size: 5 1/2" Set at: 3334' List (ALL) Perforations and Bridgeplug Sets: Elevation: 1862 (G.L. / K.B.) T.D.: 3340 PBTD: 3290' Anhy Condition of Well: Good Poor Casing Leak Junk Proposed Method of Plugging (attach a separate page if additional space is needed): We place	Cemented with:Sack
Surface Casing Size: 8 5/8" Production Casing Size: 5 1/2" Set at: 3334' List (ALL) Perforations and Bridgeplug Sets: Elevation: 1862 (G.L./VK.B.) T.D.: 3340 PBTD: 3290' Anhy Condition of Well: Good Poor Casing Leak Junk Proposed Method of Plugging (attach a separate page if additional space is needed): We place	Cemented with: 250 Sack Cemented with: 175 Sack ydrite Depth: 625' (+1237) (Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
Production Casing Size: 5 1/2" List (ALL) Perforations and Bridgeplug Sets: Elevation: 1862 (G.L. / K.B.) T.D.: 3340 PBTD: 3290' Anhy Condition of Well: Good Poor Casing Leak Junk Proposed Method of Plugging (attach a separate page if additional space is needed): We place	ydrite Depth: 625' (+1237) (Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
List (ALL) Perforations and Bridgeplug Sets: Elevation: 1862 (G.L. / V.B.) T.D.: 3340 PBTD: 3290 Anhy Condition of Well: Good Poor Casing Leak Junk Proposed Method of Plugging (attach a separate page if additional space is needed): We place	ydrite Depth: 625' (+1237) (Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
Condition of Well: Good Poor Casing Leak Junk Proposed Method of Plugging (attach a separate page if additional space is needed): We pla	(Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
Condition of Well:	(Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
Condition of Well: Good Poor Casing Leak Junk Proposed Method of Plugging (attach a separate page if additional space is needed): We pla	(Stone Corral Formation) k in Hole an to remove retrievable 5 1/2" casing and plug
Proposed Method of Plugging (attach a separate page if additional space is needed): We pla	an to remove retrievable 5 1/2" casing and plug
	art to remove remevable 5 1/2 casing and plug
as directed by RCC.	
	Keren.
	NA AN
Is Well Log attached to this application as required? Yes No Is ACO-1 filed?	✓ Yes \(\text{No} \) No
If not explain why?	KCC MICLUS
Plugging of this Well will be done in accordance with K.S.A. 55-101 <u>et, seq</u> . and the R	
List Name of Company Representative authorized to be in charge of plugging operations:	Grady Bolding
	Phone: (620) 564 - 2240
Address: P.O. Box 486	City / State: Ellinwood, Kansas 67526
Plugging Contractor: Mike's Testing & Salvage, Inc.	KCC License #: 31529 (Contractors)
Address: P.O. Box 467, Chase, Kansas 67524	Phone: (620) 938-2634
Proposed Date and Hour of Plugging (if known?): To be arranged with KCC - Dist	trict Office - Wichita
Payment of the Plugging Fee (K.A.R. 82-3-118) will be guaranteed by Operator of Age	unt ,
- 11 - 12 - 12 G	(Signature) Room 2078, Wichita, Kansas 67202
Date: 1-13-09 Authorized Operator / Agent: Lady 1	(Signatura)



Mark Parkinson, Governor Thomas E. Wright, Chairman Michael C. Moffet, Commissioner Joseph F. Harkins, Commissioner

NOTICE OF RECEIPT OF WELL PLUGGING APPLICATION (CP-1)

GRADY BOLDING CORPORATION PO BOX 486 ELLINWOOD, KS 67526-0486

July 20, 2009

Re: PETERMAN #1

API 15-053-20846-00-00

17-17S-10W, 330 FNL 330 FWL ELLSWORTH COUNTY, KANSAS

Dear Operator:

This letter is to notify you that the Conservation Division has received your plugging proposal, form CP-1, for the above well and has reviewed the proposal for completeness. The central office will now forward your CP-1 to the district office listed below for review of the proposed plugging method. Please contact the district office for approval of your proposed plugging method at least five (5) days before plugging the well, pursuant to K.A.R. 82-3-113(b). If a workover pit will be used during the plugging of the well it must be permitted. A CDP-1 form must be filed and approved prior to the use of the pit in accordance with K.A.R. 82-3-600.

The Conservation Division's review of form CP-1, either in the central or district office, does not include an inquiry into well ownership or the filing operator's legal right to plug the well. This notice in no way constitutes authorization to plug the above well by persons not having legal rights of ownership or interest in the well.

This notice is void after January 16, 2010. The CP-1 filing does not bring the above well into compliance with K.A.R. 82-3-111 with regard to the Commission's temporary abandonment requirements.

Sincerely,

Steve Bond

Steve Bond

Production Department Supervisor

District: #2

3450 N. Rock Road, Suite 601

Wichita, KS 67226 (316) 630-4000