

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION
WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Form ACO-1
September 1999
Form Must Be Typed

Operator: License # 33190
Name: Noble Energy, Inc.
Address: 1625 Broadway, Suite 2200
City/State/Zip: Denver, CO 80202
Purchaser: Kinder Morgan
Operator Contact Person: Jennifer Barnett
Phone: (303) 228-4235
Contractor: Name: Excell Services Inc., Wray, CO
License: 8273

Wellsite Geologist: none
Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SIOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:
Operator: n/a

Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back Plug Back Total Depth
 Commingled Docket No. _____
 Dual Completion Docket No. _____
 Other (SWD or Enhr.?) Docket No. _____

7/18/2008 7/21/2008 8/19/2008
Spud Date or Date Reached TD Completion Date or Recompletion Date

API No. 15 - 023-21057-0000
County: Cheyenne
NW NE SE Sec. 6 Twp. 4 S. R. 41 East West
2,400' feet from S N (circle one) Line of Section
630' feet from E W (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE NW SW
Lease Name: Zimelman Well #: 43-6
Field Name: Cherry Creek


Producing Formation: Niobrara
Elevation: Ground: 3606' Kelly Bushing: 3615'
Total Depth: 1672' Plug Back Total Depth: 1617'
Amount of Surface Pipe Set and Cemented at 252' cmt w/ 87 sx Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from n/a
feet depth to _____ w/ _____ sx cmt.

Drilling Fluid Management Plan AH I NR
(Data must be collected from the Reserve Pit) 11-5-08
Chloride content _____ ppm Fluid volume _____ bbls
Dewatering method used _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Jennifer Barnett
Title: Permit Representative Date: 9/25/08
Subscribed and sworn to before me this 24th day of September
2008
Notary Public: Debbie M. Lett
Date Commission Expires: 11/09/08



KCC Office Use ONLY

N Letter of Confidentiality Received
If Denied, Yes Date: _____
 Wireline Log Received
 Geologist Report Received
 UIC Distribution

RECEIVED
KANSAS CORPORATION COMMISSION
SEP 25 2008

Operator Name: Noble Energy, Inc. Lease Name: Zimbelman Well #: 43-6
 Sec. 6 Twp. 4 S. R. 41 East West County: Cheyenne

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken Yes No
 (Attach Additional Sheets)

Samples Sent to Geological Survey Yes No

Cores Taken Yes No

Electric Log Run Yes No
 (Submit Copy)

List All E. Logs Run:

Triple Combo (DEN/NEU/IND), CBL/CCL/GR

Log Formation (Top), Depth and Datum Sample

Name Niobrara Top 1448' Datum

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	9 7/8"	7"	17 Lbs./Ft.	252'	50/50 POZ	87 SX	3% CaCl, .25% Flo-cel
Production	6 1/4"	4 1/2"	11.6 Lbs./Ft.	1659'	Lead Type III	38 SX	12% Gel, 2% CaCl, .25% Polyflake
					Tail Type III	56 SX	2% Gel, 1% CFL-80

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
3 spf	Perf Niobrara interval from 1448'-1486'	Niobrara frac'd with 500 gals 7.5% HCL acid, 12,000 gals of	
	(38', 3spf, 114 holes) .41" EHD, 120 degree phase	25% CO2 foamed gel pad; 33,174 gals 25% CO2 foamed	
		gel carrying 100,040 lbs 16/30 sand. ATP-523 psi; ATR-14.8 bpm.	

TUBING RECORD	Size	Set At	Packer At	Liner Run
				<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

Date of First, Resumerd Production, SWD or Enhr. 8/29/2008		Producing Method			
		<input checked="" type="checkbox"/> Flowing	<input type="checkbox"/> Pumping	<input type="checkbox"/> Gas Lift	<input type="checkbox"/> Other (Explain)
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity
	0	76	0	0	

Disposition of Gas Vented Sold Used on Lease (If vented, Submit ACO-18.)

METHOD OF COMPLETION Open Hole Perf. Dually Comp. Commingled Other (Specify) _____

Production Interval _____

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-298-8143
 E-mail: bisonoil@qwest.net

INVOICE # 7805
 LOCATION C.R. 6 St. Francis KS
 FOREMAN Eric, Cizo, Jorge

TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RGE	COUNTY	FORMATION
7-18-08	Zimkelman 43-6				Cherokee	

CHARGE TO <u>McPherson Drilling</u>	OWNER
MAILING ADDRESS	OPERATOR <u>Scott</u>
CITY	CONTRACTOR <u>McPherson</u>
STATE ZIP CODE	DISTANCE TO LOCATION <u>70</u>
TIME ARRIVED ON LOCATION <u>10:45</u>	TIME LEFT LOCATION

WELL DATA

PRESSURE LIMITATIONS

HOLE SIZE	TUBING SIZE	PERFORATIONS		THEORETICAL	INSTRUCTED
<u>9 3/8</u>					
TOTAL DEPTH <u>248</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>7"</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>244</u>		TREATMENT VIA	TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT <u>12</u>	PACKER DEPTH		<input type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM	
CASING CONDITION <u>good</u>			<input type="checkbox"/> PRODUCTION CASING	INITIAL BPM	
			<input type="checkbox"/> SOOZE CEMENT	FINAL BPM	
			<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM	
			<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM	
			<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM	
			<input type="checkbox"/> MISC PUMP		
			<input type="checkbox"/> OTHER	HYD HHP = RATE X PRESSURE X 10.8	

PRESSURE SUMMARY

BREAKDOWN or CIRCULATING	psi	AVERAGE	psi
FINAL DISPLACEMENT	psi	15IP	psi
ANNULUS	psi	5 MIN SIP	psi
MAXIMUM	psi	15 MIN SIP	psi
MINIMUM	psi		

INSTRUCTIONS PRIOR TO JOB: MTRP, safety meeting, Est. die, m+p 87 sks cement yield 1.13
Density 15.2, Displace 9 BBLs H₂O, shut in well wash up to pit.

JOB SUMMARY

DESCRIPTION OF JOB EVENTS: mtrp (11:00) safety meeting (11:15) Est. die (11:20) m+p 87 sks
cmat (11:21) Displace 9 BBLs H₂O (11:29) shut in well wash up to pit
(11:34)

7 BBLs to pit

RECEIVED
 KANSAS CORPORATION COMMISSION

SEP 25 2008

CONSERVATION DIVISION
 WICHITA, KS

Scott
 AUTHORIZATION TO PROCEED

Driller
 TITLE

7-18-08
 DATE

BISON OIL WELL CEMENTING, INC.



1738 Wynkoop St., Ste. 102
 Denver, Colorado 80202
 Phone: 303-296-3010
 Fax: 303-296-8143
 E-mail: bisonoil1@qwest.net

INVOICE # 7757

LOCATION KS

FOREMAN STANLEY R. Simpson
ALFH
Zerhan

TREATMENT REPORT

DATE	WELL NAME	SECTION	TWP	RGE	COUNTY	FORMATION
7-21-08	ZimBELman 43-6				Chickani	

CHARGE TO <u>EXCEL</u>	OWNER
MAILING ADDRESS	OPERATOR <u>GREG</u>
CITY	CONTRACTOR <u>EXCEL Rig 17</u>
STATE ZIP CODE	DISTANCE TO LOCATION
TIME ARRIVED ON LOCATION <u>5:05</u>	TIME LEFT LOCATION <u>6:30</u>

WELL DATA			PRESSURE LIMITATIONS		
HOLE SIZE <u>6 1/4</u>	TUBING SIZE	PERFORATIONS		THEORETICAL	INSTRUCTED
TOTAL DEPTH <u>1674</u>	TUBING DEPTH	SHOTS/FT	SURFACE PIPE ANNULUS LONG		
	TUBING WEIGHT	OPEN HOLE	STRING		
CASING SIZE <u>4 1/2</u>	TUBING CONDITION		TUBING		
CASING DEPTH <u>1650</u>		TREATMENT VIA	TYPE OF TREATMENT		TREATMENT RATE
CASING WEIGHT <u>11.6</u>	PACKER DEPTH		<input type="checkbox"/> SURFACE PIPE	BREAKDOWN BPM	
CASING CONDITION <u>good</u>	<u>POR 1617</u>		<input checked="" type="checkbox"/> PRODUCTION CASING	INITIAL BPM	
PRESSURE SUMMARY			<input type="checkbox"/> SQUEEZE CEMENT	FINAL BPM	
BREAKDOWN or CIRCULATING psi	AVERAGE psi		<input type="checkbox"/> ACID BREAKDOWN	MINIMUM BPM	
FINAL DISPLACEMENT psi	ISIP psi		<input type="checkbox"/> ACID STIMULATION	MAXIMUM BPM	
ANNULUS psi	5 MIN SIP psi		<input type="checkbox"/> ACID SPOTTING	AVERAGE BPM	
MAXIMUM psi	15 MIN SIP psi		<input type="checkbox"/> MISC PUMP		
MINIMUM psi			<input type="checkbox"/> OTHER	HYD HHP = RATE X PRESSURE X 40.8	

INSTRUCTIONS PRIOR TO JOB MRK SAPTY m.c.t.m.y EST 6:17C m-p 30 BBIS mud flush
m-p 38 SKS 50/50 P02 12% BBIS-1 2% BFLA-1 12.5% BFLA-1 - 14.7 BBIS mix H2O
m-p 56 SKS 50/50 P02 2% BBIS-1 1% BFLA-1 12.5% BFLA-1 - 12.9 BBIS mix H2O
Drop Plug Displace 2.5 BBIS H2O SIT Plug 1400 @ 1600 PSI
Check float & latch Washup & PIT Rig down

JOB SUMMARY
 DESCRIPTION OF JOB EVENTS MRK 5:05 SAPTY 5:28 m-p mud flush 5:30
Lead Cement 5:37 Tail Cement 5:40
Drop Plug 5:48 Displace 5:51
7 hrs Annul PSI
5:56 10 200
5:58 20 300
6:00 30 Plug 1500

RECEIVED
 KANSAS CORPORATION COMMISSION

SEP 25 2008

CONSERVATION DIVISION
 WICHITA, KS

AUTHORIZATION TO PROCEED

7-21-08

TITLE DATE

Customers hereby acknowledge and specifically agrees to the terms and conditions on this work order, including, without limitation, the provisions on the reverse side hereof which include the release and indemnity.