15-163-03373-0000

DISTRICT CONSERVATION AGENT'S REPORT

Dry Hole Abandoned Oil Well X Abandoned Gas Well I have this date completed supervision of plugging of: Well No. 4 Lease Dunlap Operator C & G Drg Co Address Wichita, Kans Field County Rooks Total Depth 3781 Feet. Plugging Contractor Globe Cementing Co Plugging Contractor's License No. Address (Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 5\frac{3}{2}" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel) , hole filled from 3776' to 0' with mud. Mudding by Globe Cementing co - 1350# pump pressure.	To: State Corporation Commission Conservation Division 211 North Broadway Wichita, Kansas LOCATION NW SW SW SEC. 7 TWP. 10 RGE. 19
Well No. 4 Lease Dunlap Operator C & G Drg Co Address Wichita, Kans Field County Rooks Total Depth 3781 Feet. Plugging Contractor Globe Cementing Co Plugging Contractor's License No. Address (Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 5%" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel) , hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1550# pump pressure.	
Operator C & G Drg Co Address Wichita, Kans Field County Rooks Total Depth 3781 Feet. Plugging Contractor Globe Cementing Co Plugging Contractor's License No. Address (Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 5½" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel), hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1550# pump pressure.	I have this date completed supervision of plugging of:
Total Depth 3781 Feet. Plugging Contractor Globe Cementing Co Plugging Contractor's License No. Address (Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 5\frac{1}{2}" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel) , hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1550# pump pressure.	Well No. 4 Lease Dunlap
Total Depth 3781 Feet. Plugging Contractor Globe Cementing Co Plugging Contractor's License No. Address (Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 5\frac{1}{2}" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel) , hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1350# pump pressure.	Operator C & G Drg Co Address Wichita, Kans
Plugging Contractor Globe Cementing Co Plugging Contractor's License No. Address (Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 52" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel) , hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1350# pump pressure.	Field County Rooks
Plugging Contractor's License No. Address (Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 52" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel) , hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1350# pump pressure.	Total Depth 3781 Feet.
(Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 5\frac{1}{2}" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel) , hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1350# pump pressure.	Plugging Contractor Globe Cementing Co
(Describe Briefly the manner in which the well was plugged) 8 5/8" at 250' circulated with cement - 5\frac{1}{2}" at 3776' cemented and squeezed with cement from 1090' to 0' with cement. No pipe Rec. Pumped hole full heavy mud (40 sax Gel), hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1350# pump pressure.	Plugging Contractor's License No.
Pumped hole full heavy mud (40 sax Gel), hole filled from 5776' to 0' with mud. Mudding by Globe Cementing co - 1350# pump pressure.	(Describe Briefly the manner in which the well was plugged)
Mudding by Globe Cementing co - 1350# pump pressure.	and squeezed with cement from 1090' to 0' with cement. No pipe Rec.
Mudding by Globe Cementing co - 1350# pump pressure.	Pumped hole full heavy mud (40 sax Gel) , hole filled from
Ledon Tette	5776' to 0' with mud.
District Conservation Agent	Mudding by Globe Cementing co - 1350# pump pressure.
Date 3-18-57	

PLUGGING
FILE SEC 7 T 10 R 19 W
POJK PAGE 2 LINE 45

STATE CORPORATION COMMINGS STATE CORPORATION COMMINGS OF COMMINGS OF STATE CORPORATION COMMINGS OF STATE CORPORATION COMMINGS OF COM CONSERVATION DIVISION
Wichita, Kansein