310

4- 041370 5-18

15-163-03373-00-01

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15- - 12-1-1950

NW SW SW /4 SEC. 07, 10 S, 19 W
990 feet from S section line
4950 feet from E section line

Operator license# 5310

Lease Dunlap well # 1

Operator: Four-Way Operations, Inc.

County Rooks

Address: P.O. Box 698
Great Bend, Kansas 67530

Well total depth 3802 feet 123.56
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 251 feet w/circ. cmt.

Aband. oil well X, Gas well ___, Input well ___, SWD ___, D & A ___

Plugging contractor: Allied Cementing License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: 8:00P.M. Day: 18 Month: May Year: 92

Plugging proposal received from: Jim Rockhold

Company: Four-Way Operations, Inc. Phone:

Were: 5 1/2" casing set @ 3780' w/NA cement. Open hole @ 3785'-3802'. Anhy. perf. @ 1650'. Dakota @ 950'. W.L.M. 3790'. Squeezed @ 1291' w/105 sx. plus cement.
Ordered 350 sxs. 60/40 pozmix - 10% gel. with 1/4# F.C. plus 500# hulls.

Plugging Proposal Received by: Dennis L. Hamel
Plugging operations attended by agent? All[ X ], Part[ ], None[ ]

Completed: Hour: 2:00P.M., Day: 18, Month: May, Year: 92

Actual plugging report: Run in hole with tubing to 1660'. Spot 215 sxs. cir. cement w/250# hulls. P.O.O.H. with tubing. Hooked-up to 5 1/2" csg. Squeezed 60 sks. cement w/150# hulls.
Max. P.S.I. 800#. Shut in P.S.I. 500#. Hood-up to 8 5/8" S.P.
Squeezed 75 sx. cement with 100# hulls mixed in cement.
Max. P.S.I. 600#. Shut in P.S.I. 300#.

Remarks:
Condition of casing(in hole): GOOD X BAD ___ Anhy.plug: YES X NO ___
Bottom plug(in place): YES X, CALC X, NO ___ Dakota plug: YES X NO ___
Plugged through TUBING X, CASING ___. Elevation: ___ GL

RECEIVED
STATE CORPORATION COMMISSION
6-1-92
JUN 1 1992
CONSERVATION DIVISION
Wichita, Kansas

I did[X] / did not[ ] observe the plugging. Dennis L. Hamel (agent)

INVOICED
DATE 6-30-92
INV. NO. 35589
5-18

Form CP-2/3