

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-065-01381-00-00  
Spot: SENWSE Sec/Twnshp/Rge: 14-9S-21W  
1650 feet from S Section Line, 1650 feet from E Section Line  
Lease Name: LANSING KANSAS CITY UNIT Well #: 6  
County: GRAHAM Total Vertical Depth: 3823 feet

Operator License No.: 5552  
Op Name: GORE OIL COMPANY  
Address: 202 S ST FRANCIS PO BOX 2757  
WICHITA, KS 67202

| String | Size  | Depth (ft) | Pulled (ft) | Comment                     |
|--------|-------|------------|-------------|-----------------------------|
| SURF   | 8.625 | 1776       | 0           | w/500 sxs cmt               |
| PROD   | 4.5   | 3821       | 0           | w/200 sxs cmt <u>124.25</u> |

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 08/25/2009 9:00 AM  
Plug Co. License No.: 99996 Plug Co. Name: ALLIED CEMENT COMPANY  
Proposal Rcvd. from: LENNY DINKEL Company: GORE OIL COMPANY Phone: (785) 259-1928

Proposed Plugging Method: Ordered 550 sxs 60/40 pozmix - 4% gel - 700# hulls.  
CIBP 3762'.

Plugging Proposal Received By: RICHARD WILLIAMS WitnessType: COMPLETE (100%)  
Date/Time Plugging Completed: 08/25/2009 10:30 AM KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

Perf Tech perforated two holes at 1700' and 920'.  
Allied pumped 525 sxs 60/40 pozmix - 4% gel with 600# hulls.  
Circulated cement out 8 5/8".  
Max. P.S.I. 600#. S.I.P. 300#.

Perfs:

| Top  | Bot  | Thru | Comments |
|------|------|------|----------|
| 3444 | 3756 |      |          |

INVOICED  
DATE 10-7-09  
INV NO 2010060345

KANSAS CORPORATION COMMISSION  
SEP 02 2009

Remarks: ORIGINALLY KNOWN AS KNIPP #6. ALLIED CEMENTING COMPANY.

RECEIVED

Plugged through: CSG

District: 04

Signed Richard Williams  
(TECHNICIAN)

CM

SEP 01 2009

PKT

SHELL OIL COMPANY

#6

KNIPP

14-9-21W  
SE NW SE

Contr. \_\_\_\_\_ GRAHAM \_\_\_\_\_ County

E. 2263 Comm. 10-19-48 Comp. 11-26-48 IP 3000 FOPD DEPTH

| Tops  | Depth | Datum | Casing                     |
|-------|-------|-------|----------------------------|
|       |       |       | 8" 1726 PERF 39 S, 3740-48 |
|       |       |       | 4.5" 3821 900' 01H/3 HRS   |
| TOP   | 3202  | -939  | ACIL 500                   |
|       |       |       | S.W. 190 80/3 HRS          |
| LANS  | 3114  | -1181 |                            |
| COING | 3700  | -1437 |                            |
| ARB   | 3741  | -1478 |                            |
| T.D.  | 3823  | -1560 |                            |

INDEPENDENT OIL & GAS SERVICE  
WICHITA, KANSAS

|  |  |  |
|--|--|--|
|  |  |  |
|  |  |  |
|  |  |  |