

15-163-01980-0001

6-30 4-041978

E
R-06,557

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Number: 15- - 08-44

NW
NE SW SW /4 SEC. 35, 10 S, 19 W
990 2310 ^{27KCL} feet from S section line
4290 feet from E section line

RECEIVED
STATE CORPORATION COMMISSION

7-15-98
JUL 15 1998

Operator license# 30606 Lease: Casey Well # 1

Operator: Murfin Drilling Company County: Rooks
Wichita, Kansas

Address: 250 N. Water - #300 Well total depth 3551 ^{115.41} feet
Wichita, Kansas 67202 Conductor Pipe: 0 inch @ 0 feet
Surface Pipe: 8 5/8 Inch ^{290.98} ^{27KCL} Feet
W/N/A sxs cmt.

Aband. oil well, Gas well, Input well , SWD , D & A

Plugging contractor: Halliburton Cementing License# -

Address: Hays, Kansas 67601

Company to plug at: Hour: 8:00 A.M. Day: 30 Month: June Year: 1998

Plugging proposal received from: John Gerstner

Company: Murfin Drilling Company Phone: -

Were: 5 1/2" casing set at 3495' w/125 sxs cement. Perfs at 677' - 680'.
Dakota at 850'. 4" boiler casing to 1600' from surface. Plug back to 880'.
Ordered 300 sxs 60/40 pozmix - 10% gel with 1/4# F.C. plus 400# hulls.

Plugging Proposal Received by: Dennis Hamel
Plugging operations attended by agent? All [], Part [X], None []

Completed: Hour: 11:30 A.M., Day: 30, Month: June, Year: 1998

Actual plugging report: 5 1/2" casing; R.I.H. with tubing to 870'. Spotted 30 sxs cement with 150# hulls. Circulated cement to surface. Pulled tubing and squeezed casing to 700# Max with 5 sxs cement. S.I.P. at 650#. Squeezed 8 5/8" S.P. with 30 sxs cement with 100# hulls.

Remarks:
Condition of casing (in hole): GOOD - BAD
Bottom plug (in place): YES, CALC, NO
Plugged through TUBING CASING
Any plug: YES X NO
Dakota plug: YES X NO
Elevation: G.L.

I did [X] / did not [] observe the plugging.

Dennis J. Hamel
(agent)

Form CP-2/3

INVOICED

DATE 7-16-98

INV. NO. 50936