

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

ORIGINAL

Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33640
Name: Haas Petroleum, LLC
Address: 800 West 47th Street, Suite #409
City/State/Zip: Kansas City, MO 64112
Purchaser: Plains Marketing, L.P.
Operator Contact Person: Mark Haas
Phone: (816) 531.5922
Contractor: Name: Skyy Drilling, LLC
License: 33557
Wellsite Geologist: David Griffin, RG.

Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SIOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:
Operator: _____
Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back Plug Back Total Depth
 Commingled Docket No. _____
 Dual Completion Docket No. _____
 Other (SWD or Enhr.?) Docket No. _____

10/27/07	10/31/07	11/1/07
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 207-27197-0000
County: Woodson
NE SE SW Sec. 07 Twp. 24 S. R. 14 East West
985 feet from (S) N (circle one) Line of Section
2260 feet from E / (W) (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE NW SW
Lease Name: Dye Well #: 44
Field Name: Winterschied
Producing Formation: Mississippian Dolomite
Elevation: Ground: 1164' Kelly Bushing: _____
Total Depth: 1777' Plug Back Total Depth: 1774'
Amount of Surface Pipe Set and Cemented at 40 Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from 1777'
feet depth to surface w/ 135 sx cmt.

Drilling Fluid Management Plan
(Data must be collected from the Reserve Pit)
Chloride content _____ ppm Fluid volume _____ bbls
Dewatering method used _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

ALT 2-Dlg-1/23/09

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Marcia Littell
Title: Agent Date: 01/09/08
Subscribed and sworn to before me this 9th day of JANUARY
20 08
Notary Public: Maureen Elton
Date Commission Expires: 9/18/2010

KCC Office Use ONLY

Letter of Confidentiality Received
 If Denied, Yes Date: _____ **RECEIVED**
 Wireline Log Received **KANSAS CORPORATION COMMISSION**
 Geologist Report Received
 UIC Distribution

JAN 14 2008
CONSERVATION DIVISION
WICHITA, KS

Maureen Elton
Notary Public, State of Kansas
My Appt Expires 9/18/2010

Operator Name: Haas Petroleum, LLC Lease Name: Dye Well #: 44
 Sec. 07 Twp. 24 S. R. 14 East West County: Woodson

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Gamma Ray Neutron	<input type="checkbox"/> Log Formation (Top), Depth and Datum <input checked="" type="checkbox"/> Sample Name Top Datum
--	--

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	11 1/4"	8 5/8"	20.5#	40'	Class "A"	20	2% CaCl ₂ , 2% Gel
Production	6 3/4"	4 1/2"	9.5#	1774'	60/40 Poz Mix	135	8% gel, 1/4# flocele

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate				
<input type="checkbox"/> Protect Casing				
<input type="checkbox"/> Plug Back TD				
<input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
4 SPF	1721-1729'	2000 gal. 15% HCL	1721-1729'

TUBING RECORD		Size <u>2 3/8"</u>	Set At <u>1729.42'</u>	Packer At	Liner Run <input type="checkbox"/> Yes <input type="checkbox"/> No
Date of First, Resumerd Production, SWD or Enhr.		Producing Method <input type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)			
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity

Disposition of Gas	METHOD OF COMPLETION	Production Interval	RECEIVED
<input type="checkbox"/> Vented <input type="checkbox"/> Sold <input type="checkbox"/> Used on Lease <i>(If vented, Submit ACO-18.)</i>	<input type="checkbox"/> Open Hole <input checked="" type="checkbox"/> Perf. <input type="checkbox"/> Dually Comp. <input type="checkbox"/> Commingled <input type="checkbox"/> Other (Specify) _____	_____	KANSAS CORPORATION COMMISSION

JAN 14 2008
 CONSERVATION DIVISION
 WICHITA, KS

CONSOLIDATED OIL WELL SERVICES, LLC
 P.O. BOX 884, CHANUTE, KS 66720
 620-431-9210 OR 800-467-8676

TICKET NUMBER 13116
 LOCATION Eureka
 FOREMAN Kevin McCoy

TREATMENT REPORT & FIELD TICKET
 CEMENT

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY																
11-1-07	3451	Dye # 44				Wichita																
CUSTOMER <u>Haas Petroleum, LLC</u>			SKYY DRIG RIG 2																			
MAILING ADDRESS <u>800 West 47th St # 409</u>																						
CITY <u>Kansas City</u>	STATE <u>Mo</u>	ZIP CODE <u>64112</u>																				
<table border="1"> <thead> <tr> <th>TRUCK #</th> <th>DRIVER</th> <th>TRUCK #</th> <th>DRIVER</th> </tr> </thead> <tbody> <tr> <td>445</td> <td>Justin</td> <td></td> <td></td> </tr> <tr> <td>479</td> <td>SHANNON</td> <td></td> <td></td> </tr> <tr> <td>502</td> <td>Heath</td> <td></td> <td></td> </tr> <tr> <td>452 T63</td> <td>Jim</td> <td></td> <td></td> </tr> </tbody> </table>							TRUCK #	DRIVER	TRUCK #	DRIVER	445	Justin			479	SHANNON			502	Heath		
TRUCK #	DRIVER	TRUCK #	DRIVER																			
445	Justin																					
479	SHANNON																					
502	Heath																					
452 T63	Jim																					

JOB TYPE Completion HOLE SIZE 6 3/4 HOLE DEPTH 1777' CASING SIZE & WEIGHT 4 1/2 9.5 #
 CASING DEPTH 1780' 1774 DRILL PIPE _____ TUBING _____ OTHER _____
 SLURRY WEIGHT 12.8-13.4 SLURRY VOL 55 bbl WATER gal/sk 8-8.5 CEMENT LEFT In CASING 60' +/-
 DISPLACEMENT 28.8 bbl DISPLACEMENT PSI 700 PSI 1200 Bump Plug RATE _____

REMARKS: Safety Meeting: Rig up to 4 1/2 casing. Break Circulation w/ 5 min fresh water. Mixed 125 sks 60/40 Pozmix Cement w/ 8% Gel, 1/4" Flocle Analok @ 12.8 # per/gal, yield 1.65. Tail in w/ 50 sks Thick Set Cement w/ 5" Kol-Seal Analok @ 13.4 # per/gal, yield 1.69. Shut down. Release Plug. Displace w/ 20 min fresh water. Final Pumping Pressure 700 PSI. Bump Plug to 1200 PSI. wait 2 minutes. Release Pressure. First Heil. Good Cement Returns to Surface 3 18 bbl Heavy to Pt. Job Complete. Rig down.

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
5401	1	PUMP CHARGE	200.00	200.00
5406	30	MILEAGE	3.20	97.00
1131	135 sks	60/40 Pozmix Cement	9.80	1323.00
1118 A	930 #	Gel 8%	.15 #	139.50
1107	34 #	Flocle 1/4" per/sk	1.90 #	64.60
1126 A	50 sks	Thick Set Cement	15.40	770.00
1110 A	250 #	Kol-Seal 5" per/sk	.38 #	95.00
5407	8.55 tons	Ten Mileage Bulk Truck	111.00	948.00
1123	6000 gal	City water	1.00	6000.00
5501 C	3 Hrs	water transport	100.00	300.00
4404	1	4 1/2 Top Rubber Plug	40.00	40.00
4310	1	4 1/2 Back Plate	25.00	25.00
			Sub Total	4057.90
			SALES TAX 6.3%	255.65
			ESTIMATED TOTAL	4313.55

RECEIVED
 KANSAS CORPORATION COMMISSION
 JAN 14 2008
 CONSERVATION DIVISION
 WICHITA, KS

Thank You
 217985

AUTHORIZATION Called By Bob Haasell TITLE Talposhee DATE _____
 4217.55

CONSOLIDATED OIL WELL SERVICES, LLC
 P.O. BOX 884, CHANUTE, KS 66720
 620-431-9210 OR 800-467-8676

TICKET NUMBER 12775
 LOCATION Eureka
 FOREMAN Troy Brubaker

TREATMENT REPORT & FIELD TICKET
 CEMENT

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
10-22-07	3451	Dye #44				Wagoner
CUSTOMER			TRUCK #	DRIVER	TRUCK #	DRIVER
Hoas Petroleum, LLC			445	Cliff		
MAILING ADDRESS			502	Ed		
800 West 47th Ste 409						
CITY	STATE	ZIP CODE				
Kansas City	Mo	64122				

JOB TYPE Surface HOLE SIZE 11 1/4" HOLE DEPTH 40' CASING SIZE & WEIGHT 1 1/2"
 CASING DEPTH _____ DRILL PIPE _____ TUBING _____ OTHER _____
 SLURRY WEIGHT 14.80 SLURRY VOL _____ WATER gal/sk _____ CEMENT LEFT in CASING 10'
 DISPLACEMENT 2861 DISPLACEMENT PSI _____ MIX PSI _____ RATE _____

REMARKS: Safety Meeting: Rig up to 8 1/2" casing break circulation w/ water.
Mixed 20% Class A Cement w/ 2% Gel + 2% Cels @ 14.8 = 14.8
Displace w/ 2861 water. Shut casing in w/ good cement to surface.

Job Complete

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
54015	1	PUMP CHARGE	650.00	650.00
5406	36	MILEAGE	2.75	99.00
11045	2014	Class A Cement	12.20	24570.80
1107	40*	Cels 22	.67	26.80
1118A	40*	Gel 22	.15*	6.00
5407		Ten - Mileage Bulk Truck	mk	285.00
RECEIVED KANSAS CORPORATION COMMISSION JAN 14 2008 CONSERVATION DIVISION WICHITA, KS				
<u>Thank U!</u>				
			6.92	1328.24
			SALES TAX	17.44
			ESTIMATED TOTAL	1328.24

AUTHORIZATION Called by Ren

TITLE Skay

DATE _____

211992

1328.24