

6 010185

34

API NUMBER 15- 051- 24431-00-00

SE, SEC. 19, T 12 S, R 19 W1/2

330 feet from S section line

330 feet from E section line

Lease Name Armbrister Well # 1-19

County Ellis 128.67

Well Total Depth 3959 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 301

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

Operator License # 6033

Operator: Murfin Drilling Co.

Name & Address 250 N. Water

Wichita KS.

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well (D&A)

Other well as hereinafter indicated _____

Plugging Contractor Murfin Drilling Co. License Number 6033

Address Wichita

Company to plug at: Hour: _____ Day: 27 Month: 9 Year: 19 86

Plugging proposal received from Lloyd Deliff

(company name) Murfin (phone) _____

were: Order 2 1/2 5x. cem. 60/40 permix 6 1/2% Gel.

Heavy mud between all plugs

Pump cem. down drill pipe

Elev. 2175 Anhydrite 1544-82 Arbuckle 3905

Dakota 1650 Plugging Proposal Received by D.Z.B.

525 = 825 (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None _____

Operations Completed: Hour: 6:15 PM Day: 27 Month: 9 Year: 19 86

ACTUAL PLUGGING REPORT Proposed & plugged as follows.

25 5x @ 3905

25 5x @ 1570

100 5x @ 825

40 5x @ 320

10 5x @ 40

RECEIVED
STATE CORPORATION COMMISSION
CONS. DIV. WICHITA, KS

10-14-1986

OCT 17 1986

Remarks: 15 5x in Ret Hole B.S. Titan cem. &
(If additional description is necessary, use BACK of this form.)

INVOICED

DATE 10-15-86 observe this plugging.

INV. NO. 15160 plug of

Signed Paul Balthazor (TECHNICIAN) 10-10-86

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Date 9/22/86 month day year

API Number 15- 051-24431-00-00

OPERATOR: License # 6033 Name Murfin Drilling Company Address 250 N. Water, Suite 300 City/State/Zip Wichita, Ks, 67202 Contact Person David Doyel Phone 316-267-3241

SE SE SE Sec. 19 Twp. 12 S, Rg. 19 East West 330 Ft. from South Line of Section 330 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 6033 Name Murfin Drilling Company City/State Wichita, Ks, 67202

Nearest lease or unit boundary line 330 feet County Ellis

Lease Name ARMBRISTER Well # 1-19 Ground surface elevation feet MSL

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield X Mud Rotary Gas Inj X Pool Ext Air Rotary OWWO Expl Wildcat Cable

Domestic well within 330 feet: yes Xno Municipal well within one mile: yes Xno

Depth to bottom of fresh water 150 Depth to bottom of usable water 800

Surface pipe by Alternate: 1 2 X Surface pipe planned to be set 300

Conductor pipe required Projected Total Depth 3920 feet

Formation Arbuckle

If OWWO: old well info as follows:

Operator Well Name Comp Date Old Total Depth

certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 9-18-86 Signature of Operator or Agent David Doyel Title Geological Manager

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 250 feet per Alt. This Authorization Expires 3-18-87 Approved By 9-18-86

SE SE SE Sec. 19 Twp. 12 S, Rg. 19 East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 1600 feet depth with 25 sxs of 60/40 poz, .6% gel, .3% cc 2nd plug @ 880 feet depth with 100 sxs of 3rd plug @ 340 feet depth with 40 sxs of 4th plug @ 40 feet depth with 10 sxs of 5th plug @ Rathole with 15 sxs (b) Mousehole with sxs

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. In Addition: Call district office after well is either plugged or production casing is cemented in.

(Call 7 a.m. to 5 p.m. workdays)

District office use only:

API #15- 051-24431 surface casing of feet set with sxs at hours, 19 Alternate 1 or 2 surface pipe was used. Alternate 2 cementing was completed @ ft. depth with sxs on 19 hole plugged 19, agent SEP 22 1986

RECEIVED DIST. #6 Hays, KS