

10/15/09

CONFIDENTIAL

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

ORIGINAL

Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33365
Name: Layne Energy Operating, LLC
Address: 1900 Shawnee Mission Parkway
City/State/Zip: Mission Woods, KS 66205
Purchaser: _____
Operator Contact Person: Timothy H. Wright
Phone: (913) 748-3960
Contractor: Name: Thornton Air Rotary
License: 33606

Wellsite Geologist: _____
Designate Type of Completion:
____ New Well ____ Re-Entry Workover
____ Oil ____ SWD ____ SLOW ____ Temp. Abd.
 Gas ____ ENHR ____ SIGW
____ Dry ____ Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:
Operator: _____
Well Name: _____
Original Comp. Date: 5/31/2007 Original Total Depth: _____
____ Deepening Re-perf. ____ Conv. to Enhr./SWD
____ Plug Back ____ Plug Back Total Depth
 Commingled Docket No. _____
____ Dual Completion Docket No. _____
____ Other (SWD or Enhr.?) Docket No. _____
6/22/2007 6/25/2007
Spud Date or Date Reached TD Completion Date or
Recompletion Date Recompletion Date

API No. 15 - 205-26949-00-01
County: Wilson
____ SW SE Sec. 33 Twp. 30 S. R. 14 East West
621 feet from N (circle one) Line of Section
1730 feet from W (circle one) Line of Section
Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE NW SW
Lease Name: McCabe Well #: 15-33
Field Name: Cherokee Basin Coal Area
Producing Formation: Cherokee Coals
Elevation: Ground: 884' Kelly Bushing: _____
Total Depth: 1523' Plug Back Total Depth: 1515.6'
Amount of Surface Pipe Set and Cemented at 20 Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from 1515
feet depth to Surface w/ 155 sx cmt.

Drilling Fluid Management Plan WONS 31209
(Data must be collected from the Reserve Pit)
Chloride content N/A ppm Fluid volume _____ bbls
Dewatering method used N/A - Air Drilled
Location of fluid disposal if hauled offsite:
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: [Signature]
Title: Agent Date: 10/15/09
Subscribed and sworn to before me this 15 day of October,
2007.
Notary Public: MacLaughlin Darline
Date Commission Expires: 1-4-2009

MacLAUGHLIN DARLINE
Notary Public - State of Kansas
My Appt. Expires 1-4-2009

KCC Office Use ONLY
 Letter of Confidentiality Attached
If Denied, Yes Date: _____
 Wireline Log Received
 Geologist Report Received
 UIC Distribution

RECEIVED
KANSAS CORPORATION COMMISSION

OCT 16 2007

CONSERVATION DIVISION
WICHITA, KS

CONFIDENTIAL

OCT 15 2007

KCC

Operator Name: Layne Energy Operating, LLC Lease Name: McCabe Well #: 15-33
 Sec. 33 Twp. 30 S. R. 14 East West County: Wilson

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Compensated Density Neutron Dual Induction	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample <table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:60%;">Name</td> <td style="width:20%;">Top</td> <td style="width:20%;">Datum</td> </tr> <tr> <td>Pawnee Lime</td> <td>896 GL</td> <td>-12</td> </tr> <tr> <td>Excello Shale</td> <td>1028 GL</td> <td>-144</td> </tr> <tr> <td>V Shale</td> <td>1097 GL</td> <td>-213</td> </tr> <tr> <td>Mineral Coal</td> <td>1140 GL</td> <td>-256</td> </tr> <tr> <td>Mississippian</td> <td>1412 GL</td> <td>-528</td> </tr> </table>	Name	Top	Datum	Pawnee Lime	896 GL	-12	Excello Shale	1028 GL	-144	V Shale	1097 GL	-213	Mineral Coal	1140 GL	-256	Mississippian	1412 GL	-528
Name	Top	Datum																	
Pawnee Lime	896 GL	-12																	
Excello Shale	1028 GL	-144																	
V Shale	1097 GL	-213																	
Mineral Coal	1140 GL	-256																	
Mississippian	1412 GL	-528																	

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacjs Used	Type and Percent Additives
Surface	11"	8.625"	24	20'	Class A	4	Type 1 cement
Casing	6.75"	4.5"	10.5	1515'	Thick Set	155	10# KOL seal @ sx

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
	See Attached Page		

TUBING RECORD		Size	Set At	Packer At	Liner Run	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		2-3/8"	1391'			
Date of First, Resumerd Production, SWD or Enhr.			Producing Method			
6/26/2007			<input type="checkbox"/> Flowing <input checked="" type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)			
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity	
	0	145	3			

Disposition of Gas	METHOD OF COMPLETION	Production Interval
<input type="checkbox"/> Vented <input checked="" type="checkbox"/> Sold <input type="checkbox"/> Used on Lease <i>(If vented, Submit ACO-18.)</i>	<input type="checkbox"/> Open Hole <input checked="" type="checkbox"/> Perf. <input type="checkbox"/> Dually Comp. <input checked="" type="checkbox"/> Commingled <input type="checkbox"/> Other (Specify) _____	

RECEIVED
KANSAS CORPORATION COMMISSION

OCT 16 2007

CONSERVATION DIVISION
WICHITA, KS

CONFIDENTIAL
 OCT 15 2007
 KCC

Operator Name:	Layne Energy Operating, LLC.		
Lease Name:	McCabe 15-33		
	Sec. 33 Twp. 303S Rng. 14E, Wilson County		
API:	15-205-26949-00-01		
Shots per Foot	Perforation Record	Acid, Fracture, Shot, Cement Squeeze Record	Depth
Initial Perforations (5/2007)			
4	Rowe 1354' - 1355.5' Mineral 1139.5' - 1142'	5100 lbs 20/40 sand 454 bbls water 600 gals 15% HCl acid	1139.5' - 1335.5'
4	Croweburg 1098' - 1100.5' Bevier 1079' - 1081'	6400 lbs 20/40 sand 517 bbls water 500 gals 15% HCl acid	1079' - 1100.5'
Recompletion Perforations (6/2007)			
4	Mulky 1028' - 1033' Summit 1011' - 1014.5'	10100 lbs 20/40 sand 655 bbls water 750 gals 15% HCl acid	1011' - 1033'

RECEIVED
 KANSAS CORPORATION COMMISSION

OCT 16 2007

CONSERVATION DIVISION
 WICHITA, KS