

4-041758

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

3-4

API Number: 15- -

NW SW NE /4 SEC. 14, 10 S, 20 W
1650 feet from N section line
2310 feet from E section line

Operator license# 5337

Lease: Stithem Well # 5

Operator: Nadel and Gussman

County: Rooks

Address: 3200 First National Tower
Tulsa, OK 74103

Well total depth 3770 ^{122.52} feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 159 feet
100 sxs

Aband. oil well , Gas well , Input well , SWD , D & A

Plugging contractor: Allied Cementing License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: P.M. Day: 4 Month: March Year: 1996

Plugging proposal received from: John Rolo

Company: Nadel and Gussman Phone: 918-583-3333

5 1/2 csg, set w 3769 w/125 sxs cnt
Were: 5 1/2" casing ⁵² at 1658' w/300 sxs cement.

Ordered 250 sxs. 60/40 pozmix - 10% gel with 1/4# F.C. plus 500# hulls.

Perfs 3766' - 3770' - BP at 3750' - Perfs 3653' - 3657' - BP at 3600'.

RECEIVED
STATE CORPORATION COMMISSION

MAR 27 1996
3-27-1996
CONSERVATION DIVISION
Wichita Kansas

Plugging Proposal Received by: Dennis L. Hamel

Plugging operations attended by agent? All[], Part[], None[]

Completed: Hour: 3:00 P.M. , Day: 4 , Month: March , Year: 1996

Actual plugging report: R.I.H. with tubing to 2500' spotted 100 sxs cement with 200# hulls.
Pulled tubing to 800' and circulated cement with 60 sxs cement. Pulled tubing and squeezed casing with 10 sxs cement. Max. P.S.I. 500#. Hooked-up to 8 5/8" S.P. Squeezed 25 sxs cement with 100# hulls. S.I.P. 100#.

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD BAD Anhy.plug: YES NO
Bottom plug(in place): YES , CALC , NO Dakota plug: YES , NO
Plugged through TUBING , CASING . Elevation: _____ GL

I did / did not observe the plugging.

Dennis L. Hamel
(agent)

Form CP-2/3

INVOICED
DATE MAR 28 1996
INV. NO. 45156

PO