

4- 060329

15-163-02171-0000 ²³⁷

D-08,580

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15- - 2-10-61

S2 NW SW /4 SEC. 16, 10 S, 20 W
1650 feet from S section line
4620 feet from E section line

Operator license# 6750

Lease Cowgill well # 2

Operator: Trumart Oil Company

County Rooks

Address: 1400 Washington
Ellis, Kansas 67637

Well total depth 4293 feet ^{139.52}
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 175 feet

Aband. oil well , Gas well , Input well , SWD , D & A

Plugging contractor: Co Tools License# -

Address: _____

Company to plug at: Hour: 9:30A.M. Day: 21 Month: August Year: 92

Plugging proposal received from: Don Martin

Company: Trumart Oil Company Phone: _____

Were: Order 200 sxs. common cement.
Well plugged backed for shallow disposal. Log P.B.T.D. 1223'.

Plugging Proposal Received by: Herb Deines
Plugging operations attended by agent? All[], Part[], None[]

Completed: Hour: 10:20A.M., Day: 21, Month: August, Year: 92

Actual plugging report: 8 5/8" to 175'. 5 1/2" to 3885'. Two stage
from 1690' to surface with 500 sxs. cement. Tubing to 1223' and
cemented in with cement. Tied onto annulus and had instant 200# S.I.P.
Tied onto tubing and pumped 185 sxs. cement. Max. 1500#. S.I.P. 600#.

RECEIVED
STATE CORPORATION COMMISSION

AUG 31 1992

Remarks: Allied Cementing.
Condition of casing(in hole): GOOD BAD Anhy.plug: YES NO
Bottom plug(in place): YES , CALC , NO Dakota plug: YES , NO
Plugged through TUBING , CASING . Elevation: 2222 GL

CONSERVATION DIVISION
Wichita, Kansas

I did / did not observe the plugging.

[Signature]

DATE 9-29-92
36255

OCT 28 1992

[Signature]

(agent)

Form CP-2/3