Form CP-3 Rev. 6-26-62

KANSAS

state corporation commission

CONSERVATION DIVISION AGENT'S REPORT

J. P. Roberts Administrator 500 Insurance Building Wichita, Kansas 67202



		er Oil Co.
		., Wichita, Kansas
Lease Name	Sutor	Well No. 3
Location N	W SE SE	Sec. 14 Twp. 10 Rge. 20 (E) (W) X
County	Rooks	Total Depth 3769
Abandoned Oil Wel	ll_X Gas Well	Input WellD & A
Other well as her	reafter indicated:	
Plugging Contract	tor:	Knight Casing Pulling
Address:	Box 405 Cha	ase, Kansas License No. 436
Operation Complet	ted: Hour 11:30 Ap	Day 4 Month 5 Year 1968
The Ahove well we	as plugged as follow	II.o. A
INC ADOVE WELL WA	p brabboa ap rottom	vs:
		201° cwc Cem. Mat. 125 sc 50-50 poz cement W/6%
Total Depth 3769		201' cwc Cem. Mat. 125 sc 50-50 poz cement W/6%
Total Depth 3769 $5\frac{1}{2} \text{ csg set at } 376$	• 8 5/8 csg set at 65° cw 125 sc cement	201' cwc Cem. Mat. 125 sc 50-50 poz cement W/6%
Total Depth 3769 $5\frac{1}{2} \text{ csg set at } 376$	• 8 5/8 csg set at 65° cw 125 sc cement to 3750° and dumped	201° cwc Cem. Mat. 125 sc 50-50 poz cement W/6%
Total Depth 3769 $5\frac{1}{2}$ csg set at 376 Filled with sand Recov. 500° of 5	• 8 5/8 csg set at 65° cw 125 sc cement to 3750° and dumped $\frac{1}{2}$ csg.	201° cwc Cem. Mat. 125 sc 50-50 poz cement W/6% t. d 5 sc cement with dump bailer.
Total Depth 3769 $5\frac{1}{2}$ csg set at 376 Filled with sand Recov. 500° of 5	• 8 5/8 csg set at 65° cw 125 sc cement to 3750° and dumped $\frac{1}{2}$ csg.	201° cwc Cem. Mat. 125 sc 50-50 poz cement W/6%
Total Depth 3769 $5\frac{1}{2}$ csg set at 376 Filled with sand Recov. 500° of 5	• 8 5/8 csg set at 65° cw 125 sc cement to 3750° and dumped $\frac{1}{2}$ csg.	201° cwc Cem. Mat. 125 sc 50-50 poz cement W/6% t. d 5 sc cement with dump bailer.
Total Depth 3769 $5\frac{1}{2}$ csg set at 376 Filled with sand Recov. 500° of 5	• 8 5/8 csg set at 65° cw 125 sc cement to 3750° and dumped $\frac{1}{2}$ csg.	201° cwc Cem. Mat. 125 sc 50-50 poz cement W/6% t. d 5 sc cement with dump bailer.
Total Depth 3769 5½ csg set at 376 Filled with sand Recov. 500° of 59 Pumped thru 8 5/8	• 8 5/8 csg set at 65° cw 125 sc cement to 3750° and dumped \[\frac{1}{2} \text{ csg.} \] 8 plg container with	201° cwc Cem. Mat. 125 sc 50-50 poz cement W/6% t. d 5 sc cement with dump bailer.
Total Depth 3769 5½ csg set at 376 Filled with sand Recov. 500° of 5% Pumped thru 8 5/8	• 8 5/8 csg set at 65° cw 125 sc cement to 3750° and dumped \[\frac{1}{2} \text{ csg.} \] 8 plg container with	201° cwc Cem. Mat. 125 sc 50-50 poz cement W/6% t. d 5 sc cement with dump bailer. h 3 hullis, 20 sc gel, plug and 125 sc cement.