

4-041761

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

4-4

API Number: 15- 10-08-54
200' S. of
C S2 NW /4 SEC. 33, 10 S, 20 W
2200 feet from N section line
1320 feet from W section line

Operator license# 5447

Lease: Allphin Well # A-4

Operator: OXY USA, Inc.

County: Rooks

Address: 110 S. Main - #800
Wichita, Kansas 67202

Well total depth 3825 ^{124.31} feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 250 feet
w/200 sxs.

Aband. oil well , Gas well , Input well , SWD , D & A

Plugging contractor: Allied Cementing License#

Address: Russell, Kansas 67665

Company to plug at: Hour: 8:00 A.M. Day: 4 Month: April Year 1996

Plugging proposal received from: J.D. Hininger

Company: OXY USA, Inc. Phone:

Were: 5 1/2" casing set at 3825' w/150 sxs cement. Perf. at 3601' - 3758'
Ordered 350 sxs. 60/40 pozmix -10% gel plus 500# hulls.
Anhy. 1640' - Elev. 2171' - Perf salt at 2250'.
*Squeezed at 1260' - 1278' w/200 sxs. Squeezed at 990' w/120 sxs.

RECORDED
INDEXED
APR 12 1996
KANSAS STATE COMMISSION

Plugging Proposal Received by: Dennis L. Hamel

Plugging operations attended by agent? All[], Part[], None[X]

Completed: Hour: 1:00 P.M., Day: 4, Month: April, Year: 1996

Actual plugging report: Squeezed 8 5/8" S.P. with 50 sxs 60/40 pozmix - 10% gel with 200# hulls mixed in cement. S.I.P. 100#. Squeezed 5 1/2" casing with 200 sxs 60/40 pozmix 10% gel with 300# hulls mixed in cement. Max. P.S.I. 400#. S.I.P. 300#.

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD BAD Anhy.plug: YES NO
Bottom plug(in place): YES , CALC , NO Dakota plug: YES , NO
Plugged through TUBING , CASING . Elevation: 2171 GL

I did[] did not[] observe the plugging.

Dennis L. Hamel
(agent)

Form CP-2/3

INVOICED

DATE APR 18 1996

INV. NO. 45361

4-4 JUN 27 1996