

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-179-20691-00-01
Spot: NWNENW Sec/Twnshp/Rge: 10-10S-26W
4939 feet from S Section Line, 3771 feet from E Section Line
Lease Name: FULLER OWWO Well #: 4
County: SHERIDAN Total Vertical Depth: 4395 feet

Operator License No.: 33268
Op Name: RL INVESTMENT, LLC
Address: 217 SAINT PETER ST
MORLAND, KS 67650

String	Size	Depth (ft)	Pulled (ft)	Comments
SURF	8.625	265	0	w/210 sxs cmt
PROD	5.5	4395	0	w/175 sxs cmt <u>142.84</u>

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 11/12/2009 9:00 AM
Plug Co. License No.: 32810 Plug Co. Name: PROFESSIONAL PULLING SERVICES LLC
Proposal Rcvd. from: RANDALL PFEIFER Company: RL INVESTMENT, LLC Phone: (785) 627-5711

Proposed Plug Method: Ordered 500 sxs 60/40 pozmix - 4% gel - 500# hulls.
Plug through tubing.

Plugging Proposal Received By: CASE MORRIS Witness Type: COMPLETE (100%)
Date/Time Plugging Completed: 11/12/2009 12:00 PM KCC Agent: DARREL DIPMAN

Actual Plugging Report:

8 5/8" surface casing set at 265' w/210 sxs cement.
5 1/2" production casing set at 4395' w/175 sxs cement.
Port collar at 2278' w/400 sxs cement. TD 4395'.
11-12-2009 - Ran tubing to 3000' - pumped 275 sxs cement with 400# hulls.
Pulled tubing to 1500' - pumped 170 sxs cement with 100# hulls.
Pulled tubing to surface.
Connected to production casing - pumped 45 cement.
Connected to 8 5/8" surface casing - pumped 5 sxs cement.
Max. P.S.I. 300#. S.I.P. 200#.

Perfs:

Top	Bot	Thru	Comments
4070	4072		
4050	4052		
4026	4030		
3928	3931		

INVOICED

DATE 1-4-10
INV. NO. 2010060655

Remarks: S.O.S. CEMENTING COMPANY-TICKET #404.

Plugged through: TBG

District: 04

Signed

Darrel Dipman

(TECHNICIAN)

CM

RECEIVED

NOV 30 2009

Form CP-2/3

KCC WICHITA

NOV 17 2009

RAINS & WILLIAMSON OIL COMPANY, INC.

435 PAGE COURT

WICHITA, KS 67202


#4 FULLER

10-10-26W

NW NE NW

CONTR RAINS & WILLIAMSON OIL CTY SHERIDAN

GEOL _____ FIELD FULLER



ELV 2637 KBSPD 8/14/83 CARD ISSUED 11/10/83 IP P 100 BOPD & WTR
2627 GL LKC 3920-4072 OA
 API 15-179-20,691

LOG	Tops	Depth/Datum	
ANH	2260 + 377		8 5/8 " 265/210SX; 5 1/2 " 4395/175SX; PORT COLLAR AT 2277.81/400SX
TOP	3638-1001		DST (1) 3892-3938 (LKC 35' & 50' ZNS) / 30-30-60-45, REC 240' GOCM (40% G, 30% OIL, 30% M), 180' GOCM (20% G, 4% OIL, 40% M), 180' GOCMW (10% G, 40% OIL, 15% M, 35% W), 180' GOCMW (5% G, 45% OIL, 10% M, 40% W), 180' GOCW (5% G, 45% OIL, 0% M, 50% W), 180' OIL SPKD MSW, SIP 1104-1074#, FP 122-295 / 346-540#, BHT 120°
HEEB	3850-1213		DST (2) 4007-40 (LKC 140' ZN) / 30-30-60-45, 910' GIP, REC 260' GSY FROGGY SMC0, 270' GSY FROGGY OIL, SIP 643-756#, FP102-132 / 163-214, BHT 120°
LANS	3888-1251		DST (3) 4045-84 (LKC 160 & 180' ZNS) / 30-30-60-45, 1180' GIP, REC 90' SMC0, 230' GO, 240' GSY FROGGY OIL, 300' GSY FROGGY SMC0, SIP 387-408#, FP 122-193 / 244-316#
BKC	4122-1485		DST (4) 4088-4101 (LKC 200' ZN) / 30-30-30-30, REC 5' M, W/ OIL SPTS, SIP 40-40#, FP 40-40 / 40-40#, BHT 120°
CHER SH	4335-1698		(over)
CHER LM	4352-1715		
RTD	4395-1758		
LTD	4396-1759		