6-15

4-<u>032069</u>

		D-25,8	84
TO:	API	Number: 15-065	-21,085 -090)
STATE CORPORATION COMMISSION			
CONSERVATION DIVISION - PLUGGING	NE SE NE	/4 SEC	19 , 10 S, 21 W
			m S section line
130 SOUTH MARKET, SUITE 2078			
WICHITA, KANSAS 67202	_330	feet fro	m E section line
Operator license#_5146	Lease:	McClellan	Well # <u>1</u>
Operator 1100m50			
Operator: Rains & Williamson Oil Co. Inc.	County:	Graham	
		7 1	4018 /30.59 feet inch @0 feet
Address: 220 W. Douglas	Well total	. deptn	inch @ 0 feet
Suite #435 Wichita, Kansas 67202		_	204 feet
wichita, Kansas 6/202	burrace pr	.pe 070 inen e_	
Aband. oil well, Gas well, Input wel	1, SWD_	x_, D & A	
Plugging contractor: Halliburton		Lic	ense#
Address: Hays, Kansas 67601			
Company to plug at: Hour: A.M. Day: 15	Month	June	Year: 1995
company to prug at: nour bay			
Plugging proposal received from: A.D. Belt	& Halliburto	on	
Company: Rains & Williamson Oil Co. Inc.	F	Phone:	
Were: Order 250 sxs. 60/40 posmix - 10% gel -	500# hulls.		
		<u> </u>	
			
			8/4
			Contra
			STATE CONTRE
			On SI
·	<u>,</u>		CON: COMPA
		·	William & Branch
Plugging Proposal Received by: Carl Goodrow			- 430 - 495
Plugging operations attended by agent? All[>	K], Part[], None[]	7 25V
			ANSAKA
Completed: Hour: 10:00 A.M., Day: 15 , M	Month: June	9	, Year: <u>1995</u>
0.5/00.50041/150	Alexan A	1 1/28 set 6 3	1011: with 150 ava
Actual plugging report: 8 5/8" to 204' w/150	sxs cwc. 4	1 1/2" SET G :	ys coment own O.H.
Shots at 1775' - 1220' - 670' - 460' and squeez	ed individual	eith 250 ava	- 500# bulls May
3911' - 4018' - Test 8 5/8" - O.H. 200#. Squee		VICH 250 SXS.	- 500# Hulls. Max.
P.S.I. 900#. Close in 150#.		· · · · · · · · · · · · · · · · · ·	
	·		
Dama wing a			
Remarks:		Anhy.plug: YE	S X NO
Remarks: BAI Condition of casing(in hole): GOOD BAI Rottom plug(in place): YES CALC	D NO	Anhy.plug: YE	S X NO NO YES X , NO
Condition of casing(in hole): GOODBAI Bottom plug(in place): YES, CALC,	NO	Dakota plug:	S X NO YES X , NO GI
Condition of casing(in hole): GOOD BAI	NO	Dakota plug:	YES X NO
Condition of casing(in hole): GOODBAI Bottom plug(in place): YES, CALC, Plugged Through TUBING, CASING	NO Elevat	Dakota plug:	YES X NO
Condition of casing(in hole): GOODBAI Bottom plug(in place): YES, CALC,	NO Elevat	Dakota plug:	YES X NO