4-041586 6-16

TO:	API number: 15 6-20-52
STATE CORPORATION COMMISSION	AFT Mulliper. 13 0-20-32
CONSERVATION DIVISION - PLUGGING	<u>NE NW NW</u> /4 SEC. <u>05</u> , <u>10</u> S, <u>21</u> W
200 COLORADO DERBY BUILDING	4950 feet from S section line
WICHITA, KANSAS 67202	4290 feet from E section line
Operator license#_6931_	Lease_Smith well #_4
Operator: Bowman Oil Company	County Graham
Address: Boy 17	Well total depth 3881 feet
Address: Box 17 Codell, Kansas 67630	Conductor Pine: 0 inch 0 0 feet
	Surface pipe 8 5/8 Inch @ 195 feet
	w/145 sxs.
Aband. oil well X, Gas well, Inp	out well, SWD, D & A
Plugging contractor: Allied Cementing	License# -
Address: <u>Hays, Kansas 67601</u>	
Company to plug at: Hour: 8:00A.M. Day:	16 Month: June Year: 94
Plugging proposal received from: Don E	Jowman
Company, Perman Oil Company	Dh an a c
Company: Bowman Oil Company	Pnone:
Were: <u>5 1/2" casing set @ 3881' w/1</u>	.00 sxs. cement. Perf. at 3555' -
3561'. Anhy. @ 1770'. Holes in casin	g 200' - 900'. Casing squeeze
at 2920' w/200 sxs. and not drilled ou	t. Ordered 250 sxs. 60/40 pozmix -
10% gel with 1/4# F.C. plus 500# hulls	plus 10 sxs. gel.
	M-14
The second secon	
Plugging Proposal Received by: Dennis	L. Hamel
Plugging operations attended by agent?	
	•
Completed: Hour: 1:00P.M., Day: 16, Mo	nth: June , Year: 94
Actual plugging report: R.I.H. with tu	hing to 28001 Snot 25 sys gement
with 100# hulls plus 10 sxs. gel. Pul	1 to 1780'. Spot 75 sxs. cement
with 100# hulls. Pull to 800'. Spot	70 sxs. cement to circulate at
surface. Squeezed 5 1/2" casing to 50	0#. Hooked-up to 8 5/8" -
squeezed S.P. to 500#.	
	(1)
Remarks:	u k
Condition of casing(in hole):GOODB	AD X Anhy.plug:YES X NO
Bottom plug(in place):YES_X_,CALC	,NO Dakota plug:YES ,NO
Plugged through TUBING X , CASING	. Elevation: GL
T diagrama and a second	
i dia mort j observe the p	lugging. Newnis I. Hamel
	lugging. <u>Newnes I Hamel</u>
oate $6-39-94$	